

2008
Shaft Fitting
Addendum

Chapter 4
Archived Shaft Data
Alphabetical Listings by
Manufacturer P-Z

© Copyright 2008 HIREKO GOLF
All rights reserved. May not be reproduced in any form without written consent from Hireko Golf

PARAGON

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
D.K.S. (Dual Kick System) Wood Shafts																		
R	90.1	.335	.598	24.69	22.50	11.33	345.4	214.0	50.6	80.8	254	46	21	2.2	4.32	4.46	43"-M1	87
S	92.0	.336	.599	24.75	22.44	11.40	346.7	214.1	50.6	82.0	260	51	22	2.3	4.41	4.50	43"-M1	90
Lite Touch A&L Combination Flex Wood Shaft																		
L	66.4	.335	.582	24.25	21.38	9.69	319.7	214.8	47.1	57.8	245	41	20	2.1	7.13	7.67	42"-M2	73
A	66.7	.334	.582	24.25	21.94	10.27	325.7	216.2	50.0	59.5	241	39	16	2.4	6.98	7.61	43"-M2	77
Lite Touch A&L Combination Flex Iron Shaft																		
L	61.1	.371	.581	20.19	17.75	6.66	369.7	269.1	47.1	53.5	280	74	51	1.5	5.86	6.21	36.5"	60
A	61.2	.371	.581	20.25	18.44	7.21	374.4	269.4	50.0	55.0	283	75	49	1.5	5.70	6.12	37.5"	64
Lite Touch R&S Combination Flex Wood Shaft																		
R	68.8	.335	.585	24.31	21.94	10.33	326.8	215.7	50.0	61.1	255	46	19	2.4	7.56	7.95	43"-M2	81
S	68.9	.336	.585	24.25	22.00	10.36	327.4	215.7	50.0	61.7	256	48	19	2.5	7.04	7.77	43"-M2	83
Lite Touch R&S Combination Flex Iron Shaft																		
R	66.0	.371	.588	20.63	18.63	7.36	378.1	268.9	50.0	59.2	286	76	51	1.5	5.83	6.01	37.5"	65
S	65.6	.370	.589	20.69	18.75	7.34	377.7	269.1	50.0	58.6	292	79	53	1.5	5.38	5.94	37.5"	68
Low Torque and Low Torque II Wood Shafts																		
L	76.0	.336	.590	23.88	21.88	10.54	335.5	215.6	50.6	69.3	252	49	21	2.3	4.85	-----	42"-M1	81
R	81.8	.335	.598	24.63	21.63	11.06	340.2	214.8	50.6	74.8	252	46	16	2.9	5.39	-----	43"-M1	82
S	86.0	.336	.600	24.50	22.63	11.22	343.2	214.0	50.6	78.6	272	55	25	2.2	5.04	-----	43"-M1	94
Low Torque and Low Torque II Iron Shafts																		
L	70.0	.368	.590	20.13	18.63	7.39	387.5	272.8	50.6	64.1	287	75	51	1.5	4.08	-----	36.5"	62
R	75.4	.369	.592	20.13	19.25	7.81	389.1	269.0	50.6	69.5	299	82	52	1.6	4.07	-----	37.5"	71
S	82.3	.370	.610	21.13	19.63	8.00	393.7	267.8	50.6	75.3	331	94	53	1.8	4.26	-----	37.5"	77
Parasonic Wood Shafts																		
R	91.5	.336	.612	24.75	22.63	11.49	348.3	214.0	50.6	83.7	259	47	22	2.1	3.91	-----	43"-M1	90
S	95.8	.337	.623	25.00	22.75	11.31	345.0	211.7	46.2	87.1	282				3.99	-----	43"-M1	96*
Parasonic Iron Shafts																		
R	81.7	.372	.601	20.63	19.25	8.01	394.2	268.0	50.6	75.6	304	86	54	1.6	3.43	-----	37.5"	74
S	86.1	.370	.603	20.75	19.38	8.10	396.4	265.9	50.6	79.9	326	93	57	1.6	3.35	-----	37.5"	79

PARAGON continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Pro Player's Edition Wood Shaft																		
R	72.2	.336	.585	23.25	22.44	11.68	315.7	195.4	50.6	69.3	251	37	10	3.7	3.39	3.53	45"-BB	93
S	78.0	.334	.591	23.88	22.88	11.90	319.5	194.3	51.0	74.2	264	44	11	4.0	3.33	3.47	45"-BB	100
PV 46 Wood Shafts																		
R	70.5	.336	.592	23.88	22.06	10.46	329.2	214.2	50.2	64.8	244	42	16	2.6	7.16	7.35	43"-M2	76
S	72.6	.336	.597	24.31	22.44	10.56	330.9	214.5	50.2	66.2	250	47	17	2.8	7.75	7.98	43"-M2	79
PV 40 Iron Shafts																		
R	69.2	.373	.597	20.31	18.88	7.57	383.1	269.1	50.2	63.8	293	74	48	1.5	5.12	5.38	37.5"	65
S	69.3	.370	.593	20.25	18.88	7.59	383.6	269.1	50.2	64.3	291	76	48	1.6	5.17	5.42	37.5"	65
Syclone Wood Shafts																		
R	66.6	.335	.855	24.88	23.88	8.96	290.1	198.9	27.9	63.3	261				5.86	6.21	44"-BB	85*
S	72.3	.338	.867	24.88	23.81	9.28	294.5	197.5	27.9	69.1	275				5.87	6.22	44"-BB	90*
Syclone Iron Shafts																		
R	68.1	.372	.862	20.69	19.25	6.14	351.6	261.7	27.9	62.0	305				3.74	4.19	37.5"	67*
S	70.8	.373	.875	20.75	19.31	6.27	354.0	261.3	57.9	64.8	341	89	56	1.6	4.13	4.76	37.5"	76
VST Wood Shafts																		
R	62.4	.332	.580	24.06	22.69	11.14	307.3	198.2	50.6	58.5	250	37	10	3.7	4.13	4.30	45"-BB	90
S	64.0	.332	.582	24.13	22.75	11.25	309.0	198.2	50.6	60.2	258	41	12	3.4	4.12	4.27	45"-BB	94

PENLEY

Bushido Wood Shaft																		
S	75.9	.335	.564	23.06	22.69	11.92	319.8	195.0	50.2	74.6	253	40	13	3.1	7.33	7.49	45"-BB	85
ETA Tour Wood Shaft																		
S	69.0	.334	.601	25.00	23.56	11.52	313.2	198.2	50.6	64.4	261	37	19	1.9	3.79	3.97	45"-BB	98
G2-85 Wood Shaft																		
S	87.3	.331	.619	24.13	21.81	11.01	339.4	210.4	50.2	78.8	253	45	25	1.7	4.41	4.87	43"-M2	89

PENLEY continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Graphite Light Wood Shafts																		
A	69.0	.336	.590	23.00	22.19	11.45	312.1	195.6	50.2	66.3	222	18	11	1.6	6.19	6.49	45"-BB	69
S	77.2	.332	.600	23.31	22.38	11.76	317.1	192.7	50.2	74.2	253	34	18	1.9	6.14	6.45	45"-BB	87
John Daly Wood Shaft																		
R	71.2	.333	.607	23.94	22.88	11.61	314.6	196.1	50.6	67.9	248	32	14	2.3	3.68	3.86	45"-BB	90
Graphite Light 45" R&S Combination Flex Wood Shaft																		
R	73.1	.335	.600	23.25	21.38	10.62	331.9	214.3	50.6	67.0	266				6.31	6.50	43"-M1	83*
S	75.4	.336	.599	23.00	21.19	10.68	333.1	213.2	50.6	69.1	274	51	22	2.3	5.60	6.12	43"-M1	90
Parabolic Wood Shaft																		
A	74.2	.334	.568	23.06	22.63	11.78	317.6	194.4	50.2	73.0	234	31	10	3.1	7.60	7.72	45"-BB	75
R	72.7	.333	.564	23.38	21.44	10.59	331.4	214.3	50.8	66.3	234	39	14	2.8	7.82	8.00	43"-M1	72
Platinum Wood Shafts																		
R	93.2	.334	.580	23.06	21.94	12.05	340.0	201.2	50.6	88.2	242	39	17	2.3	3.74	3.90	44"-M2	87
S	90.1	.334	.580	23.19	22.00	11.94	337.9	202.0	50.6	85.3	251	43	16	2.7	3.26	3.39	44"-M2	92
X	91.0	.333	.586	23.19	22.00	11.96	338.2	201.4	50.6	86.2	258	44	19	2.3	3.20	3.25	44"-M2	96
Stealth 70 Wood Shafts																		
R	71.9	.334	.603	24.06	22.25	11.13	323.6	207.0	50.6	66.0	250	36	14	2.6	4.50	4.58	44"-M2	84
S	73.2	.333	.614	24.19	22.38	11.22	325.0	207.2	50.6	67.2	263	38	14	2.7	4.42	4.50	44"-M2	89
X	73.9	.335	.616	24.44	22.56	11.27	325.7	207.5	50.6	67.6	281	45	21	2.1	4.25	4.43	44"-M2	100
Tour Light Wood Shafts																		
A	64.0	.333	.599	24.81	23.31	11.27	309.2	198.8	50.6	59.8	222	23	6	3.8	4.55	4.72	45"-BB	73
R	63.3	.334	.603	24.75	23.25	11.22	308.5	198.9	50.6	59.0	233	28	11	2.5	4.59	4.66	45"-BB	80
S	68.8	.333	.606	24.50	22.94	11.45	312.0	197.0	50.6	64.4	246	30	14	2.1	4.68	4.78	45"-BB	85
X	64.7	.335	.606	24.88	23.44	11.32	310.1	198.9	50.6	60.6	253	36	14	2.6	4.44	4.59	45"-BB	91

PHOENIXX TPC Formerly Quadrax

Thermo Force Wood Shafts																		
BT20	69.3	.338	.596	22.94	21.84	11.36	310.6	194.4	50.6	65.6	231	27	15	1.8	6.41	6.48	45"-BB	77
BT30	72.1	.337	.604	23.38	22.25	11.54	313.6	194.5	50.6	68.5	242	32	18	1.8	6.29	6.41	45"-BB	83

PHOENIXX TPC continued	Formerly Quadrax
-------------------------------	-------------------------

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Thermo Lite Tour Wood Shafts																		
T1320	66.0	.339	.601	23.25	22.06	11.23	308.6	195.7	50.6	62.3	233	31	17	1.8	6.33	6.55	45"-BB	80
T1330	66.3	.339	.601	23.63	22.44	11.29	309.6	196.4	50.6	62.6	240	33	17	1.9	6.20	6.41	45"-BB	83
Thermo Pro Wood Shafts																		
P1220	62.1	.338	.601	23.50	22.31	11.09	306.5	197.2	50.6	58.7	230	28	13	2.2	6.47	6.58	45"-BB	76
P1230	70.4	.337	.601	23.31	22.13	11.45	312.2	194.6	50.6	67.0	238	32	18	1.8	5.82	5.91	45"-BB	83
Thermo Pro Tour Wood Shafts																		
P1220	T72.8	.338	.611	23.69	22.50	11.59	314.3	195.0	50.6	68.7	233	33	15	2.2	6.02	6.11	45"-BB	81
P1230	T76.5	.340	.605	23.69	22.56	11.78	317.4	194.1	50.6	72.7	250	37	19	1.9	5.91	6.08	45"-BB	89
Thermo Lite Wood Shafts																		
T1320	66.7	.341	.599	23.81	22.50	11.32	310.1	196.4	50.6	63.1	235				6.20	6.47	45"-BB	79*
T1330	63.9	.340	.603	23.63	22.63	11.20	308.3	197.4	50.6	60.3	236				6.63	6.73	45"-BB	78*

POWERFLEX

CPF50 46" A&L Wood Shaft																		
L	88.1	.332	.606	24.38	22.81	11.64	318.8	194.2	42.1	82.5	237	31	9	3.4	7.62	8.23	45"-BB	72
A	88.9	.333	.605	24.38	23.25	12.48	329.5	192.7	51.0	85.8	237	33	12	2.8	7.20	8.13	45"-BB	78
CPF50 46" R&S Wood Shaft																		
R	90.7	.336	.614	25.31	24.31	12.70	333.4	195.4	51.0	87.0	248	37	7	5.3	7.69	8.15	45"-BB	80
S	91.3	.336	.615	25.44	24.31	12.76	334.4	195.2	51.0	88.2	256	40	7	5.7	7.32	8.22	45"-BB	84
CPF5040" A&L Iron Shaft																		
L	82.0	.373	.596	20.31	18.19	7.75	371.6	255.5	42.1	74.0	257	57	30	1.9	4.88		37.5"	52
A	78.1	.367	.595	20.44	19.00	8.50	381.3	257.8	51.0	72.5	254	54	31	1.7	4.74		38.5"	54
CPF50 40" R&S Iron Shaft																		
R	86.9	.369	.606	21.19	19.69	8.87	390.5	258.7	51.0	80.8	277	66	32	2.1	4.99		38.5"	60
S	88.5	.369	.605	21.19	19.75	8.94	392.1	258.4	51.0	82.7	287	71	33	2.2	4.53		38.5"	64

QUADRAX

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
N-Series Wood Shafts																		
1100	73.3	.343	.604	23.50	21.31	10.38	327.7	211.3	50.0	66.4	221	31	14	2.2	6.75	7.08	43"-M2	67
1110	77.3	.341	.610	23.88	21.75	10.59	331.4	211.5	50.0	69.9	229	33	14	2.4	6.97	7.29	43"-M2	69
1120	75.1	.338	.611	23.88	21.56	10.49	329.6	212.0	50.0	67.6	239	38	18	2.1	6.83	7.33	43"-M2	75
1130	79.1	.341	.615	23.94	21.63	10.62	332.0	211.0	50.0	71.0	245	39	19	2.1	6.63	6.81	43"-M2	78
P-Series Wood Shafts																		
1210	66.0	.336	.602	23.56	21.31	10.07	322.2	212.8	50.0	59.4	232	36	14	2.6	5.69	5.94	43"-M2	74
1220	68.9	.336	.602	23.63	21.31	10.18	324.2	212.2	50.0	62.0	240	39	18	2.2	5.39	5.58	43"-M2	78
1230	71.6	.342	.602	23.56	21.25	10.28	326.0	211.8	50.0	64.2	242	40	20	2.0	5.34	5.54	43"-M2	80
1240	70.3	.338	.601	23.69	21.38	10.27	325.8	212.4	50.0	63.4	255	45	21	2.1	5.25	5.54	43"-M2	85
1250	70.1	.337	.602	23.88	21.56	10.25	325.5	212.6	50.0	62.9	261	45	20	2.3	5.21	5.51	43"-M2	86
Thermo-Lite Wood Shafts																		
L	61.1	.337	.594	23.44	20.50	8.74	303.9	210.9	39.8	53.2	220	31	13	2.4	7.17	7.33	42"-M2	62
A	62.5	.336	.594	23.50	21.19	9.92	319.8	213.8	50.0	56.0	227	34	14	2.4	6.37	6.52	43"-M2	71
R	63.3	.338	.593	23.56	21.25	9.97	320.6	213.8	50.0	56.8	233	37	16	2.3	6.19	6.34	43"-M2	74
S	64.1	.337	.598	23.81	21.50	10.00	321.3	213.9	50.0	57.4	244	38	18	2.1	6.16	6.26	43"-M2	78

PRECISION COMPOSITES

Eagle Classic Filament Wound Wood Shafts																		
L	91.2	.335	.591	22.44	20.00	10.65	337.3	208.4	47.3	81.6	240	41	19	2.2	3.70	4.14	42"-M1	78
A	90.2	.338	.610	23.50	21.38	11.30	344.7	212.6	50.6	81.5	247	43	20	2.2	3.74	4.03	43"-M1	85
R	92.3	.330	.593	22.56	20.50	11.31	345.1	209.9	50.6	84.6	264	50	26	1.9	3.26	3.55	43"-M1	96
S	92.7	.333	.610	23.31	21.31	11.33	345.3	210.1	50.6	84.6	269	54	26	2.1	3.12	3.37	43"-M1	99
X	94.4	.334	.601	23.44	21.44	11.49	348.3	211.7	50.6	86.0	282	58	28	2.1	3.01	3.35	43"-M1	106
Eagle Classic Filament Wound Iron Shafts																		
L	87.1	.371	.589	19.56	17.44	7.50	390.3	265.3	47.3	77.7	281	70	47	1.5	2.35	2.61	36.5"	63
A	89.9	.374	.597	19.75	18.06	8.15	397.6	265.7	50.6	81.3	287	73	49	1.5	2.37	2.55	37.5"	69
R	91.0	.365	.597	20.25	18.38	8.17	397.9	265.3	50.6	82.0	296	77	49	1.6	2.60	2.85	37.5"	71
S	91.1	.366	.596	20.06	18.25	8.23	399.8	266.0	50.6	83.2	310	85	53	1.6	2.44	2.71	37.5"	76
X	92.3	.368	.598	20.13	18.25	8.24	400.0	265.6	50.6	83.8	314	86	57	1.5	2.56	2.76	37.5"	78
Flair Filament Wound Wood Shaft																		
L	84.5	.334	.594	22.81	20.38	9.85	322.5	207.2	39.8	75.5	235	38	18	2.1	3.36	3.75	42"-M1	77

PRECISION COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Flair Filament Wound Iron Shaft																		
L	87.4	.369	.591	19.81	17.69	6.97	379.6	261.9	39.8	77.9	267	67	43	1.6	2.11	2.38	36.5"	60
PC Dual Filament Wound Iron																		
S	112.3	.367	.599	20.19	18.69	8.86	416.7	261.8	50.6	104.3	313	86	54	1.6	2.04	2.26	37.5"	79
PC Forty Filament Wound Wood																		
R	88.7	.335	.599	23.00	21.00	11.17	342.1	210.6	50.6	80.9	257	47	22	2.1	3.65	3.96	43"-M1	90
PC Forty Filament Wound Iron																		
R	88.3	.371	.598	20.19	18.31	8.06	395.2	264.5	50.6	80.1	297	78	52	1.5	2.79	3.03	37.5"	72
Statement Filament Wound Wood Shaft																		
A	87.6	.336	.600	22.88	20.88	11.05	340.0	209.3	50.6	80.1	244	39	22	1.8	3.03	3.39	43"-M1	87
Statement Filament Wound Iron Shaft																		
A	89.4	.369	.600	20.13	18.38	8.10	396.3	264.5	50.6	81.2	280	70	44	1.6	2.06	2.27	37.5"	67

RAPPORT COMPOSITES

Advent 45" Wood Shafts																		
L	87.9	.338	.577	22.69	21.25	11.31	330.8	201.0	47.6	82.2	245	37	16	2.3	4.62	4.80	43"-M2	80
A	82.3	.336	.595	22.94	21.81	11.62	332.0	203.2	50.6	78.2	245	36	11	3.3	5.07	5.22	44"-M2	81
R	83.8	.335	.592	22.94	21.88	11.67	332.7	203.2	50.6	78.9	250	36	13	3.0	5.12	5.26	44"-M2	82
S	83.6	.336	.592	22.69	21.63	11.62	332.0	202.6	50.6	78.8	262	41	14	2.9	5.48	5.58	44"-M2	87
Advent 40" Iron Shafts																		
L	86.4	.374	.585	20.25	18.47	8.24	383.6	256.9	47.6	79.1	277	62	43	1.4	2.89	3.23	37.5"	62
A	83.1	.372	.605	20.75	19.31	8.71	386.6	258.6	50.6	77.4	276	62	32	1.9	2.84	3.11	38.5"	62
R	81.6	.372	.605	20.56	19.06	8.64	384.7	258.0	50.6	76.1	286	64	41	1.6	2.92	3.20	38.5"	65
S	84.1	.371	.604	20.56	19.13	8.73	387.0	257.6	50.6	78.8	290	69	40	1.7	3.00	3.27	38.5"	69
Advent Wood Shafts (sheet wrapped model)																		
L	78.2	.334	.583	23.19	20.69	9.81	321.8	210.3	41.8	69.7	252	46	20	2.3	9.19	10.29	42"-M1	73
A	82.7	.335	.595	23.56	21.63	11.00	339.1	213.1	50.6	75.4	254	47	18	2.6	9.31	10.34	43"-M1	77
R	88.7	.333	.603	24.00	21.94	11.27	344.2	212.7	50.6	80.9	275	56	24	2.3	8.83	9.87	43"-M1	87

RAPPORT COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Advent Iron Shafts (sheet wrapped model)																		
L	87.1	.370	.588	19.75	17.81	7.25	383.8	263.3	42.0	78.5	285	77	49	1.6	5.93	6.60	36.5"	60
A	88.3	.368	.591	20.00	18.56	8.16	397.8	265.0	50.6	82.2	284	76	47	1.6	6.82	7.33	37.5"	63
R	90.0	.369	.599	20.13	18.69	8.19	398.7	264.3	50.6	83.8	293	80	47	1.7	6.85	7.42	37.5"	65
Advent II Wood Shafts																		
L	83.3	.332	.598	23.56	20.88	9.90	323.4	208.0	41.8	73.6	246	44	20	2.2	7.20	8.00	42"-M1	73
A	89.0	.335	.603	23.94	21.88	11.28	344.4	212.4	50.6	81.4	259	50	14	3.6	6.58	7.36	43"-M1	82
R	93.9	.334	.610	24.38	22.25	11.51	349.1	212.9	50.6	85.6	277	57	22	2.6	6.68	7.53	43"-M1	91
Blue Velvet Wood Shaft																		
Tour S	72.7	.340	.595	22.63	21.75	11.57	314.1	193.1	51.0	70.0	270	45	18	2.5	3.70	3.85	45"-BB	104
Cirrus Pro Wood Shafts																		
R	64.1	.339	.590	22.38	21.56	11.14	307.2	194.9	50.6	61.7	245	30	17	1.8	3.84	3.90	45"-BB	90
S	66.4	.336	.595	22.56	21.63	11.25	308.9	194.4	50.6	63.9	261	42	21	2.0	3.87	3.92	45"-BB	100
X	68.6	.337	.601	23.06	22.13	11.41	311.5	194.9	50.6	66.0	274	45	23	2.0	3.81	3.85	45"-BB	106
Oracle Plus 46.5" A&L Wood Shafts																		
L	86.5	.336	.593	24.06	21.81	11.20	328.9	203.4	47.6	77.9	242	35	12	2.9	5.17	5.39	43"-M2	75
A	85.5	.334	.593	23.94	22.06	11.68	333.2	203.7	50.6	78.9	240	37	13	2.8	5.00	5.46	44"-M2	81
Oracle Plus 40.5" A&L Iron Shafts																		
L	79.2	.371	.594	20.44	18.25	7.94	376.1	257.5	47.6	71.0	278	63	41	1.5	3.05	3.45	37.5"	62
A	77.2	.370	.592	20.31	18.56	8.39	378.8	257.4	50.6	70.8	276	63	39	1.6	2.92	3.39	38.5"	65
Oracle Plus 46.5" R&S Wood Shafts																		
R	82.5	.335	.588	23.69	21.81	11.52	330.4	203.9	50.6	75.9	257	40	13	3.1	5.69	5.91	44"-M2	85
S	81.8	.335	.590	23.69	21.81	11.49	329.7	203.7	50.6	75.4	261	44	16	2.8	5.52	5.95	44"-M2	89
Oracle Plus 40.5" R&S Iron Shafts																		
R	77.6	.368	.594	20.38	18.63	8.41	379.3	257.2	50.6	71.5	291	71	36	2.0	3.36	3.70	38.5"	68
S	78.9	.372	.597	20.38	18.63	8.45	380.3	257.0	50.6	72.7	298	73	35	2.1	3.13	3.60	38.5"	69
ProWound Wood Shafts																		
R	76.1	.337	.588	23.06	21.50	11.13	323.4	201.8	50.6	71.0	255	40	17	2.4	3.69	3.88	44"-M2	92
S	78.7	.344	.588	23.06	21.56	11.27	325.8	201.7	50.6	73.5	270	44	19	2.3	3.75	3.92	44"-M2	98

RAPPORT COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Cirrus Wood Shafts (1997 model)																		
90	58.3	.333	.577	22.69	22.25	10.79	301.8	194.4	50.0	57.4	237	32	12	2.7	5.31	5.44	45"-BB	81
Cirrus OS .365" Wood Shafts																		
R	63.5	.366	.573	22.06	21.38	11.23	308.7	196.2	50.6	61.9	226	30	18	1.7	5.03	5.06	45"-M2	80
S	67.8	.369	.578	22.31	21.63	11.36	310.7	194.2	50.6	65.9	243	32	22	1.5	4.89	4.99	45"-M2	88
Cirrus Tour Wood Shaft (1997 model)																		
110	67.7	.336	.634	25.19	24.13	11.45	312.0	197.8	50.0	64.2	253				4.25	4.33	45"-BB	92*
Cirrus Tour Wood Shafts																		
X	69.1	.336	.601	24.63	23.50	11.57	314.2	197.9	50.6	65.7	276	43	15	2.9	4.04	4.10	45"-BB	102
XX	68.8	.335	.598	24.56	23.56	11.57	314.1	198.0	50.6	65.5	273	45	17	2.6	4.06	4.09	45"-BB	103
Cirrus Wood Shafts (1996 version)																		
90	51.3	.335	.573	23.25	22.88	10.60	299.2	198.8	51.0	50.4	232	35	13	2.7	5.45	5.50	45"-BB	82
100	53.3	.336	.578	23.50	23.19	10.75	301.4	198.0	51.0	52.4	244	38	7	5.4	5.10	5.15	45"-BB	84
HG Iron Shafts																		
R	98.0	.367	.622	20.88	19.31	8.19	398.7	261.6	46.2	90.9	313	86	49	1.8	2.64	2.84	37.5"	75
S	99.8	.368	.619	20.75	19.50	8.24	400.1	263.1	46.2	92.8	317	84	50	1.7	3.03	3.19	37.5"	75
HG Tapered Iron Shafts																		
R	100.2	.351	.621	20.75	19.25	8.31	401.6	263.2	46.2	92.2	305	81	51	1.6	3.19	3.34	37.5"	72
S	100.0	.351	.625	20.94	19.50	8.34	402.6	264.2	46.2	92.2	314	83	52	1.6	3.23	3.28	37.5"	74
Hyperflex Wood Shafts																		
A	82.5	.336	.599	23.75	21.75	11.00	339.0	213.1	50.6	75.3	255	48	15	3.2	5.48	6.02	43"-M1	83
R	80.4	.335	.601	23.81	21.81	10.94	337.8	213.7	50.6	73.5	261	50	16	3.1	5.39	5.93	43"-M1	86
S	87.2	.333	.606	24.19	22.06	11.24	343.5	213.2	50.6	79.7	274	55	19	2.9	5.46	5.97	43"-M1	91
Hyperflex Iron Shafts																		
A	78.4	.361	.590	20.19	18.81	7.88	390.6	267.1	50.6	72.9	289	78	40	2.0	4.00	4.37	37.5"	65
R	81.7	.368	.594	20.19	18.81	7.98	393.3	266.6	50.6	76.1	300	84	49	1.7	3.77	4.03	37.5"	71
S	82.6	.369	.601	20.38	18.94	8.01	394.0	266.9	50.6	76.5	312	87	49	1.8	3.90	4.25	37.5"	73

RAPPORT COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Hyperflex Plus Wood Shafts																		
R	88.7	.331	.613	24.50	22.38	11.34	345.5	213.9	50.6	81.0	267	52	15	3.5	3.41	3.77	43"-M1	93
S	90.0	.333	.614	24.56	22.44	11.39	346.5	213.9	50.6	82.0	274	54	16	3.4	3.53	3.98	43"-M1	96
X	94.0	.335	.620	24.81	22.69	11.27	344.1	211.2	47.1	85.8	290	60	17	3.5	3.44	3.84	43"-M1	103
Hyperflex Plus Iron Shafts																		
R	84.6	.368	.608	20.69	19.13	8.08	395.9	267.2	50.6	78.1	309	87	49	1.8	2.94	3.20	37.5"	74
S	84.9	.367	.611	20.75	19.25	8.09	396.1	267.2	50.6	78.3	317	89	50	1.8	2.98	3.24	37.5"	76
X	88.1	.367	.610	20.88	19.38	8.21	399.3	267.2	50.6	81.5	333	97	54	1.8	3.20	3.48	37.5"	81
Hyperflex Tour Wood Shafts																		
R	92.9	.337	.607	24.81	23.06	12.02	339.3	203.8	50.6	84.9	272	45	16	2.8	4.30	4.51	44"-M2	95
S	99.4	.338	.615	25.00	23.31	12.30	344.8	203.3	50.6	90.9	282	50	17	2.9	4.22	4.32	44"-M2	101
Hyperflex Tour Wood Shafts (pre 1997 model)																		
R	91.7	.335	.620	24.56	22.44	11.18	342.4	211.8	47.1	83.5	267	52	15	3.5	3.10	3.46	43"-M1	95
S	93.2	.335	.621	24.75	22.63	11.24	343.5	211.5	47.1	84.9	279	55	15	3.7	3.03	3.35	43"-M1	100
X	101.0	.335	.634	25.06	22.88	11.56	349.8	210.7	47.1	92.0	308	68	21	3.2	3.03	3.34	43"-M1	114
Hyperflex Tour Iron Shafts																		
R	83.7	.369	.611	20.38	18.94	7.87	390.4	262.2	50.6	77.6	315	87	56	1.6	2.39	2.58	37.5"	79
S	86.7	.368	.609	20.69	19.25	8.17	397.9	267.1	50.6	80.2	321	93	49	1.9	2.45	2.64	37.5"	79
X	88.1	.370	.614	20.88	19.38	8.21	399.3	267.2	50.6	81.5	332	99	55	1.8	2.93	3.19	37.5"	82
Ni-257 Iron Shafts																		
R	117.5	.371	.601	21.13	18.56	8.97	420.0	265.2	50.2	104.6	302	80	53	1.5	2.90	----	37.5"	73
S	119.6	.372	.600	21.13	18.63	9.03	421.9	264.4	50.2	107.3	313	88	52	1.7	3.06	----	37.5"	76
Ni-256 Taper Iron Shafts																		
R	88.7	.357	.607	19.94	18.56	8.31	401.6	269.0	50.2	82.4	293	77	52	1.5	3.04	----	37.5"	71
S	90.8	.356	.605	19.94	18.63	8.38	403.6	268.6	50.2	84.8	306	82	56	1.5	3.18	----	37.5"	74
Ni-259 Taper Iron Shafts																		
R	117.6	.357	.596	20.25	18.50	9.02	421.6	264.4	50.2	107.0	293	79	59	1.3	2.51	----	37.5"	74
S	118.1	.358	.599	20.38	18.56	9.04	422.0	264.6	50.2	107.2	305	83	62	1.3	2.59	----	37.5"	77

RAPPORT COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Ni-271 Wood Shaft																		
R	93.7	.333	.599	23.38	22.25	12.12	341.4	201.6	50.6	89.2	255	38	16	2.4	5.03	5.10	44"-M2	86
Ni-271 Iron Shafts																		
L	82.4	.372	.598	20.31	17.81	7.10	380.2	267.8	39.7	72.7	278	71	53	1.3	3.31	3.76	36.5"	63
A	81.9	.373	.597	20.25	18.25	7.94	392.1	267.6	50.2	74.3	284	70	48	1.5	3.46	4.11	37.5"	65
R	87.8	.370	.604	20.81	18.69	8.23	399.6	269.5	50.2	79.9	294	78	51	1.5	3.13	3.73	37.5"	70
S	87.6	.372	.602	20.63	18.50	8.22	399.4	269.5	50.2	79.7	301	81	53	1.5	3.22	3.71	37.5"	72
Oracle Wood Shafts (2000-2003 model)																		
R	88.7	.336	.594	22.81	21.75	11.88	336.8	201.8	50.6	84.4	257	40	16	2.5	4.76	4.85	44"-M2	88
S	86.2	.337	.588	22.81	21.81	11.79	335.2	202.4	50.6	82.2	265	44	13	3.4	5.45	5.59	44"-M2	89
Oracle Iron Shafts (2000-2003 model)																		
R	84.0	.372	.602	20.50	19.06	8.72	386.7	257.5	50.6	78.6	291	66	37	1.8	2.90	3.17	38.5"	67
S	84.1	.372	.603	20.56	19.06	8.71	386.5	257.5	50.6	78.4	298	72	41	1.8	2.95	3.35	38.5"	71
Oracle Wood Shafts (pre-2000 model)																		
L	85.0	.331	.591	23.25	20.69	10.06	326.2	208.2	41.8	76.2	251	45	19	2.4	4.24	4.59	42"-M1	81
A	90.9	.333	.592	23.56	21.56	11.33	345.4	211.2	50.6	83.6	251	44	14	3.1	4.14	4.44	43"-M1	84
R	90.2	.337	.586	23.31	21.38	11.28	344.5	210.9	50.6	83.0	261	49	20	2.5	4.22	4.54	43"-M1	90
S	93.4	.336	.596	23.63	21.63	11.43	347.4	210.9	50.6	85.9	274	53	23	2.3	4.17	4.50	43"-M1	96
Oracle Iron Shafts (pre-2000 model)																		
L	76.2	.369	.587	19.31	17.38	6.93	376.0	265.1	42.0	68.9	276	71	52	1.4	3.02	3.29	36.5"	62
A	76.8	.368	.575	19.38	18.00	7.67	385.5	263.6	50.8	71.1	283	71	52	1.4	3.06	3.26	37.5"	68
R	81.6	.368	.579	19.56	18.19	7.81	389.1	262.1	50.8	76.2	294	82	53	1.5	2.99	3.21	37.5"	72
S	79.4	.370	.575	19.38	17.94	7.74	387.3	263.0	50.8	74.1	310	87	54	1.6	3.22	3.43	37.5"	75
Oracle Lite Wood Shafts																		
R	72.3	.339	.593	23.56	22.44	11.28	326.1	207.1	50.6	68.4	254	41	17	2.4	5.80	5.93	44"-M2	85
S	75.1	.340	.598	23.94	22.75	11.43	328.7	207.3	50.6	70.8	260	42	17	2.5	5.72	5.91	44"-M2	88
Oracle Lite Iron Shafts																		
R	79.2	.373	.601	20.31	18.88	8.52	382.0	257.7	50.6	73.7	282	70	35	2.0	3.64	3.94	38.5"	65
S	78.1	.373	.597	20.19	18.81	8.48	380.9	257.7	50.6	72.6	295	76	41	1.9	3.76	4.08	38.5"	70

RAPPORT COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Oracle SGS Plus Wood Shafts																		
R	94.6	.335	.600	23.56	21.63	11.49	348.4	210.7	50.6	87.1	259	47	19	2.5	3.84	4.20	43"-M1	89
S	96.4	.335	.603	23.75	21.75	11.53	349.4	210.4	50.6	88.4	272	52	21	2.5	3.72	4.06	43"-M1	95
X	95.6	.335	.600	23.56	21.63	11.54	349.5	210.3	50.6	88.6	284	58	24	2.4	3.81	4.14	43"-M1	101
Oracle SGS Plus Iron Shafts																		
R	72.4	.369	.565	19.00	17.75	7.57	382.9	264.6	50.8	67.5	288	78	40	2.0	3.70	3.87	37.5"	65
S	74.9	.369	.574	19.25	17.88	7.66	385.2	264.6	50.8	69.8	303	84	50	1.7	3.64	3.87	37.5"	72
X	76.9	.371	.575	19.25	17.88	7.67	385.6	263.4	50.8	71.4	317	91	56	1.4	3.59	3.80	37.5"	77
Recoil Wood Shaft																		
-----	87.6	.335	.605	23.75	21.69	11.21	342.9	212.0	50.6	80.3	239	41	16	2.6	2.97	3.29	43"-M1	85
Recoil Iron Shaft																		
-----	82.6	.370	.600	20.31	18.81	7.98	393.3	265.9	50.6	76.8	272	79	44	1.8	2.05	2.22	37.5"	69
Sceptre Ultralight Wood Shafts																		
L	79.0	.334	.590	23.38	20.81	9.81	321.9	209.8	41.8	70.3	256	48	20	2.4	3.99	4.49	42"-M1	84
A	75.1	.335	.588	23.31	21.38	10.65	332.5	212.9	50.8	68.8	241	41	12	3.4	4.42	4.81	43"-M1	79
R	77.5	.334	.585	23.31	21.38	10.73	334.0	212.2	50.8	71.0	254	47	16	2.9	4.11	4.58	43"-M1	86
Sceptre Ultralight Iron Shafts																		
L	75.2	.369	.579	19.50	17.63	6.94	376.3	266.6	42.0	67.7	292	79	55	1.4	3.24	3.54	36.5"	66
A	74.1	.370	.582	19.75	18.31	7.60	383.8	264.7	50.8	68.3	294	80	46	1.7	3.76	4.00	37.5"	68
R	75.9	.369	.588	20.00	18.50	7.71	386.3	265.5	50.8	70.0	303	82	53	1.5	3.69	3.97	37.5"	72
SL Ultralite .350" Wood Shafts																		
R	68.3	.354	.602	22.63	22.06	11.45	312.1	194.9	50.6	66.6	241	31	21	1.5	3.67	3.74	45"-M2	91
S	67.6	.354	.599	22.50	21.94	11.40	311.3	194.8	50.6	65.9	252	34	21	1.6	3.82	3.87	45"-M2	95
Synsor 46" R&S Combination Wood Shaft																		
R	91.9	.333	.612	24.81	22.13	11.33	345.3	213.2	50.6	81.5	277	56	16	3.5	4.84	5.34	43"-M1	93
S	91.9	.335	.612	24.75	22.06	11.30	344.8	212.0	50.6	82.2	282	56	24	2.3	4.56	5.29	43"-M1	98
Synsor 41" R&S Combination Iron Shaft																		
R	91.3	.370	.610	21.88	19.25	8.20	398.9	268.6	50.6	79.7	308	88	49	1.8	3.65	4.05	37.5"	73
S	91.3	.370	.612	21.81	19.19	8.20	398.8	268.1	50.6	80.1	328	94	54	1.7	3.41	3.90	37.5"	79

RAPPORT COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Synsor 45" Wood Shafts																		
L	77.9	.335	.590	23.38	20.81	9.73	320.4	209.6	41.8	69.0	246	42	16	2.6	5.21	5.85	42"-M1	75
A	79.8	.333	.601	23.75	21.75	10.88	336.7	213.7	50.6	72.4	250	46	17	2.7	5.50	6.10	43"-M1	81
R	87.9	.334	.608	24.00	22.00	11.39	346.5	215.5	50.6	80.4	273	53	21	2.5	4.87	5.43	43"-M1	93
S	90.0	.334	.616	24.50	22.31	11.39	346.4	213.0	50.6	82.8	283	59	18	3.3	5.38	5.96	43"-M1	94
Synsor 39" Iron Shafts																		
L	77.0	.371	.584	19.75	17.81	6.97	377.1	265.6	42.0	69.5	290	77	52	1.5	4.01	4.33	36.5"	64
A	77.9	.371	.592	20.06	18.63	7.82	389.3	266.7	50.6	72.0	287	77	51	1.5	4.20	4.50	37.5"	67
R	80.9	.370	.599	20.38	18.88	7.91	391.4	266.0	50.6	74.8	308	87	52	1.7	3.91	4.14	37.5"	73
S	94.8	.365	.614	21.25	19.69	8.45	405.5	267.5	50.6	87.4	320	89	53	1.7	3.17	3.43	37.5"	77
Synsor Lite Wood Shafts																		
L	64.0	.340	.567	22.31	20.50	10.18	311.0	204.6	47.6	58.8	215	29	16	1.8	8.18	8.49	43"-M2	64
A	67.4	.341	.592	23.75	22.50	11.09	322.5	208.3	50.6	63.6	242	37	14	2.6	7.01	7.19	44"-M2	77
A	63.5	.336	.602	24.00	23.63	11.31	309.8	197.3	50.0	62.5	241	37	9	4.1	6.88	7.12	45"-BB	80
R	62.2	.336	.595	23.81	23.44	11.20	308.3	197.1	50.0	61.2	241	33	9	3.7	6.98	7.26	45"-BB	78
Synsor Lite Iron Shafts																		
L	60.5	.375	.578	18.81	17.44	7.34	362.4	258.7	47.6	56.1	262	59	44	1.3	4.12	4.54	37.5"	58
A	63.0	.374	.587	19.31	18.38	7.98	369.4	258.9	50.6	59.9	279	64	42	1.5	4.73	4.97	38.5"	63
A	63.9	.371	.592	19.50	18.06	7.33	377.3	268.0	50.0	59.3	273	68	48	1.4	4.88	5.27	37.5"	62
R	66.4	.372	.596	19.81	18.38	7.42	379.6	268.3	50.0	61.3	299	80	51	1.6	4.21	4.59	37.5"	69
Tour Profile Parallel Tip Iron Shafts (1995 model, boron reinforced tip)																		
R	86.6	.370	.610	20.88	19.38	8.21	399.2	268.4	50.6	80.2	310	85	46	1.8	2.14	2.29	37.5"	75
S	89.7	.370	.611	20.75	19.25	8.30	401.3	267.8	50.6	82.9	326	92	47	2.0	2.10	2.24	37.5"	80
X	92.2	.371	.617	20.94	19.44	8.08	395.7	264.3	46.2	85.4	336	96	53	1.8	1.99	2.17	37.5"	84
Tour Profile Taper Tip Iron Shafts (1995 model - boron reinforced tip)																		
R	85.0	.352	.604	20.88	19.50	8.14	397.3	268.6	50.6	78.1	301	82	43	1.9	2.18	2.34	37.5"	73
S	88.9	.351	.612	21.06	19.63	8.23	400.9	268.7	50.6	81.6	317	89	47	1.9	2.14	2.24	37.5"	78
X	90.7	.350	.614	21.13	19.56	8.01	394.2	264.9	46.2	83.1	319	88	49	1.8	2.12	2.22	37.5"	79
Tour Profile Parallel Tip Iron Shafts (1994 model - no boron)																		
R	86.7	.370	.599	20.69	19.19	8.15	397.5	267.0	50.6	79.9	303	84	44	1.9	2.09	2.10	37.5"	74
S	89.8	.370	.605	20.94	19.31	8.22	399.5	267.0	50.6	81.9	313	89	46	1.9	2.09	2.09	37.5"	77
X	95.4	.371	.612	21.13	19.56	8.47	405.9	268.1	50.6	87.2	332	97	48	2.0	2.07	2.14	37.5"	82

RAPPORT COMPOSITES continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
------	----------------	----------------	-----------------	-----------	-----------	-----------	-------------------	-----------------	-----------------	------------------	-------------	---------------------	---------------------	-----------	------------------	------------------	-------------------	------

Tour Profile Taper Tip Iron Shafts (1994 model - no boron)

R	84.7	.351	.601	20.75	19.31	8.14	397.3	268.2	50.6	78.5	297	83	42	2.0	2.10	2.16	37.5"	72
S	87.0	.353	.607	21.00	19.56	8.20	398.9	268.2	50.6	80.1	305	87	43	2.0	2.23	2.25	37.5"	74
X	92.4	.352	.615	21.13	19.63	8.35	402.9	267.2	50.6	85.1	327	94	49	1.9	2.15	2.17	37.5"	81

Wasp Tour Wood Shafts

R	103.7	.336	.607	23.88	22.56	11.78	354.4	205.1	51.0	98.3	258				4.02	4.22	43"-BB	
R	103.7	.336	.607	23.88	22.25	11.86	356.1	207.7	51.0	97.4	260	47	17	2.8	3.90	4.22	43"-M2	90
S	101.5	.336	.603	23.94	22.69	11.72	353.1	205.9	51.0	96.2	270				4.37	4.53	43"-BB	
S	101.5	.336	.603	23.94	22.38	11.79	354.8	208.5	51.0	95.3	272	50	17	2.9	4.25	4.53	43"-M2	93

ROYAL PRECISION

Air Rifle 37.5" Iron Shaft

S	97.3	.371	.610	19.06	18.44	8.54	408.0	263.5	51.0	93.5	298	73	48	1.5	1.99	2.05	37.5"	72
---	------	------	------	-------	-------	------	-------	-------	------	------	-----	----	----	-----	------	------	-------	----

Champion Graphite Wood Shafts

L	69.5	.336	.578	22.19	20.69	9.69	319.8	208.0	47.1	64.7	229				6.67	6.74	42"-BB	
L	69.5	.336	.578	22.19	20.44	9.79	321.5	210.5	47.1	63.9	229	35	16	2.2	6.60	6.74	42"-M2	67
R	71.7	.336	.590	23.25	21.81	10.38	327.8	210.7	50.0	67.1	253				5.98	6.19	43"-BB	
R	71.7	.336	.590	23.25	21.50	10.48	329.5	213.4	50.0	66.1	252	43	16	2.7	5.86	6.19	43"-M2	81

CW-6000 Wood Shafts

R	69.4	.337	.593	22.75	20.63	10.12	323.3	210.1	50.0	63.2	237				4.82	5.03	43"-BB	
R	69.4	.337	.593	22.75	20.38	10.23	325.3	212.9	50.0	62.4	236	37	17	2.2	4.78	5.03	43"-M2	78

CW-8000 Wood Shafts

R	84.2	.335	.598	23.69	21.69	10.82	335.8	209.3	50.0	76.5	246				5.41	5.56	43"-BB	
R	84.2	.335	.598	23.69	21.38	10.91	337.4	212.0	50.0	75.4	245	42	14	3.0	5.38	5.56	43"-M2	79
S	86.8	.336	.599	23.63	21.63	10.91	337.5	208.4	50.0	79.1	263				5.21	5.39	43"-BB	
S	86.8	.336	.599	23.63	21.38	11.00	339.2	211.1	50.0	78.1	262	48	17	2.8	5.17	5.39	43"-M2	86

Diamond Rifle Iron Shafts

5.0	124.1	.371	.601	22.13	18.50	8.86	416.7	263.5	50.6	102.6	318	85	53	1.6	1.84	2.14	37.5"	80
5.5	129.0	.369	.604	22.00	18.50	9.01	421.2	263.2	50.6	107.4	327	88	53	1.7	1.74	2.11	37.5"	82
6.0	131.3	.370	.602	22.00	18.50	9.05	422.5	262.6	50.6	109.3	328	89	55	1.6	1.70	2.02	37.5"	83
6.5	136.9	.370	.605	22.25	18.63	9.18	426.1	262.3	50.6	113.2	335	96	55	1.7	1.63	1.95	37.5"	86

ROYAL PRECISION continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
FibreMatch Wood Shafts																		
4.5	96.2	.335	.600	24.00	22.00	11.58	350.3	212.0	51.0	87.3	252	47	16	2.9	3.01	-----	43"-M1	90
5.5	98.0	.333	.600	24.13	22.00	11.70	352.7	212.3	51.0	89.4	262	52	17	3.1	2.89	-----	43"-M1	95
6.5	96.4	.333	.600	24.00	22.06	11.64	351.6	213.0	51.0	87.6	269	53	20	2.7	2.98	-----	43"-M1	97
7.0	98.3	.333	.600	24.00	22.13	11.70	352.7	211.8	51.0	89.9	276	58	20	2.9	3.04	-----	43"-M1	101
7.5	97.8	.332	.601	24.13	22.25	11.68	352.4	212.4	51.0	89.0	281	59	21	2.8	3.20	-----	43"-M1	102
FibreMatrix Wood Shafts																		
5.5	82.9	.339	.602	23.69	21.50	11.95	340.0	214.8	50.6	74.6	262	51	22	2.3	4.62	4.93	43"-M1	90
6.5	89.2	.341	.603	23.81	21.69	11.25	343.9	212.5	51.0	80.4	275	57	25	2.3	4.60	4.89	43"-M1	96
Lightweight Rifle Graphite 46" Wood Shafts (for Drivers)																		
R65	65.7	.334	.605	24.06	22.97	11.32	310.1	197.0	50.6	62.5	247	37	18	2.1	3.83	3.99	45"-BB	93
S65	66.2	.333	.605	24.06	22.94	11.34	310.5	197.2	50.6	62.7	260	43	20	2.2	4.16	4.31	45"-BB	100
X65	69.3	.334	.604	23.75	22.72	11.50	312.9	196.3	50.6	66.0	275	47	25	1.9	3.99	4.10	45"-BB	108
R75	73.7	.334	.604	24.25	23.19	11.76	317.3	196.6	50.6	70.1	246	38	16	2.4	4.54	4.56	45"-BB	90
S75	73.0	.334	.603	24.19	23.00	11.71	316.4	196.3	50.6	69.5	257	42	19	2.2	4.27	4.32	45"-BB	97
X75	76.4	.334	.605	24.31	23.25	11.87	319.0	195.9	50.6	72.5	274	45	21	2.1	4.27	4.29	45"-BB	104
Lightweight Rifle Graphite 45" Wood Shafts (for 3-woods)																		
R65	65.8	.332	.605	23.81	22.72	10.83	318.4	205.5	50.6	62.3	257	39	19	2.1	3.87	3.94	44"-BB	92
S65	65.6	.333	.606	23.63	22.50	10.83	318.3	205.1	50.6	62.6	270	44	23	1.9	3.99	4.04	44"-BB	99
R75	72.6	.335	.605	23.19	22.06	11.05	322.1	202.5	50.6	69.0	255	39	23	1.7	4.01	4.05	44"-BB	94
S75	73.2	.334	.604	23.25	22.15	11.10	322.9	202.8	50.6	69.5	272	44	26	1.7	3.86	3.91	44"-BB	102
Lightweight Rifle Graphite 44" Wood Shafts (for 5 and 7 woods)																		
R65	63.4	.334	.606	23.00	21.94	10.15	323.8	213.2	50.6	60.0	267	49	25	2.0	3.78	3.89	43"-BB	97
S65	64.8	.332	.606	23.00	21.94	10.22	324.9	213.0	50.6	61.3	276	52	27	1.9	3.83	3.92	43"-BB	101
R75	75.9	.334	.606	22.69	21.66	10.67	332.7	210.0	50.6	72.1	266	46	23	2.0	4.11	4.25	43"-BB	94
S75	73.2	.334	.604	23.28	22.19	10.65	332.4	212.1	50.6	69.7	283	53	25	2.1	4.18	4.27	43"-BB	101
Lightweight Rifle Graphite 38" Iron Shaft																		
R75	71.9	.370	.604	19.56	19.09	8.38	378.6	258.1	50.6	69.9	297	75	46	1.6	3.96	4.09	38.5"	71

ROYAL PRECISION continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Microtaper 46" A&L Combination Flex Wood Shaft																		
L	115.4	.335	.561	24.44	21.88	11.40	352.6	203.0	47.3	102.3	238				3.41	3.61	42"-BB	
L	115.4	.335	.561	24.44	21.63	11.48	354.4	206.0	47.3	101.1	240				3.34	3.61	42"-M2	
L	-----	-----	-----	-----	21.44	11.44	353.6	207.4	47.4	98.8	240	40	15	2.7	3.25	-----	42"-M1	78
A	116.0	.334	.560	24.38	22.44	12.09	360.9	203.4	51.1	106.4	236				3.36	3.62	42"-BB	
A	116.0	.334	.560	24.38	22.13	12.17	362.7	206.4	51.1	105.2	238	35	13	2.7	3.26	3.62	42"-M2	81
A	-----	-----	-----	-----	21.94	12.10	361.3	207.7	50.8	102.8	240	38	13	2.9	3.17	-----	42"-M1	82
Microtaper 40" A&L Combination Flex Iron Shaft																		
L	117.7	.370	.559	20.25	17.75	8.31	416.1	268.2	49.2	98.7	282	76	48	1.6	2.06	-----	36.5"	66
A	117.6	.369	.553	20.25	18.31	9.00	420.8	262.0	52.6	106.2	274	72	47	1.5	2.02	-----	37.5"	68
Microtaper 47" R&S Combination Flex Wood Shaft																		
R	119.1	.333	.599	25.00	22.56	12.09	361.0	203.9	51.0	106.1	245				3.27	3.49	43"-BB	
R	119.1	.333	.599	25.00	22.25	12.17	362.7	206.9	51.0	104.8	247	42	13	3.2	3.20	3.49	43"-M2	86
R	120.6	.334	.598	25.00	21.81	12.40	367.6	211.6	50.8	105.2	251	46	15	3.0	2.91	-----	43"-M1	89
S	119.3	.334	.600	25.00	22.56	12.16	362.2	203.4	51.0	107.8	258				3.09	3.48	43"-BB	
S	119.3	.334	.600	25.00	22.19	12.30	363.9	206.2	51.0	106.7	260				2.94	3.48	43"-M2	94*
S	120.1	.333	.600	25.00	21.75	12.40	367.6	210.4	50.8	106.4	259	50	17	2.9	2.70	-----	43"-M1	95
Microtaper 41" R&S Combination Flex Iron Shaft																		
R	119.4	.370	.601	20.38	18.00	8.88	417.3	262.3	50.8	104.2	287	78	49	1.6	1.95	-----	37.5"	72
S	119.4	.369	.601	20.38	18.19	8.86	416.9	262.5	50.8	103.6	298	83	51	1.6	1.84	-----	37.5"	76
Microtaper 45" A&L Combination Flex Reinforced Tip for Metal Wood Shaft																		
L	118.6	.335	.560	22.63	20.69	11.79	364.3	207.8	49.3	107.2	243	42	18	2.3	2.95	-----	42"-M1	82
A	118.9	.335	.560	22.63	21.94	12.24	364.1	205.9	53.2	111.3	242	42	16	2.6	2.90	-----	43"-M1	86
Microtaper 45" R&S Combination Flex Reinforced Tip for Metal Wood Shaft																		
R	124.2	.333	.601	23.13	21.25	12.57	369.2	205.3	50.8	113.1	252	48	19	2.5	2.66	-----	43"-M1	93
S	124.2	.334	.600	23.13	21.25	12.57	369.2	204.9	50.8	113.5	261	53	21	2.5	2.54	-----	43"-M1	98
Phoenix 46" A&L Combination Flex Wood Shaft																		
L	114.9	.335	.560	24.25	21.13	11.65	361.0	212.0	49.3	99.7	249				2.92	-----	42"-M1	87*
A	114.3	.335	.558	24.25	21.81	12.27	364.8	208.2	53.2	103.4	244	43	17	2.5	2.85	-----	43"-M1	87

ROYAL PRECISION continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Phoenix 40" A&L Combination Flex Iron Shaft																		
L	113.7	.369	.560	19.75	17.56	8.31	416.1	268.2	49.2	98.7	302	83	58	1.4	1.80	-----	36.5"	73
A	113.2	.369	.561	19.88	18.13	8.85	416.5	262.5	53.2	100.8	294	80	54	1.5	1.81	-----	37.5"	76
Phoenix 47" R&S Combination Flex Wood Shaft																		
R	120.8	.333	.600	24.88	21.94	12.29	365.3	208.8	50.8	105.7	243	46	15	3.1	2.92	-----	43"-M1	87
S	120.1	.332	.601	25.00	21.94	12.30	365.5	208.3	50.8	106.4	252	48	16	3.0	2.75	-----	43"-M1	92
Phoenix 41" R&S Combination Flex Iron Shaft																		
R	118.0	.370	.601	19.88	17.69	8.75	413.7	259.9	50.8	103.0	298	83	53	1.6	1.77	-----	37.5"	77
S	117.5	.370	.602	19.88	17.69	8.73	413.1	260.8	50.8	101.5	304	88	56	1.6	1.69	-----	37.5"	80
Precision FCM Wood Shafts																		
3.5	107.3	.334	.600	23.00	21.25	11.56	359.1	215.7	51.5	91.9	243	44	15	2.9	3.18	-----	42"-M1	81
4.0	107.4	.334	.601	23.25	21.75	11.93	357.6	210.3	51.0	96.3	245	39	14	2.8	3.10	-----	43"-M1	84
4.5	109.1	.334	.599	23.38	21.81	12.01	359.1	209.8	51.0	98.3	250	43	15	2.9	2.92	-----	43"-M1	88
5.0	109.9	.335	.601	23.50	21.75	12.05	360.0	209.1	51.0	99.9	255	43	17	2.5	2.87	-----	43"-M1	90
5.5	120.0	.335	.602	24.13	22.28	12.20	363.3	201.7	51.0	110.6	262				2.86	2.99	43"-BB	
5.5	120.0	.335	.602	24.13	22.00	12.29	365.2	204.7	51.0	109.5	264	46	17	2.7	2.84	2.99	43"-M2	95
5.5	114.9	.333	.600	23.56	21.81	12.22	363.9	208.6	51.0	104.3	262	48	17	2.6	2.87	-----	43"-M1	93
6.0	117.2	.334	.601	23.75	21.81	12.34	366.4	208.2	51.0	107.2	267	50	20	2.5	2.59	-----	43"-M1	98
6.5	125.3	.334	.601	23.50	21.88	12.55	370.9	207.3	51.0	112.8	271	50	20	2.5	2.51	-----	43"-M1	100
6.5	124.9	.334	.597	24.19	22.38	12.38	367.1	201.0	51.0	115.1	271				2.67	2.91	43"-BB	
6.5	124.9	.334	.597	24.19	22.06	12.46	368.7	204.0	51.0	113.7	271	47	19	2.5	2.65	2.91	43"-M2	99
7.0	127.6	.334	.602	23.63	21.88	12.65	373.4	206.7	51.0	115.7	277	56	21	2.7	2.40	-----	43"-M1	105
7.5	132.2	.334	.601	23.63	21.88	12.80	376.8	205.7	51.0	120.1	285	59	24	2.5	2.25	-----	43"-M1	110
Precision FCM Iron Shafts																		
3.5	111.0	.368	.597	20.56	17.25	7.56	391.8	258.0	39.8	94.0	304	78	58	1.3	1.88	2.13	36.5"	72
4.0	113.1	.367	.598	20.75	17.88	8.55	408.1	259.7	50.6	97.8	298	78	50	1.6	1.89	2.05	37.5"	74
4.5	113.9	.367	.599	20.75	18.06	8.59	409.5	259.7	50.6	99.2	304	78	54	1.4	1.85	2.00	37.5"	76
5.0	114.8	.367	.597	20.13	18.06	8.73	413.1	259.1	50.6	103.4	308	83	54	1.5	1.77	1.91	37.5"	79
5.5	117.6	.367	.600	20.13	18.13	8.82	415.5	259.0	50.6	105.9	313	86	57	1.5	1.74	1.85	37.5"	81
6.0	122.0	.369	.602	20.06	18.19	8.91	418.2	258.1	50.6	109.5	319	87	59	1.5	1.65	1.79	37.5"	83
6.5	124.4	.368	.600	20.06	18.31	9.06	422.6	258.5	50.6	113.5	324	92	60	1.5	1.61	1.78	37.5"	86
7.0	129.0	.368	.601	20.06	18.38	9.17	425.9	258.1	50.6	117.2	329	93	62	1.5	1.56	1.73	37.5"	87
7.5	129.2	.367	.599	20.13	18.44	9.24	427.9	259.0	50.6	118.3	334	96	63	1.5	1.53	1.66	37.5"	89

ROYAL PRECISION continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Precision FCM Lite Iron Shafts																		
4.5	91.1	.367	.601	19.13	17.38	8.32	401.9	262.8	51.6	87.5	293	74	52	1.4	1.95	-----	37.5"	72
5.5	100.0	.368	.600	18.88	17.63	8.49	406.5	261.2	51.6	93.7	303	81	58	1.4	1.67	-----	37.5"	79
6.5	103.4	.367	.601	19.25	17.75	8.64	410.6	261.2	51.6	97.8	315	85	64	1.3	1.64	-----	37.5"	83
7.0	104.7	.368	.621	19.00	17.56	8.33	402.3	255.8	47.8	98.7	323	87	63	1.4	1.56	-----	37.5"	85
7.5	111.6	.369	.620	18.88	17.75	8.48	406.3	254.6	47.8	103.9	329	88	64	1.4	1.57	-----	37.5"	86
Precision Lite 46" A&L Combination Wood Shaft																		
A	117.1	.334	.556	24.19	21.88	12.24	364.1	207.7	50.6	105.8	236	39	13	3.0	3.24	3.58	43"-M2	82
Precision Lite 47" R&S Combination Wood Shaft																		
R	119.8	.333	.600	24.88	22.00	12.21	363.4	207.6	50.6	105.2	246	40	13	3.1	3.10	3.42	43"-M2	85
S	120.4	.334	.600	24.84	21.94	12.25	364.2	206.5	50.6	107.1	258	45	17	2.6	2.88	3.36	43"-M2	93
Precision Lite 42" A&L Combination Iron Shaft																		
A	118.3	.369	.558	20.88	17.94	8.71	412.6	262.1	50.6	99.9	292	77	50	1.5	1.96	2.31	37.5"	73
Precision Lite 43" R&S Combination Iron Shaft																		
R	126.0	.367	.598	21.63	18.13	8.85	416.6	262.0	50.6	104.0	300	78	50	1.6	1.92	2.24	37.5"	74
S	126.3	.367	.598	21.63	18.13	8.87	417.0	262.0	50.6	104.4	311	83	53	1.6	1.80	2.25	37.5"	80
Precision Select LFA 46" A&L Combination Flex Wood Shaft																		
L3	115.5	.334	.560	24.25	21.25	11.51	355.0	207.3	47.3	100.4	240				3.22	3.52	42"-M1	83*
A3	115.5	.334	.560	24.31	21.81	12.16	362.4	207.8	50.8	103.8	238	40	15	2.7	3.19	3.61	43"-M1	83
Precision Select LFA 40" A&L Combination Flex Iron Shaft																		
L3	115.2	.367	.560	20.13	17.75	8.16	408.3	260.8	47.3	100.2	287				2.15	2.40	36.5"	68*
A3	115.1	.368	.559	20.13	18.31	8.77	414.3	260.5	50.8	103.0	283	73	45	1.6	2.14	2.36	37.5"	69
Precision Select MFA 47" R&S Combination Flex Wood Shaft																		
R3	121.2	.334	.599	25.06	21.94	12.25	364.4	208.2	50.6	105.6	254	45	16	2.8	3.01	3.30	43"-M1	90
S4	121.0	.334	.600	25.00	21.81	12.30	365.4	207.6	50.6	107.2	265	48	17	2.8	2.74	3.29	43"-M1	95
Precision Select MFA 41" R&S Combination Flex Iron Shaft																		
R3	118.2	.368	.601	20.00	17.44	8.61	409.8	256.4	50.6	102.8	308	80	55	1.5	1.85	2.02	37.5"	77
S4	118.3	.367	.600	20.00	17.81	8.66	411.0	258.4	50.6	102.0	318	85	57	1.5	1.79	2.02	37.5"	81

ROYAL PRECISION continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Precision SuperLite 41" Iron Shaft																		
R	102.2	.370	.601	20.19	17.69	8.32	401.9	262.7	50.6	88.6	298	75	50	1.5	1.97	2.19	37.5"	73
S	107.3	.370	.600	20.19	17.69	8.46	405.7	262.3	50.6	92.8	306	77	53	1.5	1.84	2.06	37.5"	76
Pro Pel II 46" A&L Combination Flex Wood Shaft																		
L	125.7	.334	.561	24.25	21.13	11.96	368.1	210.0	49.3	108.8	236	42	18	2.3	2.97	-----	42"-M1	81
A	125.8	.334	.559	24.38	21.81	12.68	373.9	207.3	53.2	113.4	235	41	16	2.6	2.91	-----	43"-M1	83
Pro Pel II 40" A&L Combination Flex Iron Shaft																		
L	125.6	.369	.560	20.13	17.75	8.54	423.0	264.5	49.2	109.3	284	76	53	1.4	1.97	-----	36.5"	68
A	124.7	.370	.560	20.00	18.06	9.17	425.8	261.4	53.2	111.2	281	75	51	1.5	1.94	-----	37.5"	71
Pro Pel II 47" R&S Combination Flex Wood Shaft																		
R	131.0	.335	.600	25.00	22.00	12.61	372.3	206.7	50.8	114.8	249	46	19	2.4	2.73	-----	43"-M1	91
S	130.2	.334	.599	25.00	21.88	12.62	372.6	205.7	50.8	115.7	259	51	20	2.6	2.58	-----	43"-M1	96
Pro Pel II 41" R&S Combination Flex Iron Shaft																		
R	130.5	.372	.600	20.50	18.06	9.10	423.7	258.7	50.8	114.2	301	85	57	1.5	1.71	-----	37.5"	79
S	132.7	.370	.601	20.63	18.06	9.17	425.8	259.0	50.8	116.0	313	90	59	1.5	1.61	-----	37.5"	83
Rifle Graphite Wood Shafts (49" filament wound version)																		
5.0	89.3	.333	.605	24.31	21.44	11.41	328.3	200.0	50.2	78.1	252				4.79	5.27	44"-M2	86*
6.0	89.9	.332	.603	24.31	21.44	11.46	329.1	199.9	50.2	79.0	263				5.21	5.62	44"-M2	89*
Rifle Graphite Wood Shafts (original 46" length)																		
4.0	80.3	.333	.603	23.13	21.06	10.80	335.5	212.0	50.2	73.3	244	40	22	1.8	4.29	5.19	43"-M2	84
5.0	81.0	.331	.602	22.94	20.94	10.84	336.0	211.7	50.2	74.1	247	42	24	1.8	4.93	4.46	43"-M2	84
6.0	81.6	.334	.600	22.75	20.81	10.82	335.8	210.6	50.2	75.0	255	46	25	1.8	4.27	4.79	43"-M2	90
7.0	86.8	.333	.606	22.94	21.00	11.03	339.6	209.8	50.2	79.6	271	52	29	1.8	4.58	4.52	43"-M2	97
Rifle Lite Wood Shafts																		
5.0	113.6	.333	.599	23.56	21.06	11.83	355.4	204.0	50.2	101.2	263	41	22	1.9	2.92	3.20	43"-M2	95
5.5	112.8	.333	.598	22.88	20.94	11.90	356.8	203.5	50.2	103.1	268	49	17	2.9	2.71	3.08	43"-M2	98
6.0	115.6	.333	.601	23.06	21.13	12.02	359.5	203.4	50.2	105.9	274				2.74	3.02	43"-M2	101*
6.5	117.8	.334	.601	23.13	21.19	12.10	361.2	203.1	50.2	107.9	277	52	20	2.6	2.65	2.92	43"-M2	103

ROYAL PRECISION continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Rifle Lite Iron Shafts																		
5.0	113.4	.367	.598	19.88	17.50	8.61	409.8	259.2	50.2	100.4	319	88	62	1.4	1.76	1.91	37.5"	84
5.5	112.4	.369	.598	19.63	17.50	8.62	410.3	259.1	50.2	101.0	322	86	62	1.4	1.68	1.81	37.5"	84
6.0	120.2	.370	.599	20.13	17.63	8.78	414.6	258.3	50.2	106.1	327	88	61	1.4	1.67	1.81	37.5"	84
6.5	121.5	.368	.597	20.25	17.88	8.85	416.6	259.1	50.2	107.3	330	84	62	1.4	1.66	1.85	37.5"	84
Rifle (Steel) Wood Shafts																		
4.5	109.0	.333	.598	23.69	21.94	11.91	357.3	205.3	51.0	101.0	247	40	16	2.5	3.16	3.33	43"-M2	86
5.5	122.5	.332	.597	24.19	22.06	12.33	365.9	203.2	51.0	111.7	266	44	17	2.6	2.80	2.96	43"-M2	95
6.0	126.2	.331	.599	23.75	21.88	12.48	369.3	201.8	51.0	116.5	273	47	19	2.5	2.64	2.87	43"-M2	99
6.5	130.5	.333	.597	24.13	22.06	12.64	373.1	202.9	51.0	119.2	274	50	20	2.5	2.64	2.85	43"-M2	101
7.0	130.3	.331	.599	23.88	21.94	12.61	372.2	201.6	51.0	119.6	276	52	21	2.5	2.62	2.81	43"-M2	102
Rifle Weight Series Iron Shafts																		
R3	119.1	.370	.580	18.94	17.94	9.08	423.3	259.2	51.2	112.9	292	75	54	1.4	1.83	1.87	37.5"	74
S3	124.0	.369	.598	19.25	18.13	9.21	426.9	260.0	50.2	116.7	318	86	59	1.5	1.59	1.66	37.5"	83
X1	125.1	.368	.598	18.84	17.88	9.16	425.1	256.7	50.2	118.7	325				1.58	1.63	37.5"	85*
Sabre Wood Shafts																		
R	84.9	.335	.602	23.63	21.94	10.90	337.2	207.7	51.0	78.5	258				4.73	4.84	43"-BB	
R	84.9	.335	.602	23.63	21.69	10.97	338.5	210.1	51.0	77.4	258	45	18	2.5	4.71	4.84	43"-M2	86
S	85.3	.335	.598	23.56	21.88	10.88	336.9	207.0	51.0	78.9	270				4.82	4.92	43"-BB	
S	85.3	.335	.598	23.56	21.63	10.99	338.8	209.8	51.0	78.0	268	50	20	2.5	4.80	4.92	43"-M2	91
Super Champion Graphite Wood Shafts																		
A	62.8	.335	.598	23.94	22.38	10.94	304.2	195.8	50.0	58.4	230	32	9	3.6	6.19	6.26	45"-BB	76
R	64.0	.335	.601	24.25	22.69	11.05	305.9	196.0	50.0	59.9	236	34	9	3.8	6.11	6.25	45"-BB	79
UCV-2000 Wood Shafts																		
L	95.3	.335	.561	22.25	20.81	10.76	339.5	203.7	47.1	88.7	229				3.58	3.74	42"-BB	
L	95.3	.335	.561	22.25	20.56	10.85	341.4	207.0	47.1	87.3	230	35	14	2.5	3.47	3.74	42"-M2	74
A	95.9	.334	.601	23.13	21.56	11.31	345.0	205.8	50.0	89.2	223				3.77	3.97	43"-BB	
A	95.9	.334	.601	23.13	21.31	11.39	346.5	208.7	50.0	87.8	225	32	11	2.9	3.67	3.97	43"-M2	74
R	96.2	.335	.601	22.88	21.44	11.31	345.0	205.2	50.0	89.8	233				3.58	3.64	43"-BB	
R	96.2	.335	.601	22.88	21.19	11.39	346.3	207.6	50.0	88.7	234	36	12	3.0	3.52	3.64	43"-M2	79
S	97.2	.335	.602	23.00	21.50	11.34	345.6	205.2	50.0	90.4	241				3.28	3.41	43"-BB	
S	97.2	.335	.602	23.00	21.19	11.43	347.3	208.0	50.0	89.3	242	39	14	2.8	3.23	3.41	43"-M2	84

ROYAL PRECISION continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
UCV-2000 Iron Shafts																		
L	94.1	.369	.561	19.38	17.50	7.69	395.2	264.4	47.1	83.7	275	71	45	1.6	2.41	2.64	36.5"	62
A	94.1	.368	.601	19.50	17.63	8.06	395.3	261.7	50.0	83.6	266	62	40	1.6	2.65	2.78	37.5"	61
R	95.6	.370	.605	19.75	17.63	8.09	396.1	261.7	50.0	84.4	277	69	43	1.6	2.34	2.51	37.5"	65
S	95.2	.371	.603	19.56	17.50	8.05	395.0	261.0	50.0	84.0	285	67	46	1.5	2.29	2.37	37.5"	67

UCV-304 Wood Shafts

R	102.1	.335	.600	24.13	22.63	12.08	360.7	213.9	50.8	96.0	252	48	15	3.2	2.95	-----	43"-M1	90
R	102.1	.336	.601	24.50	22.63	12.09	360.9	213.6	50.8	96.5	255	49	15	3.3	2.94	-----	43"-M1	91
S	109.1	.333	.599	23.88	22.25	12.40	367.7	213.7	50.8	102.8	266	52	19	2.7	2.63	-----	43"-M1	98
S	108.9	.334	.602	23.88	21.81	12.38	367.2	213.6	50.8	102.8	267	51	20	2.6	2.60	-----	43"-M1	98

UCV-304 Iron Shafts

R	102.5	.370	.601	18.87	17.06	8.52	407.4	262.8	50.8	93.8	298	79	58	1.4	1.72	-----	37.5"	78
R	102.1	.371	.599	18.75	17.31	8.51	407.1	262.2	50.8	94.1	301	80	58	1.4	1.73	-----	37.5"	78
S	107.4	.369	.600	19.88	17.50	8.70	412.3	261.7	50.8	99.8	311	82	64	1.3	1.60	-----	37.5"	82
S	107.5	.370	.600	19.00	17.50	8.69	412.1	261.7	50.8	99.6	312	84	63	1.3	1.59	-----	37.5"	82

SK FIBER

Formerly known as FIBER-X

AH40 Professional Wood Shafts

R	94.4	.335	.609	24.75	23.13	11.43	347.4	209.4	51.0	87.0	250				2.66	2.77	43"-BB	
R	94.4	.335	.609	24.75	22.88	11.50	348.7	212.1	51.0	85.6	249	43	14	3.1	2.65	2.77	43"-M2	90
S	99.4	.335	.621	25.13	23.50	11.30	344.7	207.4	46.0	91.3	266				2.79	2.85	43"-BB	
S	99.4	.335	.621	25.13	23.25	11.40	346.8	210.9	46.0	89.9	266	49	18	2.7	2.78	2.85	43"-M2	98

AH40 2.0 Wood Shafts (pre 1996 version)

R	93.2	.332	.606	25.00	22.81	11.49	348.3	214.3	50.8	83.2	250	46	16	2.9	2.64	-----	43"-M1	91
S	102.1	.332	.619	25.13	23.06	11.83	355.5	213.3	50.8	91.4	275	54	23	2.3	2.69	-----	43"-M1	103

AH30 X-Calibur Taper Tip Iron Shafts

R	82.0	.356	.602	21.25	19.13	7.91	391.6	268.0	51.0	72.6	290	78	52	1.5	2.49	2.67	37.5"	72
S	85.3	.355	.608	21.63	19.44	8.06	395.3	268.7	51.0	75.6	308	86	52	1.7	2.54	2.63	37.5"	76

AM40 UltraLite Wood Shafts

A	75.6	.335	.576	24.25	22.19	10.79	335.0	215.5	50.8	68.7	240	43	18	2.4	3.71	-----	43"-M1	83
R	77.9	.334	.584	24.50	22.44	10.90	337.1	216.1	50.8	70.2	252	46	21	2.2	3.58	-----	43"-M1	89
S	83.2	.337	.590	24.94	22.69	11.11	341.0	215.1	50.8	75.1	270	54	24	2.3	3.54	-----	43"-M1	97

SK FIBER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
AT40 Tour Styx Wood Shafts																		
S	95.5	.334	.601	25.00	23.50	11.53	349.4	210.0	51.0	88.4	265				2.72	2.77	43"-BB	
S	95.5	.334	.601	25.00	23.25	11.60	350.8	212.9	51.0	86.9	264	51	20	2.6	2.71	2.77	43"-M2	98
X	104.9	.336	.605	24.94	23.56	11.93	357.5	208.7	51.0	97.8	279				2.33	2.43	43"-BB	
X	104.9	.336	.605	24.94	23.31	11.98	358.7	211.3	51.0	96.4	279	54	24	2.3	2.33	2.43	43"-M2	108
AT40 Tour Styx Iron Shafts																		
S	110.0	.371	.616	21.13	19.31	8.50	406.7	261.1	46.0	99.6	314	87	47	1.9	1.94	2.00	37.5"	78
X	111.7	.369	.622	21.38	19.56	8.62	410.1	263.5	46.0	100.6	330	94	51	1.8	1.91	1.96	37.5"	83
BH35 Championship Wood Shafts																		
R	96.8	.335	.617	24.94	23.31	11.21	343.1	208.0	46.0	89.1	252				3.03	3.11	43"-BB	
R	96.8	.335	.617	24.94	23.06	11.27	344.2	210.6	46.0	87.6	251	44	15	2.9	3.02	3.11	43"-M2	89
S	99.5	.336	.620	25.13	23.56	11.34	345.7	208.2	46.0	91.5	268				2.95	2.98	43"-BB	
S	99.5	.336	.620	25.13	23.25	11.40	346.7	210.6	46.0	90.1	266	50	18	2.8	2.93	2.98	43"-M2	97
BH35 2.5 Wood Shafts (pre 1996 version)																		
R	92.6	.332	.603	24.94	22.75	11.43	347.4	213.8	50.8	82.8	250	46	19	2.4	2.99	-----	43"-M1	90
S	98.8	.334	.608	25.31	23.13	11.72	353.3	214.2	50.8	88.3	274	56	22	2.5	2.97	-----	43"-M1	101
BH30 Augusta Wood Shafts																		
R	93.4	.332	.609	24.94	23.38	11.43	347.3	210.1	51.0	86.2	252				3.78	3.89	43"-BB	
R	93.4	.332	.609	24.94	23.13	11.50	348.7	212.9	51.0	84.8	250	44	15	2.9	3.76	3.89	43"-M2	86
S	97.4	.336	.609	25.00	23.44	11.58	350.5	209.6	51.0	89.9	265				3.62	3.73	43"-BB	
S	97.4	.336	.609	25.00	23.13	11.67	352.1	212.6	51.0	88.5	263	51	17	3.0	3.59	3.73	43"-M2	93
BH30 Augusta 40" Iron Shafts																		
R	87.6	.372	.609	21.38	19.13	8.10	396.4	267.9	51.0	77.5	289	77	47	1.6	2.66	2.77	37.5"	69
S	89.0	.368	.611	21.56	19.38	8.17	398.0	268.6	51.0	78.4	300	82	50	1.6	2.72	2.86	37.5"	73
BH30 3.0 Wood Shafts (pre 1996 version)																		
R	92.1	.333	.607	25.13	23.00	11.41	347.1	213.9	50.8	82.4	253	48	17	2.8	3.56	-----	43"-M1	88
S	98.4	.331	.618	25.25	23.13	11.72	353.1	214.1	50.8	88.2	271	55	22	2.5	3.66	-----	43"-M1	97
BH30 2.5 39" Iron Shafts (pre 1996 version)																		
R	83.1	.369	.608	21.25	19.63	8.05	394.8	268.4	50.8	75.6	289	72	45	1.6	2.86	-----	37.5"	67
S	90.4	.372	.613	21.25	19.69	8.30	401.5	267.9	50.8	82.8	305	85	50	1.7	2.84	-----	37.5"	74

SK FIBER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Big Bulge Wood Shafts																		
A	70.0	.336	.607	24.13	23.00	10.58	331.3	215.2	50.0	66.1	229	33	11	3.0	5.07	5.71	43"-M2	71
R	72.1	.333	.613	24.38	23.19	10.77	334.9	216.7	50.0	68.2	253	41	17	2.4	4.91	5.52	43"-M2	83
S	75.4	.338	.618	24.31	23.13	10.87	336.4	215.1	50.0	71.3	270	49	17	2.9	4.81	5.34	43"-M2	90
Big Bulge Iron Shafts																		
A	74.7	.370	.590	20.31	19.13	7.80	388.7	269.4	50.0	69.3	279	71	43	1.7	3.97	5.26	37.5"	63
R	77.7	.373	.595	20.50	19.31	7.91	391.4	269.6	50.0	71.8	291	78	45	1.7	3.89	5.19	37.5"	67
S	82.2	.373	.601	20.56	19.31	8.05	394.8	268.7	50.0	76.1	307	83	52	1.6	3.93	4.46	37.5"	72
Big T 811 Wood Shafts (formerly known as Tornado BB30 811 Wood Shafts)																		
L	62.5	.336	.813	25.88	23.50	8.33	283.3	200.0	27.9	55.4	243				5.51	5.57	43"-BB	78*
A	64.5	.332	.815	25.94	24.25	8.79	287.7	200.6	27.9	59.2	254				5.87	5.89	44"-BB	83*
R	62.9	.331	.814	26.31	24.63	8.73	287.0	201.6	27.9	57.5	272				4.11	4.18	44"-BB	96*
S	68.1	.336	.819	26.19	24.50	9.00	290.5	200.2	27.9	62.4	287				4.07	4.16	44"-BB	101*
Big T 860 (formerly known as Tornado BB30 860 Wood Shafts)																		
R	67.7	.335	.866	26.31	24.56	8.96	290.1	200.4	27.9	61.8	264				5.11	5.19	44"-BB	89*
S	70.9	.335	.865	26.25	24.56	9.16	292.9	200.2	27.9	64.8	276				4.07	4.23	44"-BB	97*
BM24 President Wood Shafts																		
A	83.6	.334	.598	24.25	23.19	11.09	340.9	211.0	51.0	78.9	234				4.82	4.94	43"-BB	
A	83.6	.334	.598	24.25	22.88	11.14	341.7	213.0	51.0	77.7	232	40	13	3.1	4.79	4.94	43"-M2	76
R	80.4	.333	.594	24.63	23.63	11.05	339.9	212.7	51.0	76.2	246				4.75	4.83	43"-BB	
R	80.4	.333	.594	24.63	23.38	11.14	341.6	215.4	51.0	75.2	244	43	11	3.9	4.71	4.83	43"-M2	80
S	91.5	.336	.606	24.44	23.31	11.43	347.2	209.8	51.0	86.4	264				4.67	4.79	43"-BB	
S	91.5	.336	.606	24.44	23.00	11.51	349.1	213.2	51.0	84.9	262	51	19	2.7	4.64	4.79	43"-M2	90
BM24 President 40" Iron Shafts																		
A	82.7	.372	.600	21.38	19.25	7.97	393.0	268.6	51.0	73.4	276	70	45	1.6	3.77	3.96	37.5"	63
R	83.1	.370	.605	21.44	19.31	7.99	393.4	268.9	51.0	73.5	287	77	48	1.6	3.73	3.86	37.5"	67
S	85.4	.369	.606	21.63	19.44	8.08	395.7	269.1	51.0	75.6	299	81	49	1.7	3.67	3.89	37.5"	70
BM24 USA 40" Taper Tip Iron Shafts																		
A	81.7	.358	.603	21.13	18.81	7.85	390.1	267.3	51.0	71.8	274	71	50	1.4	3.53	3.62	37.5"	65
R	81.6	.355	.603	21.38	19.13	7.91	391.6	268.9	51.0	71.7	287	76	49	1.6	3.63	3.81	37.5"	67
S	88.1	.355	.616	21.25	19.00	8.08	395.8	267.4	51.0	77.4	302	84	59	1.4	3.47	3.63	37.5"	74

SK FIBER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
BM24 Wood Shafts (pre 1996 version)																		
A	82.7	.333	.595	24.25	22.63	11.12	341.2	214.6	50.8	75.8	240	44	15	2.9	5.08	-----	43"-M1	79
R	86.9	.334	.605	24.44	22.81	11.31	345.1	214.5	50.8	79.8	253	49	17	2.9	4.97	-----	43"-M1	85
S	90.9	.330	.603	24.44	22.81	11.49	348.4	214.2	50.8	83.4	270	56	22	2.5	5.09	-----	43"-M1	93
BM24 39" Iron Shafts (pre 1996 version)																		
A	77.0	.366	.599	20.69	19.19	7.82	389.2	268.2	50.8	70.2	277	73	44	1.7	3.79	-----	37.5"	63
R	79.9	.369	.602	20.88	19.31	7.92	391.9	268.1	50.8	73.0	291	77	48	1.6	3.60	-----	37.5"	68
S	83.5	.370	.611	21.06	19.50	8.03	394.3	267.6	50.8	75.9	305	83	50	1.7	3.53	-----	37.5"	72
BM30 3.5 Wood Shafts (pre 1996 version)																		
A	82.2	.332	.600	24.69	22.44	10.87	336.6	212.6	50.8	73.2	238	43	16	2.7	4.03	-----	43"-M1	81
R	85.0	.332	.603	24.94	22.88	11.11	341.1	214.3	50.8	76.0	251	48	16	3.0	4.00	-----	43"-M1	86
S	92.3	.333	.611	24.88	22.69	11.40	346.6	213.3	50.8	82.5	272	56	21	2.7	4.03	-----	43"-M1	96
BM30 3.0 39" Iron Shafts (pre 1996 version)																		
R	79.6	.372	.603	20.75	19.13	7.90	391.2	267.9	50.8	72.5	290	80	48	1.7	3.08	-----	37.5"	69
S	83.2	.371	.610	20.94	19.38	8.06	395.1	268.3	50.8	76.0	308	87	52	1.7	3.04	-----	37.5"	75
BM30 Colonial Wood Shafts																		
A	82.4	.333	.596	24.75	23.06	10.94	338.0	211.3	51.0	75.7	235				4.33	4.42	43"-BB	
A	82.4	.333	.596	24.75	22.75	11.03	339.7	214.1	51.0	74.6	233	42	13	3.2	4.29	4.42	43"-M2	78
R	86.7	.332	.602	24.88	23.13	11.12	341.3	210.9	51.0	79.4	246				4.36	4.41	43"-BB	
R	86.7	.332	.602	24.88	22.88	11.18	342.6	213.4	51.0	78.2	244	45	16	2.8	4.33	4.41	43"-M2	83
S	90.3	.332	.608	24.94	23.25	11.27	344.1	210.2	51.0	82.9	263				4.24	4.29	43"-BB	
S	90.3	.332	.608	24.94	23.00	11.33	345.3	212.9	51.0	81.4	261	50	20	2.5	4.22	4.29	43"-M2	91
BM30 Colonial 40" Iron Shafts																		
A	79.2	.370	.599	21.31	19.06	7.83	389.5	268.7	51.0	69.8	271	69	44	1.6	3.31	3.44	37.5"	63
R	81.1	.367	.595	21.38	19.25	7.91	391.5	268.7	51.0	71.8	287	77	47	1.6	3.32	3.52	37.5"	68
S	85.5	.370	.604	21.50	19.38	8.04	394.6	268.5	51.0	75.1	302	83	49	1.7	3.16	3.24	37.5"	72
CGH24 Challenger Wood Shafts																		
A	88.3	.334	.598	24.69	23.00	11.44	347.5	216.1	50.6	80.8	235	42	13	3.2	7.52	7.56	43"-M1	72
R	90.3	.334	.597	24.56	22.94	11.51	349.1	215.6	50.6	82.9	249	43	15	2.9	7.46	7.49	43"-M1	76
S	97.9	.330	.612	24.81	23.13	11.79	354.8	214.8	50.6	89.4	265	50	19	2.6	7.61	7.65	43"-M1	83

SK FIBER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
CGH24 Challenger Iron Shafts																		
A	87.1	.369	.598	21.25	19.69	8.18	398.2	267.8	50.8	79.6	269	71	37	1.9	5.94	-----	37.5"	58
R	89.7	.368	.611	21.38	19.88	8.30	401.3	268.2	50.8	82.3	287	78	43	1.8	5.88	-----	37.5"	63
S	96.5	.368	.612	21.44	20.00	8.55	408.2	268.5	50.8	88.9	300	81	44	1.8	5.61	-----	37.5"	66
CL24 Silver Fox Wood Shafts (Ladies Length)																		
L	65.4	.335	.582	24.25	22.50	9.64	318.9	211.9	47.3	59.7	228				7.06	7.21	42"-BB	
L	65.4	.335	.582	24.25	22.19	9.74	320.7	214.8	47.3	58.6	227	36	13	2.8	6.99	7.21	42"-M2	65
A	67.7	.332	.579	24.25	21.94	9.81	321.9	214.4	47.6	59.9	239	41	17	2.4	7.00	-----	42"-M1	70
R	71.8	.332	.582	24.44	22.19	10.06	326.3	214.8	47.6	63.9	256	48	20	2.4	6.75	-----	42"-M1	78
CL24 Silver Fox Wood Shafts (Men's Length)																		
A	67.7	.332	.579	24.25	22.56	10.48	329.4	216.9	50.8	61.7	232				7.04	-----	43"-M1	71*
CL24 Silver Fox Iron Shafts (Ladies Length)																		
L	62.6	.370	.574	20.44	18.31	6.75	371.6	268.9	47.6	55.1	265	69	47	1.5	5.23	-----	36.5"	56
A	65.7	.371	.582	20.63	18.56	6.90	375.3	269.8	47.6	57.9	279	67	48	1.4	5.07	-----	36.5"	58
R	67.4	.368	.580	20.88	18.75	6.99	377.2	269.9	47.6	59.7	291	81	50	1.6	5.00	-----	36.5"	63
CL24 Silver Fox Iron Shafts (Men's Length)																		
A	65.7	.371	.582	20.63	19.13	7.40	379.0	268.1	50.8	60.1	273	79	42	1.9	5.11	-----	37.5"	62
CM24 Intrepid Wood Shafts																		
A	75.1	.335	.594	24.25	23.25	10.76	334.6	212.4	51.0	71.2	235				5.29	5.42	43"-BB	
A	75.1	.335	.594	24.25	22.94	10.85	336.2	215.3	51.0	69.9	234	39	15	2.6	5.24	5.42	43"-M2	76
R	73.9	.334	.585	24.31	23.38	10.73	334.1	212.9	50.8	70.4	246				5.54	5.66	43"-BB	
R	73.9	.334	.585	24.31	23.06	10.82	335.6	215.5	50.8	69.3	245	44	13	3.4	5.49	5.66	43"-M2	79
S	77.9	.333	.594	24.50	23.50	10.91	337.5	212.5	51.0	74.0	258				5.46	5.60	43"-BB	
S	77.9	.333	.594	24.50	23.25	10.99	338.9	215.3	51.0	72.6	257	50	15	3.3	5.42	5.60	43"M2	85
CM 24 Intrepid Iron Shafts																		
A	73.0	.363	.589	21.13	18.94	7.61	384.2	268.8	50.8	64.6	274	73	46	1.6	4.40	4.63	37.5"	63
R	79.1	.367	.605	21.63	19.44	7.87	390.4	269.7	51.0	69.7	287	79	45	1.8	4.24	4.43	37.5"	66
S	79.9	.366	.600	21.44	19.19	7.87	390.3	268.8	51.0	70.5	301	84	51	1.6	4.32	4.56	37.5"	70

SK FIBER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
CM24 Wood Shafts (pre 1996 version)																		
A	76.5	.333	.594	24.25	22.56	10.84	335.9	215.3	50.8	69.8	242	44	15	2.9	5.11	-----	43"-M1	79
R	81.2	.333	.598	24.31	22.69	11.08	340.6	215.2	50.8	74.6	253	48	18	2.7	5.11	-----	43"-M1	84
S	86.6	.333	.601	24.38	22.69	11.25	344.0	213.8	50.8	79.4	272	57	23	2.5	5.43	-----	43"-M1	93
CM24 39" Iron Shafts (pre 1996 version)																		
A	72.0	.373	.593	20.81	19.19	7.71	386.4	269.7	50.8	65.9	275	72	41	1.8	3.97	-----	37.5"	62
R	75.3	.373	.600	21.00	19.38	7.83	389.5	269.9	50.8	68.8	287	78	44	1.8	3.99	-----	37.5"	66
S	79.9	.370	.599	21.00	19.50	7.95	392.3	268.5	50.8	73.0	307	87	50	1.7	4.12	-----	37.5"	70
Lady 39" Iron Shaft (pre 1996 version)																		
L	61.4	.369	.575	20.50	18.19	6.68	369.9	268.3	47.3	54.0	258	63	44	1.4	5.36	-----	36.5"	53
Lady Liberty Wood Shaft																		
L	66.5	.332	.575	24.38	22.13	9.81	322.0	215.3	47.6	59.1	238				7.16	-----	42"-M1	70*
Lady Liberty 40" Iron Shaft																		
L	65.8	.371	.582	20.81	17.94	6.82	373.4	269.7	47.3	56.4	265	68	52	1.3	5.24	5.47	36.5"	57
Quick Taper Wood Shaft																		
R	66.0	.336	.880	26.00	24.94	9.10	292.2	201.8	27.9	62.5	257				4.37	4.71	44"-BB	89*
S	70.5	.334	.867	25.88	24.81	9.32	295.0	200.2	27.9	66.9	270				3.98	4.26	44"-BB	96*
SL30 Maximum Distance Wood Shafts																		
A	53.1	.332	.594	23.75	23.38	10.77	301.7	198.4	51.0	52.3	233	33	8	4.1	5.66	5.81	45"-BB	79
R	58.1	.335	.597	23.94	23.56	11.03	305.7	197.8	51.0	56.9	245	36	9	4.0	5.54	5.59	45"-BB	83
SL-40 Maximum Control Wood Shafts																		
R	61.9	.333	.614	24.31	23.88	11.22	308.5	197.7	50.0	60.8	243	36	10	3.6	5.04	4.96	45"-BB	85
S	65.5	.334	.614	24.06	23.75	11.34	310.4	196.0	50.0	64.4	263	41	14	2.9	4.87	4.92	45"-BB	95
SL46 Maximum Accuracy Wood Shafts																		
R	62.2	.333	.620	24.88	24.50	11.36	310.8	198.9	51.0	60.9	246	36	7	5.1	4.36	4.39	45"-BB	86
S	65.1	.335	.618	24.56	24.31	11.49	312.8	197.6	51.0	64.2	258	39	10	3.9	4.16	4.24	45"-BB	93

SK FIBER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Tornado BB30 811 Iron Shafts																		
L	53.0	.370	.810	21.63	18.44	5.12	336.7	264.7	27.9	44.1	263				3.63	3.71	36.5"	56*
A	57.0	.370	.809	21.63	19.19	5.55	339.8	262.2	27.9	49.7	284				3.67	3.72	37.5"	63*
R	57.8	.367	.811	21.69	19.25	5.65	342.0	264.0	27.9	50.1	299				3.62	3.76	37.5"	66*
S	60.9	.365	.816	22.06	19.56	5.81	344.9	264.6	27.9	52.4	316				3.63	3.69	37.5"	70*
Tornado BB30 860 Iron Shafts																		
R	59.7	.371	.857	22.00	19.63	5.70	342.7	262.8	27.9	52.0	304				3.12	3.22	37.5"	69*
S	62.1	.372	.862	22.13	19.75	5.83	345.2	263.1	27.9	54.2	311				3.24	3.29	37.5"	70*
Wave Stick Wood Shafts																		
R	75.6	.335	.616	24.63	23.06	10.77	334.8	214.5	50.0	70.3	258	46	18	2.6	5.09	5.81	43"-M2	86
S	78.3	.335	.620	24.63	23.06	10.91	337.3	214.5	50.0	72.8	270	50	18	2.8	5.00	5.69	43"-M2	90
Wave Stick Iron Shafts																		
R	80.3	.372	.597	20.94	19.19	7.90	391.3	269.1	50.0	72.2	305	83	51	1.6	3.57	4.51	37.5"	72
S	83.2	.369	.602	21.25	19.38	8.06	395.2	269.9	50.0	75.3	322	92	54	1.7	3.56	4.49	37.5"	78

SOMAR

Intensia FX-92020 Wood Shafts (for oversized metal woods)																		
R	74.3	.336	.589	23.13	22.13	10.59	331.5	212.7	50.4	68.4	262				3.95	-----	43"-BB	90*
S	74.9	.335	.590	23.25	22.25	10.51	330.1	210.7	50.4	69.0	283				4.48	-----	43"-BB	94*

SWIX

Performa 80 Wood Shafts																		
L	81.2	.331	.583	23.00	20.75	10.47	333.9	208.9	52.0	73.0	258				5.36	-----	42"-M1	80*
A	84.9	.338	.588	23.00	21.38	10.97	338.5	208.0	52.0	78.5	257				5.14	-----	43"-M1	83*
R	80.3	.334	.582	22.88	21.25	10.82	335.8	209.7	52.0	74.1	263				4.92	-----	43"-M1	86*
Performa 90 Wood Shafts																		
A	79.1	.330	.586	23.13	21.38	10.71	333.7	208.9	52.0	72.8	263				4.10	-----	43"-M1	89*
R	79.8	.330	.585	23.25	21.38	10.71	333.6	208.2	52.0	73.4	266				3.97	-----	43"-M1	91*
S	79.3	.337	.582	23.00	21.13	10.71	333.5	208.5	52.0	73.0	274				3.83	-----	43"-M1	94*

SWIX continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Performa 100 Wood Shafts																		
R	87.1	.335	.601	23.75	21.88	11.21	343.1	211.3	51.7	80.1	267				3.56	-----	43"-M1	93*
S	85.3	.330	.591	23.63	21.75	11.09	340.9	210.7	51.7	78.5	272				3.53	-----	43"-M1	95*
X	86.4	.333	.598	23.63	21.75	11.15	342.0	210.8	51.7	79.5	282				3.24	-----	43"-M1	100*
Performa 100+ Wood Shafts																		
R	89.1	.331	.600	23.88	21.88	11.25	343.8	210.2	51.7	81.9	275				2.75	-----	43"-M1	101*
S	90.7	.335	.606	23.75	21.75	11.28	344.4	208.9	51.7	83.8	284				2.49	-----	43"-M1	106*

SYSTEM FLEX

K2 Wood Shafts

S	-----	-----	-----	-----	22.31	11.43	347.3	210.6	47.1	89.6	279	56	19	2.9	3.90	-----	43"-M1	98
X	-----	-----	-----	-----	22.63	11.67	352.1	210.7	47.1	94.3	295	63	20	3.2	4.06	-----	43"-M1	103

K2 Tour 55 Wood Shafts

S	97.8	.336	.609	25.00	23.88	11.71	352.9	213.5	50.6	88.8	275	59	19	3.1	2.32	-----	43"-M1	105
X	97.7	.334	.605	25.13	22.94	11.71	352.9	213.9	50.6	88.4	290	61	21	2.9	2.29	-----	43"-M1	111

K2 Featherweight 46" R&S Combination Flex Wood Shaft (formerly K3 Featherweight)

R	66.5	.336	.590	24.50	23.56	11.38	311.0	196.4	51.0	63.6	250	37	8	4.6	4.47	4.66	45"-BB	88
R	64.5	.332	.589	24.38	21.88	10.21	325.0	217.7	50.6	56.7	255	51	12	4.3	4.13	4.75	43"-M1	86
S	66.0	.333	.591	24.56	22.25	10.33	326.9	218.1	50.6	58.2	268				3.88	4.69	43"-M1	92*

K2 Featherweight 40" R&S Combination Flex Iron Shaft (formerly K3 Featherweight)

R	62.0	.368	.589	19.81	18.00	7.22	374.8	268.2	50.8	55.8	292	77	55	1.4	4.31	4.79	37.5"	69
S	62.4	.369	.587	19.63	17.88	7.19	374.1	267.6	50.8	55.7	300				4.22	4.73	37.5"	64*

K3 46" R&S Combination Flex Wood Shaft

R	-----	-----	-----	-----	22.00	11.34	345.5	212.2	50.6	82.7	271				5.09	-----	43"-M1	88*
S	-----	-----	-----	-----	22.19	11.44	342.7	210.5	50.6	83.6	273	56	18	3.1	4.80	-----	43"-M1	94

K3 40" R&S Combination Flex Iron Shaft

R	-----	-----	-----	-----	18.50	8.19	398.6	267.2	50.6	80.8	293	78	45	1.7	3.46	-----	37.5"	68
S	-----	-----	-----	-----	18.63	8.33	402.2	270.0	50.6	81.6	298	84	52	1.6	3.21	-----	37.5"	73

SYSTEM FLEX continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
K3 Plus 46" R&S Wood Shaft																		
R	76.7	.333	.593	25.06	22.69	10.68	333.0	214.5	50.2	68.3	245	43	13	3.3	4.80	5.07	43"-M2	81
S	78.5	.334	.595	25.19	22.88	10.77	334.7	214.3	50.2	70.2	252	44	14	3.1	4.22	5.03	43"-M2	85
K3 Plus 40" R&S Iron Flex																		
R	74.4	.366	.598	21.38	19.25	7.66	385.2	268.8	50.2	66.2	293	72	46	1.6	4.03	4.43	37.5"	65
S	75.6	.369	.599	21.19	19.38	7.72	386.7	269.1	50.2	67.4	302	82	46	1.8	3.79	4.41	37.5"	69
K3 Plus 46" A&L Wood Shaft																		
L	74.0	.334	.588	24.88	21.94	9.40	314.6	211.2	39.8	63.6	226	38	12	3.2	4.67	5.09	42"-M2	69
A	74.9	.334	.592	25.00	22.69	10.62	332.0	214.8	50.2	67.0	224	30	10	3.0	4.29	5.01	43"-M2	71
K3 Plus 40" A&L Iron Flex																		
L	70.2	.368	.589	20.88	18.25	6.54	366.9	267.0	39.8	60.1	272	71	46	1.5	3.90	4.39	36.5"	59
A	70.2	.370	.590	20.81	19.06	7.52	381.8	269.2	50.2	62.4	276	70	39	1.8	3.81	4.42	37.5"	61
K4 46" R&S Combination Flex Wood Shaft (1994-97 version)																		
R	94.6	.335	.620	24.81	22.25	11.03	339.6	209.9	46.0	83.7	264	51	14	3.6	6.49	7.25	43"-M1	84
S	94.6	.335	.618	24.75	22.13	11.08	340.5	209.9	46.0	84.6	269				5.99	7.21	43"-M1	85*
K4 40" R&S Combination Flex Iron Shaft (1994-97 version)																		
R	94.4	.367	.620	21.19	19.19	8.00	393.8	262.9	46.0	84.9	285	74	35	2.1	4.66	5.06	37.5"	61
S	94.4	.369	.622	21.25	19.25	7.99	393.6	262.9	46.0	84.7	296	74	41	1.8	4.43	5.03	37.5"	64
K4 44" Wood Shafts (1992-93 version)																		
R	-----	-----	-----	-----	21.81	11.20	342.7	210.5	47.1	85.1	258	48	17	2.8	6.79	-----	43"-M1	81
S	-----	-----	-----	-----	22.00	11.25	344.0	210.2	47.1	86.7	273	54	18	3.0	6.79	-----	43"-M1	88
K4 39" Iron Shafts (1992-93 version)																		
R	-----	-----	-----	-----	18.94	8.20	398.9	264.6	47.1	87.2	294	75	46	1.6	4.33	-----	37.5"	66
S	-----	-----	-----	-----	19.19	8.23	399.7	266.5	47.1	86.1	307	82	47	1.7	4.41	-----	37.5"	69
K4 Lady Wood Shaft																		
L	74.1	.336	.589	24.06	22.19	10.07	326.5	212.2	47.3	67.0	223	36	12	3.0	7.45	7.80	42"-M2	63
K4 Lady Iron Shaft																		
L	75.6	.370	.601	21.06	19.00	7.28	384.8	270.4	47.6	66.8	280	75	41	1.8	4.43	4.83	36.5"	59

SYSTEM FLEX continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
K4 Lady Ultralite Wood Shaft																		
L	58.2	.334	.578	23.81	21.88	9.42	315.1	214.7	47.6	52.8	226	33	11	3.0	5.64	5.74	42"-M2	67
K4 Lady Ultralite Iron Shaft																		
L	66.1	.369	.600	20.75	18.50	6.88	374.8	269.9	47.6	57.3	281	73	49	1.5	4.93	5.30	36.5"	60
K4 Senior Wood Shaft																		
A	80.3	.335	.601	24.31	23.00	10.97	338.6	213.3	50.0	75.3	241				8.13	8.16	43"-M2	71*
K4 Senior Iron Shaft																		
A	78.2	.370	.606	21.25	19.75	7.92	391.8	270.2	50.0	71.6	276	73	37	2.0	4.79	5.09	37.5"	60
K4 Senior Ultralite Wood Shaft																		
A	59.9	.336	.577	23.81	22.44	9.97	320.6	214.4	50.0	56.2	224	36	11	3.3	5.68	5.86	43"-M2	70
K4 Senior Ultralite Iron Shaft																		
A	67.9	.372	.595	20.56	19.06	7.48	381.0	269.6	50.0	61.4	290	78	49	1.6	4.82	5.13	37.5"	67
K4SL Wood Shaft (pre 1998 version)																		
A	-----	-----	-----	-----	21.00	11.91	337.7	209.6	50.6	77.5	241				6.86	-----	43"-M1	74*
K4SL Iron Shaft (pre 1998 version)																		
A	-----	-----	-----	-----	18.75	8.17	398.0	269.7	50.6	77.7	258	59	29	50	4.43	-----	37.5"	53
KFI Wood Shafts (1999-2002 version)																		
A	89.8	.337	.590	25.06	23.50	11.39	346.5	212.2	50.0	84.3	251	45	11	4.1	4.31	5.06	43"-M2	83
R	91.3	.333	.593	25.38	23.75	11.51	348.9	213.2	50.0	85.7	264	50	13	3.8	4.22	5.04	43"-M2	89
S	96.1	.336	.595	25.31	23.75	11.68	352.4	212.3	50.0	90.1	279	55	18	3.1	4.62	5.23	43"-M2	95
KF 1 P.O.P. Wood Shafts (pre 1998 version)																		
A	87.0	.334	.604	25.75	24.25	11.33	345.4	214.1	50.0	81.3	238				4.75	5.39	43"-BB	
A	87.0	.334	.604	25.75	23.94	11.44	347.7	217.2	50.0	80.5	241	38	6	6.3	4.61	5.39	43"-M2	76
R	94.5	.334	.597	25.25	23.88	11.63	351.2	210.7	51.0	89.5	279				4.41	5.00	43"-BB	
R	94.5	.334	.597	25.25	23.56	11.70	352.8	213.2	51.0	88.6	282	61	14	4.4	4.26	5.00	43"-M2	98
R	94.5	.334	.597	25.25	23.31	11.78	354.5	215.8	51.0	87.7	284				4.12	5.00	43"-M1	96*
S	96.2	.335	.599	25.88	24.44	11.75	353.9	211.7	51.0	91.2	292				4.28	4.82	43"-BB	98*
S	96.2	.335	.599	25.88	24.19	11.83	355.5	214.2	51.0	90.3	294				4.16	4.82	43"-M2	99*
S	96.2	.335	.599	25.88	23.94	11.92	357.2	216.8	51.0	89.4	296				4.03	4.82	43"-M1	101*

SYSTEM FLEX continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
KF1 P.O.P. 40" Iron Shafts																		
A	84.4	.369	.592	20.94	19.63	8.15	397.5	268.9	50.0	78.6	290				3.79	4.28	37.5"	64*
R	87.0	.371	.590	20.88	19.56	8.21	399.1	268.1	50.0	81.0	309	82	42	2.0	3.85	4.30	37.5"	69
S	86.7	.370	.592	21.06	19.69	8.23	399.7	268.9	50.0	80.8	322	85	43	2.0	4.03	4.58	37.5"	71
KF1 P.O.P. 39" Iron Shafts (pre 1998 version)																		
A	81.8	.371	.603	20.44	19.00	8.01	394.2	268.7	50.0	75.5	280	69	35	2.0	3.78	4.26	37.5"	60
R	84.9	.367	.599	20.38	18.94	8.10	396.2	266.4	51.0	78.8	299	86	45	1.9	3.84	4.23	37.5"	70
S	87.0	.369	.600	20.50	19.13	8.18	398.3	266.6	51.0	80.7	315	92	48	1.9	3.73	4.22	37.5"	75
KF1 Ultralite Wood Shafts																		
A	70.8	.335	.572	24.94	23.44	10.60	331.8	215.6	50.0	66.2	247	42	10	4.2	5.35	5.49	43"-M2	78
R	75.1	.335	.579	25.13	23.50	10.76	334.5	214.2	50.0	70.3	263	48	13	3.7	4.74	5.39	43"-M2	87
S	78.4	.336	.579	25.19	23.63	10.96	338.1	214.7	50.0	73.4	295	62	15	4.1	5.53	6.42	43"-M2	98
KF1 Ultralite Wood Shafts (1997 version)																		
R	64.0	.332	.558	22.81	21.25	9.85	318.6	212.6	47.1	58.9	266	46	15	3.1	7.61	8.55	43"-M2	82
KFT Frequency Tuned Wood Shafts																		
R	99.4	.336	.612	25.31	23.13	11.54	349.6	209.8	50.0	89.8	247				4.41	4.66	43"-BB	
R	99.4	.336	.612	25.31	22.81	11.64	351.5	212.5	50.0	89.0	249	40	15	2.7	4.27	4.66	43"-M2	83
S	98.8	.335	.610	25.25	23.13	11.56	349.9	209.4	50.0	90.5	252				4.06	4.46	43"-BB	
S	98.8	.335	.610	25.25	22.88	11.64	351.6	212.0	50.0	89.6	254	44	17	2.6	3.94	4.46	43"-M2	87
KFT Frequency Tuned Iron Shafts																		
R	94.5	.369	.618	21.19	19.13	8.28	401.0	266.4	50.0	84.6	284	73	52	1.4	3.58	3.92	37.5"	67
S	94.5	.370	.623	21.25	19.19	8.29	401.1	266.0	50.0	85.1	289	76	52	1.5	3.43	3.90	37.5"	69
K Lady Wood Shaft (pre 1998 version)																		
L	-----	-----	-----	-----	20.31	10.27	330.3	213.9	50.6	65.8	231	37	12	3.1	7.48	-----	42"-M1	65
K Lady Iron Shaft (pre 1998 version)																		
L	-----	-----	-----	-----	17.31	7.22	383.4	268.4	50.6	64.4	273	67	48	1.4	5.02	-----	36.5"	57

TITANIUM SPORTS

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Standard Titanium Wood Shafts (for short hosel, oversized metal woods, 1993 version)																		
R	111.4	.335	.601	22.56	21.00	11.88	356.4	202.0	50.6	103.8	243				3.19	----	43"-BB	87*
S	111.3	.335	.598	22.06	21.06	11.83	355.4	201.1	50.6	103.7	253				3.01	----	43"-BB	91*
Standard Titanium Wood Shafts (pre 1994 version)																		
L	88.0	.338	.584	22.69	20.38	10.71	338.4	208.8	50.6	79.0	237	38	18	2.1	3.29	----	42"-M1	78
A	90.9	.333	.597	22.50	20.75	11.18	342.4	207.9	50.6	83.9	238	39	18	2.2	3.10	----	43"-M1	83
R	99.9	.333	.601	22.50	20.56	11.52	349.2	206.2	50.8	92.2	244				2.60	----	43"-M1	91*
R	100.0	.332	.601	22.50	20.69	11.53	349.4	206.3	50.8	92.3	243	43	22	2.0	2.60	----	43"-M1	90
S	104.5	.334	.600	22.63	20.75	11.74	353.5	206.6	50.8	96.1	254	45	22	2.0	2.45	----	43"-M1	95
X	106.1	.335	.617	22.88	20.88	11.59	350.3	205.3	47.7	97.5	261	48	25	1.9	2.34	----	43"-M1	99
X	106.1	.335	.617	23.00	20.94	11.66	352.0	207.5	47.7	96.8	263	48	27	1.8	2.41	----	43"-M1	100
Standard Titanium Iron Shafts (pre 1994 version)																		
L	94.8	.371	.584	18.56	17.19	7.93	401.8	263.1	50.6	88.1	265	65	39	1.7	2.55	----	36.5"	57
A	101.9	.370	.602	18.75	17.88	8.50	406.7	258.7	50.6	97.4	271	68	37	1.8	2.31	----	37.5"	63
R	100.4	.368	.596	18.31	17.50	8.44	405.0	258.0	50.6	96.4	276	72	42	1.7	2.23	----	37.5"	66
S	102.2	.370	.600	18.63	17.81	8.52	407.3	258.7	50.6	98.0	291	72	41	1.8	2.09	----	37.5"	68
X	96.3	.370	.595	18.56	17.75	8.32	402.0	259.7	50.6	91.7	287	75	42	1.8	2.12	----	37.5"	69
Titanium Low Flex Wood Shafts (pre 1994 version)																		
A	98.5	.335	.606	22.75	20.94	11.54	349.5	207.8	51.6	90.1	234	39	11	3.5	3.33	----	43"-M1	79
R	99.3	.336	.600	22.63	20.50	11.54	349.6	207.0	51.6	91.0	241	46	15	3.1	3.10	----	43"-M1	85
S	105.3	.335	.603	22.75	20.88	11.75	353.7	205.5	51.6	96.6	254	46	18	2.6	2.74	----	43"-M1	92
X	105.9	.335	.601	22.63	20.50	11.77	354.1	205.4	51.6	97.1	259	46	21	2.2	2.64	----	43"-M1	95
Titanium LF 160 Wood Shaft																		
160	83.2	.334	.580	22.88	20.63	10.38	332.3	210.3	47.3	74.7	240	40	15	2.7	3.37	3.80	42"-M1	78
Titanium LF 180 Wood Shaft																		
180	102.4	.335	.579	23.56	20.69	11.47	348.1	206.9	50.8	90.4	233				3.35	3.76	43"-M1	82*
200	104.5	.335	.584	23.88	21.50	11.44	347.6	202.4	51.1	94.1	237				3.39	3.88	43"-BB	
200	104.5	.335	.584	23.88	21.25	11.50	348.8	205.0	51.1	92.7	238	39	12	3.3	3.36	3.88	43"-M2	81
Titanium MF 180 Wood Shaft																		
180	103.3	.333	.576	23.63	20.69	11.50	348.6	206.8	50.8	91.0	233				3.28	3.70	43"-M1	83*

TITANIUM SPORTS continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Titanium MF Iron Shafts																		
110	104.7	.367	.585	19.88	18.00	8.44	405.0	259.3	50.8	94.9	266				2.38	2.46	37.5"	62*
125	106.9	.366	.598	20.00	18.06	8.52	407.5	260.2	50.6	96.7	273	68	38	1.8	2.27	2.39	37.5"	63
Tour Titanium Iron Shafts																		
110	103.5	.366	.582	19.50	17.56	8.41	404.2	258.7	51.2	94.3	262	64	44	1.5	2.58	2.76	37.5"	61
125	105.6	.369	.595	19.75	17.88	8.50	406.9	259.9	51.0	96.0	267	68	44	1.5	2.40	2.55	37.5"	64
140	106.5	.368	.596	19.44	17.63	8.52	407.3	258.7	51.0	97.6	276	70	49	1.4	2.28	2.45	37.5"	67
155	103.7	.366	.597	19.69	17.75	8.41	404.3	259.4	51.0	93.9	278	78	51	1.5	2.26	2.44	37.5"	71
170	107.0	.368	.594	19.44	17.56	8.52	407.4	258.7	51.0	97.7	293	79	53	1.5	2.12	2.27	37.5"	74

TRUE TEMPER

Assailant A&L Combination Flex Wood Shaft

L	79.2	.337	.580	24.19	21.19	9.95	324.2	208.1	47.1	69.0	226				5.19	5.49	42"-BB	
L	79.2	.337	.580	24.19	20.94	10.04	325.9	210.5	47.1	68.3	228	34	19	1.8	5.05	5.49	42"-M2	71
A	79.0	.335	.580	24.38	21.88	10.63	332.2	210.2	51.0	71.0	225				4.94	5.38	43"-BB	
A	79.0	.335	.580	24.38	21.63	10.73	333.9	212.8	51.0	70.1	229	35	15	2.3	4.79	5.38	43"-M2	74

Assailant R&S Combination Flex Wood Shaft

R	81.8	.337	.600	24.38	22.00	10.74	334.2	210.2	51.0	73.0	239				5.48	5.83	43"-BB	
R	81.8	.337	.600	24.38	21.75	10.84	336.0	212.9	51.0	72.1	242	38	15	2.5	5.29	5.83	43"-M2	79
S	81.3	.335	.601	24.38	22.00	10.71	333.6	210.1	51.0	72.5	241				5.23	5.66	43"-BB	
S	81.3	.335	.601	24.38	21.75	10.80	335.5	212.9	51.0	71.6	245	41	14	2.9	5.03	5.66	43"-M2	80

Assailant A&L Combination Flex Iron Shaft

L	78.6	.373	.580	20.88	17.56	7.06	379.2	266.2	47.1	65.9	248	62	46	1.3	3.83	4.43	36.5"	54
A	78.7	.370	.580	21.00	18.13	7.66	385.3	266.2	51.0	68.1	256	61	46	1.3	3.76	4.23	37.5"	59

Assailant R&S Combination Flex Iron Shaft

R	81.6	.373	.600	20.69	17.88	7.72	386.8	264.6	51.0	71.2	275	70	49	1.4	3.54	4.05	37.5"	64
S	82.1	.373	.600	20.75	17.94	7.73	387.1	265.0	51.0	71.1	283	72	55	1.3	3.43	4.06	37.5"	68

Assailant OSC Wood Shafts

A	74.3	.335	.885	24.88	23.44	9.32	295.0	196.5	27.9	70.6	254				4.47	5.31	44"-BB	88*
R	74.8	.336	.870	24.38	22.88	9.26	294.3	195.3	27.9	71.1	263				4.46	5.35	44"-BB	91*
S	75.1	.336	.881	24.88	23.44	9.34	295.3	196.2	27.9	71.2	277				4.54	5.51	44"-BB	95*

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Assailant OSC Iron Shafts																		
A	67.0	.371	.876	21.06	19.00	5.97	348.1	262.3	27.9	57.9	297				3.28	4.29	37.5"	67*
R	68.9	.372	.877	20.75	18.69	5.97	348.1	260.3	27.9	59.9	308				3.36	4.36	37.5"	69*
S	67.5	.372	.875	20.69	18.63	5.96	347.9	261.5	27.9	58.5	326				3.46	4.52	37.5"	72*
Black Gold Graphite Wood Shafts																		
R300	89.8	.334	.598	23.81	21.88	11.28	344.4	211.1	50.6	82.7	263	47	20	2.4	3.00	----	43"-M1	94
S300	90.7	.335	.597	23.81	21.88	11.31	345.0	210.8	50.6	83.6	269	54	26	2.1	2.75	----	43"-M1	102
Black Gold Graphite Iron Shafts																		
R300	90.2	.372	.600	21.13	19.25	8.22	399.5	267.1	50.6	81.8	291	77	44	1.8	1.98	2.25	37.5"	71
S300	92.5	.375	.600	20.88	18.75	8.21	399.1	264.8	50.6	83.7	313	86	54	1.6	1.94	2.20	37.5"	79
X100	93.7	.374	.601	20.88	18.94	8.31	401.6	265.1	50.6	85.9	323	93	56	1.7	1.98	2.24	37.5"	83
Black Gold Tour Graphite Wood Shafts																		
S400	95.8	.336	.598	23.88	22.00	11.58	350.3	210.7	50.6	89.0	271	55	20	2.8	2.61	----	43"-M1	101
X100	97.5	.335	.600	23.88	22.00	11.66	351.8	210.9	50.6	90.3	284				2.62	----	43"-M1	105*
BiMatrx Wood Shafts																		
R	74.8	.333	.601	21.31	19.25	10.87	318.9	199.6	50.6	68.7	240	34	16	2.1	3.81	3.91	44"-M2	84
S	77.2	.333	.608	21.69	19.56	10.98	321.0	199.9	50.6	70.5	251	40	17	2.4	3.67	3.75	44"-M2	90
Crossfire Fairway Wood Shafts																		
R	98.6	.337	.601	23.19	22.25	11.66	351.7	206.9	51.0	93.8	248	40	14	2.9	3.09	3.23	43"-BB	87
S	98.3	.338	.600	23.13	22.19	11.64	351.5	206.7	51.0	93.8	253	42	17	2.5	2.88	2.98	43"-BB	91
Crossfire Hybrid Iron Shafts																		
R	100.9	.373	.605	21.31	19.91	9.72	386.6	241.9	51.0	93.7	278	62	37	1.7	2.31	2.39	39.5"	71
S	102.6	.374	.604	21.38	20.00	9.77	387.7	241.6	51.0	95.1	285	65	40	1.6	2.20	2.24	39.5"	73
Comet A&L Combination Flex Wood Shaft																		
L	75.8	.336	.603	24.13	21.00	9.77	321.2	208.8	47.1	65.3	233				4.77	5.23	42"-BB	
L	75.8	.336	.603	24.13	20.75	9.84	322.3	210.8	47.1	64.4	235	38	17	2.2	4.70	5.23	42"-M2	74
A	76.1	.335	.602	24.13	21.63	10.41	328.3	210.6	50.0	67.7	236				4.63	5.26	43"-BB	
A	76.1	.335	.602	24.13	21.38	10.51	329.9	212.9	50.0	67.0	238	40	16	2.5	4.52	5.26	43"-M2	79

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Comet R&S Combination Flex Wood Shaft																		
R	86.3	.335	.608	25.94	23.19	10.97	338.6	212.4	51.0	75.2	247				4.47	4.85	43"-BB	
R	86.3	.335	.608	25.94	22.88	11.08	340.5	215.3	51.0	74.2	250	42	15	2.8	4.34	4.85	43"-M2	84
S	85.9	.336	.605	25.94	23.25	11.00	339.1	212.3	51.0	75.8	257				4.21	4.81	43"-BB	
S	85.9	.336	.605	25.94	22.94	11.12	341.2	215.3	51.0	74.9	260	47	17	2.8	4.14	4.81	43"-M2	89
Comet 42" A&L Combination Flex Iron Shaft																		
L	75.6	.372	.599	21.00	17.81	7.01	377.9	267.1	47.1	63.7	255	60	38	1.6	3.49	3.98	36.5"	53
A	75.3	.373	.598	21.00	18.25	7.51	381.6	266.9	50.0	64.7	255	60	37	1.6	3.46	4.02	37.5"	56
Comet 42" R&S Combination Flex Iron Shaft																		
R	82.4	.370	.603	22.69	19.69	7.82	389.2	268.8	51.0	69.4	280	74	40	1.9	3.73	4.40	37.5"	64
S	82.3	.370	.603	22.56	19.81	7.94	392.1	270.5	51.0	70.6	301	84	47	1.8	3.29	4.26	37.5"	71
Command 47" A&L Combination Flex Wood Shaft																		
L	91.7	.333	.582	26.00	22.06	10.62	336.8	213.7	47.2	75.9	229	38	13	2.9	4.10	4.67	43"-M1	72
A	92.0	.334	.585	26.06	22.88	11.31	345.0	213.8	50.8	80.4	237	42	15	2.8	3.67	4.72	43"-M1	81
Command 42" A&L Combination Flex Iron Shaft																		
L	91.3	.368	.586	22.44	18.75	7.49	390.1	268.4	47.2	74.5	248	59	35	1.7	2.83	3.36	36.5"	52
A	93.8	.368	.585	22.75	19.75	8.23	399.7	268.2	50.8	80.7	256	63	36	1.8	2.57	3.36	37.5"	59
Command 47" R&S Combination Flex Wood Shaft																		
R	94.9	.334	.598	26.19	22.69	11.33	345.4	214.4	50.6	80.6	247	45	18	2.5	4.40	4.98	43"-M1	84
S	95.2	.334	.598	26.19	22.81	11.49	348.5	214.7	50.6	83.2	256	48	21	2.3	3.82	4.81	43"-M1	90
Command 42" R&S Combination Flex Iron Shaft																		
R	96.5	.370	.596	23.00	19.75	8.29	401.2	269.5	50.6	81.1	269	69	38	1.8	2.82	3.29	37.5"	62
S	96.6	.369	.599	23.00	19.88	8.34	402.6	268.6	50.6	83.4	287	76	43	1.8	2.47	3.23	37.5"	68
Command Wood Shafts (pre 1995 version)																		
L	90.1	.335	.580	22.75	21.00	11.00	344.5	210.3	50.6	83.6	259	48	21	2.3	3.84	----	42"-M1	85
R	96.3	.335	.598	24.13	22.19	11.60	350.7	211.2	50.6	88.9	260	51	20	2.6	3.64	----	43"-M1	92
S	99.4	.336	.600	24.75	22.06	11.68	352.5	209.9	50.6	92.0	267	53	18	2.9	3.60	----	43"-M1	94
Command Iron Shafts (pre 1995 version)																		
R	97.0	.370	.598	20.81	18.88	8.36	403.0	263.9	50.6	88.5	294	83	51	1.6	2.67	----	37.5"	73

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Command Lite Wood Shafts																		
R	83.1	.335	.598	23.19	21.38	10.94	337.9	210.6	50.6	76.7	259	51	22	2.3	3.95	----	43"-M1	92
Command Lite Iron Shafts																		
L	79.9	.370	.580	18.94	17.50	7.40	387.8	263.3	50.6	73.9	313	90	55	1.6	3.74	----	36.5"	71
A	85.6	.369	.592	20.13	18.25	7.92	391.9	264.3	50.6	77.0	282	74	49	1.5	3.94	----	37.5"	66
S	91.0	.370	.595	20.44	18.56	8.16	398.1	264.6	50.6	82.9	311	84	53	1.6	3.43	----	37.5"	74
Custom Lite 43" Iron Shaft																		
Soft R	118.7	.369	.610	21.75	18.44	8.76	414.0	263.7	50.6	99.7	303	77	49	1.6	1.95	2.33	37.5"	74
Firm R	119.3	.369	.609	21.75	18.44	8.77	414.3	263.7	50.6	100.0	310	82	52	1.6	1.86	2.32	37.5"	77
Soft S	119.5	.369	.616	21.75	18.44	8.77	414.3	263.7	50.6	100.0	316	84	55	1.5	1.79	2.32	37.5"	80
Firm S	120.5	.370	.612	21.69	18.38	8.79	414.8	263.5	50.6	100.7	322	87	60	1.5	1.67	2.30	37.5"	83
Dynalite Steel 46" A&L Combination Flex Wood Shafts																		
L	110.3	.334	.580	24.50	21.63	11.32	351.0	207.2	47.3	96.5	233	38	13	2.9	3.47	3.74	42"-M2	75
A	110.1	.333	.578	22.25	11.93	11.93	357.6	207.1	51.1	99.4	232	35	13	2.7	3.46	3.91	43"-M2	78
Dynalite Steel 46" A&L Combination Flex Wood Shafts (pre 1996 trimming instructions)																		
L	-----	-----	-----	-----	21.13	11.48	354.4	209.3	50.6	94.5	231	40	15	2.7	3.40	----	42"-M1	76
A	-----	-----	-----	-----	22.00	11.88	356.3	207.8	50.6	97.9	232	41	14	2.9	3.36	----	43"-M1	80
Dynalite Steel 47" R&S Combination Flex Wood Shaft																		
R	117.0	.334	.603	23.88	21.19	11.93	357.6	203.3	51.0	103.3	256	43	17	2.5	2.87	3.09	43"-M2	91
S	117.3	.334	.603	23.88	21.25	11.97	358.4	203.5	51.0	103.9	265	46	19	2.4	2.68	3.05	43"-M2	97
Dynalite Steel 47" R&S Combination Flex Wood Shaft (pre 1996 trimming instructions)																		
R	-----	-----	-----	-----	21.13	11.97	358.4	207.7	50.6	100.1	258				2.68	----	43"-M1	95*
S	-----	-----	-----	-----	21.25	11.96	358.2	207.9	50.6	99.7	268	47	19	2.5	2.55	----	43"-M1	99
Dynalite Graphite Wood Shafts																		
R	88.2	.335	.600	26.06	22.75	11.30	344.6	215.9	50.6	78.1	261				3.31	3.99	43"-M1	92*
S	90.3	.336	.599	25.69	22.44	11.33	345.2	214.6	50.6	80.0	265	50	19	2.6	3.23	3.92	43"-M1	94
X	90.9	.336	.598	25.81	22.50	11.36	345.9	214.6	50.6	80.7	275	52	20	2.6	3.29	3.95	43"-M1	97

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Dynalite Graphite Iron Shafts																		
R	87.2	.371	.598	22.00	18.88	7.98	393.3	267.2	51.0	75.1	286	78	45	1.7	2.43	2.99	37.5"	69
S	88.0	.370	.598	22.06	18.94	8.03	394.4	267.4	51.0	76.0	291	79	46	1.7	2.60	3.27	37.5"	70
Dynalite Gold Steel Wood Shafts																		
R300	112.0	.334	.602	23.00	21.31	12.00	358.8	204.5	51.0	103.3	258	42	17	2.5	2.82	3.09	43"-M2	92
S300	111.9	.334	.601	22.88	21.19	11.94	357.9	203.6	51.0	103.3	266	45	18	2.5	2.64	2.82	43"-M2	97
X100	117.3	.334	.602	22.75	21.13	12.10	361.2	201.4	51.0	108.6	278	47	23	2.0	2.41	2.59	43"-M2	104
Dynalite Gold Steel Wood Shafts (pre 1996 trimming instructions)																		
R300	112.1	.332	.600	22.94	21.06	11.93	357.5	204.2	50.6	102.7	260	46	18	2.6	2.70	----	43"-M1	94
S300	112.2	.332	.601	22.81	21.06	11.93	357.4	204.2	50.6	102.6	268	50	22	2.3	2.51	----	43"-M1	100
X100	117.0	.333	.600	22.75	20.94	12.14	361.9	204.2	50.6	107.1	281				2.31	2.58	43"-M1	107*
Dynalite Gold with SensiCore Wood Shafts																		
R300	118.1	.334	.600	22.94	21.31	12.16	362.4	203.0	50.0	109.4	254	42	18	2.3	2.88	3.06	43"-M2	91
S300	117.6	.334	.600	23.13	21.50	12.18	363.0	203.9	50.0	109.1	263	45	18	2.5	2.69	3.01	43"-M2	95
Dynalite Gold Steel 38" Taper Tip Iron Shafts																		
R300	109.0	.355	.580	18.81	17.88	8.70	412.2	257.5	50.8	103.9	291	74	54	1.4	1.98	2.00	37.5"	73
S300	113.0	.356	.601	18.94	18.06	8.85	416.6	258.4	50.6	107.6	309	80	58	1.4	1.75	1.84	37.5"	79
Dynamic Steel 46" A&L Combination Flex Wood Shaft																		
L	124.5	.334	.561	24.38	21.75	11.65	358.2	200.8	47.3	110.1	234				3.25	3.39	42"-BB	
L	124.5	.334	.561	24.38	21.50	11.75	360.4	204.1	47.3	109.0	235	36	16	2.3	3.17	3.39	42"-M2	78
A	124.4	.334	.558	24.38	22.38	12.38	367.2	202.2	51.1	113.9	232				3.21	3.42	43"-BB	
A	124.4	.334	.558	24.38	22.13	12.48	369.3	205.5	51.1	112.7	233	36	15	2.4	3.15	3.42	43"-M2	81
Dynamic Steel 46" A&L Combination Flex Wood Shaft (pre 1996 trimming instructions)																		
L	-----	-----	-----	-----	21.31	11.66	358.3	205.4	47.4	105.5	233	39	17	2.3	3.17	----	42"-M1	77
A	-----	-----	-----	-----	21.88	12.33	366.1	205.6	50.8	109.7	233	42	17	2.5	3.06	----	43"-M1	83
Dynamic Steel 40" A&L Combination Flex Iron Shaft																		
L	123.4	.372	.560	20.25	17.88	8.49	421.3	266.1	49.2	106.0	281				1.97	----	36.5"	68*
A	123.1	.371	.559	20.38	18.38	9.24	427.9	264.2	53.2	110.5	278	75	50	1.5	1.96	----	37.5"	71

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Dynamic Steel 47" R&S Combination Flex Wood Shaft																		
R	131.2	.333	.601	25.13	22.25	12.56	371.2	205.3	51.0	114.9	250	44	16	2.8	2.94	3.19	43"-M2	90
S	131.4	.333	.602	25.13	22.25	12.62	372.4	204.8	51.0	116.6	261	47	16	2.9	2.80	3.21	43"-M2	94
Dynamic Steel 47" R&S Combination Flex Wood Shaft (pre 1996 trimming instructions)																		
R	130.5	.331	.595	25.13	22.13	12.52	370.2	205.4	50.6	114.2	256	45	18	2.5	2.75	----	43"-M1	92
S	130.7	.331	.596	25.13	22.06	12.58	371.6	204.8	50.6	116.2	268	50	20	2.5	2.57	----	43"-M1	99
Dynamic Steel 45" Wood Shaft (1997 – 2000 trimming instructions)																		
X	124.4	.334	.601	24.06	22.63	12.48	369.3	202.2	51.0	116.1	269				2.71	2.86	43"-BB	99*
X	124.4	.334	.601	24.06	22.31	12.56	370.9	205.1	51.0	114.8	272	49	19	2.6	2.65	2.86	43"-M2	100
Dynamic Steel 45" Wood Shaft (pre 1996 trimming instructions)																		
X	125.5	.335	.602	23.88	21.75	12.65	373.3	206.5	51.6	115.2	272	51	23	2.2	2.44	----	43"-M1	102
Dynamic Steel 41" R&S Combination Flex Iron Shaft																		
R	128.9	.365	.598	20.81	18.44	9.04	422.0	258.5	50.6	112.9	310	84	54	1.6	1.76	----	37.5"	79
S	128.5	.365	.598	20.88	18.63	9.06	422.8	259.6	50.6	112.6	323	94	59	1.6	1.64	----	37.5"	86
Dynamic Steel 39" Iron Shaft																		
X	128.4	.369	.600	19.56	18.06	9.25	428.0	259.4	50.6	118.0	338	96	64	1.5	1.53	1.71	37.5"	90
Dynamic Steel Reinforced Tip for Metal Wood Shafts																		
R	117.5	.334	.601	22.00	21.13	12.39	367.3	204.9	50.8	111.6	255	49	23	2.1	2.54	----	43"-M1	96
S	127.9	.333	.600	22.13	21.19	12.75	375.5	203.0	50.8	121.7	276	55	27	2.0	2.17	----	43"-M1	107
Dynamic Steel 37" Taper Tip Iron Shafts																		
T	119.3	.354	.579	18.38	18.00	9.08	423.4	255.9	50.8	116.7	298	80	60	1.3	1.80	1.82	37.5"	77
S	123.8	.355	.601	18.63	18.25	9.26	428.7	256.8	50.6	121.3	324	87	66	1.3	1.59	1.65	37.5"	86
Dynamic Gold Lite Iron Shafts																		
R	108.4	.371	.612	20.75	18.31	8.53	407.7	263.0	50.2	94.5	282				2.34	2.53	37.5"	68*
S	108.7	.369	.611	20.81	18.44	8.56	408.6	263.4	50.2	95.0	294	74	42	1.8	2.16	2.41	37.5"	69
X	111.2	.369	.613	20.81	18.25	8.62	410.1	262.9	50.2	97.0	308	82	52	1.6	1.97	2.16	37.5"	76

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Dynamic Gold Lite 39" Taper Tip Iron Shafts																		
R	109.2	.354	.613	19.69	18.13	8.69	411.8	261.2	50.2	100.4	289	73	48	1.5	2.15	2.19	37.5"	70
S	109.7	.356	.613	19.69	18.19	8.74	413.4	261.9	50.2	101.3	304	79	51	1.5	2.00	2.04	37.5"	75
X	110.8	.355	.614	19.50	18.06	8.74	413.3	260.7	50.2	102.4	316	84	57	1.5	1.83	1.91	37.5"	80
Dynamic Gold Lite w/ SensiCore Iron Shafts																		
R	113.6	.370	.611	21.00	18.63	8.75	413.6	263.9	50.2	99.5	282	68	44	1.5	2.36	2.55	37.5"	66
S	114.1	.369	.613	20.94	18.44	8.73	413.1	262.8	50.2	100.1	295	76	46	1.7	2.10	2.34	37.5"	69
X	113.7	.369	.614	21.00	18.56	8.76	413.9	263.9	50.2	99.8	307	80	49	1.6	2.03	2.24	37.5"	74
Dynamic Gold Graphite Wood Shafts																		
R300	94.3	.333	.597	22.88	21.50	11.27	344.2	204.5	51.0	88.7	264				3.66	3.86	43"-BB	
R300	94.3	.333	.597	22.88	21.19	11.36	346.0	207.3	51.0	87.7	265	49	17	2.9	3.58	3.86	43"-M2	92
S300	94.5	.333	.598	23.00	21.56	11.23	343.4	203.8	51.0	88.6	274				4.11	4.36	43"-BB	
S300	94.5	.333	.598	23.00	21.25	11.36	345.9	207.3	51.0	87.6	276	54	22	2.5	3.98	4.36	43"-M2	98
Dynamic Gold Graphite Iron Shafts																		
R300	97.9	.368	.597	20.25	17.88	8.20	398.9	260.9	51.0	87.0	285	75	53	1.4	3.33	3.86	37.5"	68
S300	99.0	.368	.597	20.38	18.06	8.27	400.7	261.7	51.0	88.0	297	79	52	1.5	3.29	3.81	37.5"	71
Dynamic Graphite Wood Shafts																		
R	100.3	.337	.613	24.13	22.00	11.77	354.1	211.6	50.6	91.9	260				3.33	3.73	43"-M1	92*
S	109.6	.335	.598	24.19	22.88	12.06	360.2	205.6	51.0	103.6	269				3.96	4.16	43"-BB	
S	109.6	.335	.598	24.19	22.56	12.05	360.0	206.3	51.0	102.7	269	53	19	2.8	3.83	4.16	43"-M2	96
X	113.8	.337	.600	24.13	22.75	12.18	362.8	204.3	51.0	107.5	281				3.63	3.89	43"-BB	
X	113.8	.337	.600	24.13	22.44	12.14	361.9	204.4	51.0	106.5	280	57	19	3.0	3.54	3.89	43"-M2	101
Dynamic Graphite 38" Taper Tip Iron Shafts																		
R	111.6	.351	.598	18.94	18.38	8.93	418.6	259.9	50.6	108.1	309	76	66	1.2	2.26	2.34	37.5"	78
S	110.4	.345	.599	19.19	18.63	8.94	418.9	261.2	50.6	107.1	305	82	75	1.1	2.41	2.48	37.5"	81
X	110.8	.352	.600	18.94	18.38	8.93	418.8	259.9	50.6	108.3	328	87	73	1.2	2.35	2.44	37.5"	85
Dynamic Graphite Wood Shafts (1994 version; predecessor of Dynamic Lite Graphite)																		
R	77.9	.334	.598	23.38	21.63	10.82	335.6	213.6	50.6	71.4	260	50	19	2.6	3.82	4.35	43"-M1	90
S	79.3	.332	.599	23.56	21.75	10.88	336.9	213.6	50.6	72.7	269	53	19	2.8	3.85	4.34	43"-M1	94
X	82.9	.335	.599	23.38	21.63	10.99	338.8	212.1	50.6	76.1	273	55	21	2.6	3.86	4.41	43"-M1	96

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Dynamic Graphite 38" Iron Shafts (1994 version; predecessor of Dynamic Lite Graphite)																		
R	81.2	.368	.598	18.88	18.00	7.98	393.3	265.6	50.6	77.1	301	81	56	1.4	3.60	3.64	37.5"	72
R	84.6	.370	.600	19.13	18.25	8.10	396.3	264.8	50.8	80.7	304	81	60	1.4	3.27	----	37.5"	75
S	85.9	.370	.600	19.06	18.19	8.07	395.5	262.8	50.8	81.9	318	88	62	1.4	3.56	----	37.5"	78
S	87.7	.368	.600	18.94	18.13	8.22	399.5	265.4	50.6	83.5	318	87	58	1.5	3.61	3.65	37.5"	74
X	85.6	.370	.602	19.00	18.13	8.15	397.6	265.4	50.6	81.6	329	94	61	1.5	3.68	3.73	37.5"	79
Dynamic Gold Steel 44" Taper Tip Wood Shafts																		
R300	124.0	.277	.599	23.56	23.19	12.59	372.0	200.5	50.6	120.9	258	40	14	2.9	2.93	3.02	43"-TB	92
S300	123.8	.294	.620	23.38	23.00	12.29	365.1	198.0	46.2	120.9	265	43	17	2.5	2.72	2.80	43"-TB	97
Dynamic Gold Steel 45" Wood Shafts (pre 1996 trimming instructions)																		
R200	121.0	.334	.599	24.06	22.06	12.39	367.5	206.0	50.6	110.9	251	45	18	2.5	2.89	----	43"-M1	90
R300	122.5	.334	.600	24.00	22.00	12.44	368.6	205.6	50.6	112.4	254	46	17	2.7	2.83	----	43"-M1	91
R400	124.2	.334	.601	24.00	22.00	12.51	370.1	205.5	50.6	114.0	254	46	18	2.6	2.82	----	43"-M1	92
S200	122.2	.334	.600	24.00	22.00	12.47	369.1	205.9	50.6	112.6	264	49	18	2.6	2.72	----	43"-M1	96
S300	123.9	.335	.600	24.00	21.94	12.51	369.9	205.3	50.6	114.0	265	50	19	2.6	2.67	----	43"-M1	97
S400	125.2	.336	.600	24.00	22.00	12.48	369.4	203.6	50.6	115.2	267	49	21	2.3	2.65	----	43"-M1	98
X100	121.1	.333	.600	24.06	22.06	12.40	367.8	205.9	50.6	111.3	270	52	20	2.6	2.55	----	43"-M1	100
Dynamic Gold Steel 39" Iron Shafts																		
R200	118.9	.368	.600	19.81	18.44	8.99	420.5	260.0	50.6	109.9	305	80	52	1.5	1.83	----	37.5"	76
R300	120.5	.370	.602	19.81	18.44	9.02	421.7	259.8	50.6	111.3	307	81	52	1.6	1.82	----	37.5"	77
R400	122.3	.371	.602	19.69	18.31	9.05	422.5	259.1	50.6	112.8	308	83	54	1.5	1.77	----	37.5"	79
S200	122.1	.368	.602	19.81	18.38	9.04	422.0	258.4	50.6	113.0	320	88	57	1.5	1.68	----	37.5"	83
S300	123.8	.369	.600	19.75	18.38	9.07	423.1	258.4	50.6	114.1	321	90	58	1.6	1.65	----	37.5"	83
S400	125.6	.368	.600	19.69	18.63	9.14	424.9	257.9	50.6	116.4	324	92	57	1.6	1.66	----	37.5"	84
X100	124.1	.369	.600	19.75	18.38	9.10	423.9	258.4	50.6	114.9	333	93	60	1.6	1.58	----	37.5"	87
Dynamic Gold Steel 37" Taper Tip Iron Shafts																		
R300	120.4	.354	.581	18.56	18.19	9.13	424.7	256.5	50.6	117.6	304	79	61	1.3	1.72	----	37.5"	79
S300	123.8	.356	.600	18.63	18.19	9.24	427.8	256.5	50.6	120.7	319				1.55	----	37.5"	84*
X100	124.0	.355	.600	18.56	18.19	9.25	428.5	256.6	50.6	121.3	334	93	68	1.4	1.49	1.51	37.5"	90
Dynamic Gold w/ SensiCore Steel 37" Taper Tip Iron Shafts																		
R300	119.9	.335	.581	18.56	18.13	9.13	424.6	257.3	50.0	117.4	293				1.92	1.94	37.5"	74*
S300	123.7	.354	.601	18.50	18.13	9.24	427.9	256.7	50.0	121.2	312				1.69	1.71	37.5"	80*

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Dynamic Gold w/ SensiCore Steel 38" Taper Tip Iron Shafts																		
R300	118.4	.354	.580	19.13	18.13	9.07	423.0	259.8	50.9	112.3	284	74	58	1.3	1.97	2.07	37.5"	73
S300	121.6	.356	.602	18.81	17.88	9.06	422.8	257.2	50.0	115.6	305	82	61	1.3	1.79	1.85	37.5"	80
Dynamic Lite Steel 47" R&S Combination Flex Wood Shaft																		
R	123.7	.334	.600	25.13	22.50	12.24	363.9	204.4	50.0	109.5	250				3.15	3.31	43"-BB	
R	123.7	.334	.600	25.13	22.19	12.33	365.9	207.7	50.0	108.2	252	43	15	2.9	3.09	3.31	43"-M2	88
S	123.3	.334	.601	25.13	22.44	12.26	364.5	203.9	50.0	110.6	261				2.96	3.28	43"-BB	
S	123.3	.334	.601	25.13	22.13	12.38	367.1	207.4	50.0	109.7	264	45	17	2.6	2.91	3.28	43"-M2	94
Dynamic Lite 41" R&S Combination Flex Iron Shaft																		
R	119.5	.368	.600	20.63	18.19	8.78	414.5	259.5	50.0	105.0	307				1.92	2.12	37.5"	77*
S	119.7	.369	.602	20.63	18.31	8.82	415.5	260.3	50.0	105.2	318				1.79	2.13	37.5"	81*
Dynamic Lite Steel 38" Taper Tip Iron Shafts																		
R	110.2	.355	.600	18.88	17.94	8.76	413.8	258.3	50.6	104.9	296	77	58	1.3	1.90	1.93	37.5"	76
S	112.8	.355	.599	18.94	18.00	8.77	414.2	256.3	50.6	107.3	314	84	63	1.3	1.68	1.81	37.5"	82
Dynamic Lite Steel 45" Wood Shafts (1996 trimming instructions)																		
R	113.2	.334	.603	24.00	22.50	12.09	360.8	204.1	51.0	105.7	252				3.10	3.18	43"-BB	
R	113.2	.334	.603	24.00	22.25	12.17	362.7	207.2	51.0	104.5	254	42	16	2.6	2.99	3.18	43"-M2	90
S	117.3	.334	.603	24.00	22.56	12.22	363.6	203.3	51.0	109.3	261				2.95	3.03	43"-BB	
S	117.3	.334	.603	24.00	22.31	12.30	365.3	206.0	51.0	108.3	263	47	18	2.6	2.85	3.03	43"-M2	95
Dynamic Lite Steel Wood Shafts (pre 1996 trimming instructions)																		
R	113.3	.333	.601	24.00	21.94	12.17	362.7	208.2	50.6	103.9	258				2.80	3.17	43"-M1	94*
S	119.3	.332	.600	23.88	21.88	12.38	367.0	206.8	50.6	109.6	269				2.60	2.93	43"-M1	100*
Dynamic Lite 39" Steel Iron Shafts																		
R	110.1	.368	.598	19.38	18.13	8.69	412.0	259.7	50.6	101.7	307				1.83	2.02	37.5"	78*
S	117.7	.370	.601	19.56	18.25	8.89	417.7	258.1	50.6	109.0	326	88	56	1.6	1.62	1.80	37.5"	84
Dynamic Lite Graphite Wood Shafts (1995-97 version)																		
R	82.0	.343	.600	23.63	21.75	11.03	339.7	214.3	50.6	74.8	266	52	19	2.7	3.34	3.82	43"-M1	95
S	83.7	.336	.600	23.50	21.88	11.08	340.5	212.9	50.6	77.0	276	57	20	2.7	3.54	4.11	43"-M1	98
X	84.8	.336	.601	23.50	21.63	11.15	341.9	213.5	50.6	77.8	285	59	26	2.3	3.57	4.13	43"-M1	103

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Dynamic Lite Graphite Iron Shafts																		
R	75.2	.368	.601	20.00	18.13	7.63	384.3	266.3	50.0	68.0	295	79	47	1.7	4.04	4.58	37.5"	68
S	78.0	.370	.604	20.25	18.38	7.74	387.3	266.5	50.0	70.8	304	80	47	1.7	4.07	4.54	37.5"	69
Dynamic Lite Graphite 38" Iron Shafts (1995-96 version)																		
R	82.3	.369	.600	19.13	18.25	8.00	393.8	264.8	50.6	78.4	291	76	55	1.4	3.66	3.72	37.5"	69
S	84.2	.369	.598	18.88	18.13	8.06	395.2	263.8	50.6	80.8	312				3.19	3.28	37.5"	71*
X	89.8	.368	.601	19.00	18.19	8.23	399.6	262.9	50.6	86.1	328	91	67	1.4	3.31	3.40	37.5"	82
Dynamic Lite Graphite 38" Taper Tip Iron Shafts (1995 version)																		
R	83.9	.351	.601	18.94	18.06	8.04	394.5	263.8	50.6	80.1	298	78	59	1.3	3.65	3.72	37.5"	72
S	85.6	.350	.599	18.94	18.06	8.10	396.3	263.8	50.6	81.9	300	80	62	1.3	3.39	3.45	37.5"	74
Dynamic Tour Graphite Wood Shafts (1994 version; predecessor of current Dynamic Graphite)																		
R	100.3	.337	.619	24.31	22.13	11.39	346.4	209.3	46.0	91.1	245	43	14	3.1	3.79	4.30	43"-M1	82
S	105.5	.339	.620	24.06	21.94	11.54	349.5	207.1	46.0	96.4	265	48	27	1.8	3.60	4.05	43"-M1	94
X	106.7	.337	.620	24.13	22.00	11.66	351.7	208.1	46.0	97.6	273	52	20	2.6	3.63	4.11	43"-M1	96
Dynamic Tour Graphite 38" Iron Shafts (1994 version, predecessor of current Dynamic Graphite)																		
R	105.7	.369	.601	18.88	18.31	8.78	414.6	262.0	50.6	102.0	300	79	68	1.2	2.25	2.29	37.5"	78
S	101.0	.370	.600	18.88	18.25	8.68	411.6	263.3	50.6	97.7	310	84	69	1.2	2.75	2.84	37.5"	79
EI-60 Wood Shaft																		
L	68.3	.336	.580	21.50	19.88	9.98	324.9	211.5	50.6	62.8	252	46	27	1.7	4.67	----	42"-M1	82
A	67.9	.338	.600	22.88	21.25	10.36	327.4	213.6	50.8	63.2	242	44	13	3.4	5.19	----	43"-M1	78
EI-70 High Impact Wood Shafts (for oversized metal woods)																		
R	77.0	.335	.577	22.25	20.88	10.57	331.0	207.7	50.8	72.5	260	44	21	2.1	3.71	3.90	43"-BB	92
S	81.6	.337	.581	22.31	21.00	10.77	334.9	206.9	50.8	77.2	273	49	20	2.5	3.43	3.72	43"-BB	98
X	85.7	.338	.578	22.19	21.00	10.94	337.9	204.9	50.8	82.2	285	55	27	2.0	3.35	3.61	43"-BB	107
EI-70 Wood Shafts (1999-2004)																		
S	86.3	.335	.582	23.50	21.88	11.76	334.4	203.2	51.0	80.2	268	48	20	2.4	3.73		44"-M2	99
Tour S	82.3	.335	.606	23.75	22.06	11.63	332.3	204.8	51.0	76.5	267	49	22	2.2	4.13		44"-M2	99

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
EI-70 Wood Shafts (prior to 1999)																		
R	77.5	.338	.583	23.44	21.50	10.84	335.9	214.1	50.8	71.0	263	50	19	2.6	3.37	3.75	43"-M1	93
S	79.3	.338	.581	23.06	21.13	10.88	336.8	212.7	50.8	73.3	265	53	23	2.3	3.30	3.61	43"-M1	96
X	83.8	.338	.585	23.44	21.56	11.12	341.3	213.4	50.8	77.1	286	61	24	2.5	3.27	3.66	43"-M1	105
EI-70 Wood Shafts (pre 1995 version)																		
R	77.2	.337	.585	23.13	21.25	10.68	333.0	211.3	50.6	71.1	261				3.21	----	43"-M1	93*
S	79.3	.337	.578	22.88	20.98	10.74	334.3	210.5	50.8	73.0	268	52	26	2.0	3.27	3.65	43"-M1	98
EI-70 Iron Shafts																		
R	77.4	.375	.579	20.06	18.13	7.72	386.8	266.4	50.8	69.6	309	85	51	1.7	2.57	2.92	37.5"	75
S	78.4	.370	.579	20.06	18.13	7.74	387.2	265.5	50.8	70.9	319	90	57	1.6	2.62	2.93	37.5"	79
X	82.3	.373	.578	20.13	18.19	7.86	390.2	264.5	50.8	74.9	335	96	58	1.7	2.69	3.03	37.5"	83
EI-70 Tour Wood Shaft (pre 1995 version)																		
S	-----	-----	-----	-----	21.19	11.14	341.5	211.0	50.6	79.9	284	59	29	2.0	3.19	----	43"-M1	106
EI-70 Tour Wood Shafts (prior to 1999)																		
S	86.9	.341	.600	22.88	21.00	11.17	342.1	211.6	50.6	79.9	286	59	31	1.9	3.17	3.69	43"-M1	107
X	84.4	.335	.599	22.94	21.06	11.02	339.3	211.2	50.6	77.5	287	57	31	1.8	3.11	3.55	43"-M1	107
EI-70 Tour Iron Shafts																		
S	91.4	.373	.598	21.06	19.00	8.27	400.7	266.9	50.6	83.2	313	88	52	1.7	2.08	2.41	37.5"	78
X	92.4	.372	.601	21.00	19.00	8.28	401.0	266.3	50.6	84.1	333	96	59	1.6	2.12	2.39	37.5"	85
Endurance 42" A&L Combination Flex Iron Shaft																		
L	74.8	.371	.598	20.69	17.38	6.87	374.6	265.8	47.1	62.5	217	46	35	1.3	3.57	4.15	36.5"	44
A	73.5	.373	.601	20.75	18.00	7.47	380.6	266.9	51.0	62.7	237	55	35	1.6	3.46	4.12	37.5"	52
Endurance 47" R&S Combination Flex Wood Shaft																		
R	78.3	.338	.593	23.81	21.63	10.60	331.6	209.8	51.0	70.8	244				4.89	5.33	43"-BB	
R	78.3	.338	.593	23.81	21.38	10.70	333.3	212.4	51.0	69.9	247	41	14	2.9	4.83	5.33	43"-M2	81
S	78.1	.337	.599	24.51	21.94	10.57	331.0	210.2	51.0	69.8	247				4.63	5.15	43"-BB	
S	78.2	.337	.599	24.51	21.69	10.70	333.3	213.2	51.0	69.1	249	43	12	3.6	4.40	5.15	43"-M2	82
Endurance 42" R&S Combination Flex Iron Shaft																		
R	80.7	.372	.600	20.88	18.13	7.73	387.1	265.9	51.0	70.2	286	77	45	1.7	3.98	4.61	37.5"	66
S	79.7	.371	.599	20.75	17.94	7.67	385.7	265.6	51.0	69.1	296	79	51	1.5	3.89	4.66	37.5"	70

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
ExtraLite Wood Shafts																		
R	102.8	.333	.599	22.69	21.00	11.53	349.2	204.1	50.0	95.1	257	45	21	2.1	2.78	3.02	43"-M2	94
S	105.3	.334	.608	22.63	21.00	11.61	350.9	203.3	50.0	97.6	271	46	26	1.8	2.52	2.74	43"-M2	102
X	106.1	.333	.619	22.44	20.88	11.67	352.1	203.7	50.0	98.4	273	45	29	1.6	2.42	2.69	43"-M2	104
ExtraLite Iron Shafts																		
R	107.5	.369	.598	20.00	18.19	8.54	408.0	261.7	50.0	96.3	304	83	50	1.7	2.05	2.28	37.5"	75
S	109.1	.368	.601	20.19	18.31	8.61	410.0	261.9	50.0	98.1	318	84	53	1.6	1.92	2.17	37.5"	79
X	111.3	.369	.610	20.00	18.13	8.62	410.2	260.1	50.0	100.1	324	88	60	1.5	1.73	1.92	37.5"	84
Flex Flow 43" Reinforced Tip for Metal Wood Shaft																		
R	107.8	.335	.601	21.88	21.00	12.06	360.3	207.1	50.8	102.4	241	44	17	2.6	2.89	----	43"-M1	87
S	111.8	.333	.601	22.13	21.25	12.21	363.4	206.4	50.8	106.2	254	49	18	2.7	2.67	----	43"-M1	93
Gold Plus Wood Shafts																		
R300	104.0	.335	.607	22.19	21.31	11.67	352.1	201.4	51.0	99.7	253				2.85	2.91	43"-BB	
R300	104.0	.335	.607	22.19	21.06	11.77	354.0	204.6	51.0	98.4	255	43	18	2.4	2.74	2.91	43"-M2	92
S300	106.2	.333	.611	22.06	21.19	11.71	352.9	200.0	51.0	101.9	260				2.69	2.78	43"-BB	
S300	106.2	.333	.611	22.06	20.94	11.82	355.1	203.6	51.0	100.5	262	47	22	2.1	2.57	2.78	43"-M2	98
Gold Plus Wood Shafts (pre 1996 trimming instructions)																		
L300	95.7	.335	.582	22.00	20.19	11.03	345.1	207.5	50.6	87.0	227	37	15	2.5	3.42	----	42"-M1	74
R200	103.2	.335	.611	22.38	20.88	11.74	353.5	205.7	51.6	96.2	250	43	21	2.0	2.72	----	43"-M1	91
R300	104.4	.335	.614	22.25	20.88	11.80	354.7	205.7	51.6	97.4	253	44	21	2.1	2.66	----	43"-M1	93
R400	105.8	.335	.611	22.13	20.81	11.82	355.3	204.7	51.6	99.0	254	45	21	2.1	2.62	----	43"-M1	93
S200	105.1	.335	.613	22.25	21.00	11.85	355.9	206.2	51.6	98.1	257	48	22	2.2	2.52	----	43"-M1	96
S300	107.7	.337	.613	22.25	20.88	11.83	355.5	203.6	51.6	100.3	256	46	23	2.0	2.52	----	43"-M1	96
S400	105.2	.335	.611	22.13	20.75	11.84	355.7	205.7	51.6	98.4	259	47	23	2.0	2.47	----	43"-M1	97
Gold Plus Iron Shafts																		
L300	95.5	.368	.581	19.44	17.63	7.91	401.2	265.1	50.6	85.5	281	71	47	1.5	2.25	----	36.5"	63
R300	102.7	.371	.600	19.81	18.13	8.47	406.1	261.9	50.6	93.6	292	73	51	1.4	1.98	----	37.5"	72
S300	106.6	.370	.611	19.88	18.06	8.55	408.2	259.9	50.6	97.7	305	79	55	1.4	1.83	----	37.5"	77

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Gold Plus with SensiCore Wood Shafts																		
R300	110.0	.333	.608	22.50	21.63	11.89	356.7	200.9	50.0	105.8	254				2.78	2.88	43"-BB	
R300	110.0	.333	.608	22.50	21.31	12.00	359.0	204.5	50.0	104.5	257	43	21	2.0	2.73	2.88	43"-M2	94
S300	113.2	.332	.609	22.50	21.69	12.01	359.3	200.5	50.0	108.8	261				2.69	2.77	43"-BB	
S300	113.2	.332	.609	22.50	21.38	12.10	361.1	203.6	50.0	107.5	264				2.61	2.77	43"-M2	98*
Jet Step 47" R&S Combination Flex Wood Shaft																		
R	133.0	.336	.600	25.00	22.00	12.68	374.0	207.9	50.8	115.3	251				2.69	----	43"-M1	93*
S	133.0	.336	.602	25.00	21.94	12.72	374.8	207.0	50.8	117.0	263	53	21	2.5	2.52	----	43"-M1	99
Jet Step 41" R&S Combination Flex Iron Shaft																		
R	128.3	.367	.600	21.13	18.50	9.09	423.6	261.2	50.8	111.6	299	85	54	1.6	1.78	----	37.5"	78
S	128.2	.368	.600	21.13	18.63	9.12	424.4	261.5	50.8	112.1	310	92	53	1.7	1.69	----	37.5"	81
Modulus EV40 Wood Shafts (1993-1994 version)																		
R	89.9	.337	.596	23.69	21.81	11.27	344.3	211.0	50.6	82.7	258	47	24	2.0	4.14	----	43"-M1	89
S	90.0	.334	.598	23.88	21.88	11.28	344.4	211.0	50.6	82.8	270	55	23	2.4	4.30	----	43"-M1	95
Modulus EV40 Wood Shafts (1991 - 92 version)																		
R	-----	-----	-----	-----	21.69	11.23	343.3	212.6	50.6	80.1	262				3.35	----	43"-M1	93*
S	-----	-----	-----	-----	22.25	11.41	347.0	214.3	50.6	82.1	263	48	17	2.8	3.15	----	43"-M1	93
Modulus EV40 Wood Shafts (1990 version)																		
R	88.1	.336	.600	24.63	22.75	11.38	346.4	214.3	51.6	80.5	248	45	13	3.5	4.08	----	43"-M1	83
S	88.1	.335	.600	24.63	22.63	11.39	346.6	214.5	51.6	80.5	252	44	15	2.9	4.15	----	43"-M1	84
Pro Fit 47" R&S Combination Flex Wood Shaft																		
R	134.0	.333	.599	25.13	21.94	12.66	373.4	206.1	50.6	116.7	258				2.73	3.08	43"-M1	95*
S	135.0	.332	.600	25.13	21.94	12.77	375.8	205.8	50.6	119.4	272				2.53	3.06	43"-M1	102*
Quantum Iron Shafts																		
R	126.3	.370	.600	20.38	18.63	9.13	424.6	260.4	50.0	114.2	284				2.23	2.43	37.5"	69*
S	126.9	.370	.599	20.25	18.44	9.08	423.4	258.9	50.0	114.5	299	80	50	1.6	2.07	2.23	37.5"	74
X	130.0	.370	.600	20.31	18.50	9.20	426.6	259.4	50.0	117.2	313	86	53	1.6	1.93	2.12	37.5"	79

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Regency 47" A&L Combination Flex Wood Shaft																		
L	74.6	.336	.596	24.56	21.31	9.31	313.4	209.6	39.9	63.9	232	33	8	4.1	5.24	5.77	42"-M2	67
A	74.8	.336	.598	24.50	21.94	10.44	328.9	212.8	50.0	66.1	230	37	7	4.9	5.13	5.85	43"-M2	71
Regency 47" R&S Combination Flex Wood Shaft																		
R	77.4	.337	.601	24.38	21.69	10.49	329.8	211.6	50.0	68.2	239	39	11	3.5	5.22	5.72	43"-M2	76
S	79.4	.333	.601	24.44	21.88	10.65	332.6	211.6	50.0	71.0	247	43	10	4.3	5.03	5.87	43"-M2	79
Regency 42" A&L Combination Flex Iron Shaft																		
L	79.2	.372	.601	20.81	17.44	6.70	370.5	264.0	39.9	66.6	283	74	49	1.5	4.06	4.96	36.5"	61
A	79.5	.372	.602	20.69	17.81	7.60	384.0	265.6	50.0	68.4	285	74	49	1.5	4.07	4.98	37.5"	66
Regency 42" R&S Combination Flex Iron Shaft																		
R	82.3	.371	.604	20.88	18.00	7.73	387.0	265.8	50.0	71.2	286	75	47	1.6	4.05	4.74	37.5"	66
S	81.8	.372	.603	20.81	18.00	7.70	386.2	266.3	50.0	69.9	297	82	49	1.7	3.92	4.76	37.5"	70
Release Steel Wood Shafts																		
Ladies	107.4	.334	.582	22.38	20.69	11.23	349.0	202.8	47.3	98.9	232	37	16	2.3	3.31	3.58	42"-M2	76
Men's	110.0	.334	.602	22.88	21.25	11.82	355.2	202.4	51.0	101.8	234	35	16	2.2	3.20	3.34	43"-M2	81
Release Wood Shafts (pre 1996 trimming instructions)																		
Ladies	109.0	.334	.579	22.25	20.31	11.29	350.5	203.9	47.3	99.3	232				3.21	3.43	42"-M1	80*
Men's	118.7	.333	.601	22.69	20.88	11.83	355.6	205.0	50.6	100.0	233	36	18	2.3	3.06	3.34	43"-M1	81
Release Iron Shafts																		
Ladies	100.6	.369	.579	19.56	17.69	7.82	399.0	261.5	47.3	90.2	270	69	45	1.5	2.41	2.69	36.5"	61
Men's	105.4	.370	.600	19.88	18.06	8.46	405.8	260.9	50.6	94.3	275	74	49	1.5	2.18	2.39	37.5"	69
Release 38" Taper Tip Iron Shaft																		
Men's	106.4	.352	.601	19.06	18.13	8.67	411.5	259.8	50.6	101.1	284	71	50	1.4	2.01	2.08	37.5"	70
Release with SensiCore Wood Shafts																		
Ladies	113.3	.334	.577	22.31	20.75	11.45	353.8	201.8	47.1	104.9	230	36	17	2.1	3.36	3.58	42"-M2	76
Men's	118.0	.332	.602	23.00	21.44	12.22	363.6	203.2	51.0	109.4	233				3.21	3.45	43"-M2	83*
Release with SensiCore Iron Shafts																		
Ladies	109.6	.369	.580	19.44	17.56	8.12	407.0	260.7	47.1	99.2	274	70	45	1.6	2.38	2.59	36.5"	62
Men's	112.5	.369	.600	19.94	18.19	8.75	413.6	260.5	51.0	102.1	276	67	45	1.5	2.24	2.44	37.5"	65

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Release Graphite Wood Shafts (1999 version)																		
Men's	66.4	.334	.597	24.31	21.75	10.18	324.2	215.0	50.2	59.0	235	38	12	3.2	5.39	5.96	43"-M2	75
Release Graphite Iron Shafts (1999 version)																		
L	69.9	.369	.578	18.94	17.44	6.69	370.3	266.2	39.7	64.4	288	76	55	1.4	4.93	5.49	36.5"	63
Men's	68.1	.369	.598	19.94	18.06	7.41	379.2	268.4	50.2	60.6	280	72	46	1.6	4.35	4.99	37.5"	64
Release Graphite Wood Shafts (pre 1999 version)																		
Ladies	69.4	.337	.593	22.50	20.63	9.87	322.9	212.4	47.3	63.2	226				4.52	5.09	42"-M1	73*
Men's	76.4	.338	.604	23.69	21.75	10.79	335.1	215.2	50.6	69.3	245	47	14	3.4	4.57	5.23	43"-M1	81
Release Graphite Iron Shafts (pre 1999 version)																		
Ladies	79.7	.373	.580	19.00	17.69	7.32	385.7	264.8	47.3	73.6	286				3.83	4.30	36.5"	59*
Men's	87.6	.371	.599	20.63	18.63	8.05	394.8	265.7	50.6	78.5	293	79	50	1.6	3.83	4.34	37.5"	69
Rocket BiMatrix Wood Shafts																		
R	76.7	.332	.595	22.13	20.44	10.92	319.8	198.4	50.6	70.8	256	44	16	2.8	4.84	5.03	44"-M2	89
S	78.4	.333	.599	22.19	20.50	11.09	322.5	199.8	50.6	72.1	262	46	15	3.1	4.65	4.83	44"-M2	92
Rocket Graphite Wood Shafts																		
R	64.3	.336	.599	22.75	22.00	11.07	306.3	193.9	50.6	61.8	237	32	10	3.2	5.25	5.50	45"-BB	81
S	67.0	.336	.601	22.72	21.88	11.22	308.5	193.4	50.6	64.5	246	35	11	3.2	5.16	5.36	45"-BB	86
Rocket Steel Wood Shafts																		
R	115.5	.333	.601	24.56	23.06	12.30	365.3	204.6	51.0	109.7	280				2.75	3.14	43"-BB	
R	115.5	.333	.601	24.56	22.75	12.40	367.6	207.9	51.0	108.7	281	56	17	3.3	2.70	3.14	43"-M2	104
R	117.2	.333	.601	24.88	22.88	12.52	370.2	210.6	50.6	109.0	285				2.68	3.25	43"-M1	105*
S	119.6	.333	.601	24.88	23.44	12.53	370.6	206.3	51.0	113.3	293				2.72	3.11	43"-BB	
S	119.6	.333	.601	24.88	23.13	12.61	372.3	209.1	51.0	112.2	295	60	18	3.3	2.64	3.11	43"-M2	110
S	119.6	.333	.601	24.88	22.88	12.59	372.0	210.0	51.0	111.0	296				2.56	3.11	43"-M1	110*
Rocket Steel with SensiCore Wood Shafts																		
RR	122.9	.335	.581	23.75	22.13	12.43	368.2	201.8	50.0	116.4	273				2.86	3.26	43"-BB	
RR	122.9	.335	.581	23.75	21.81	12.51	369.9	204.6	50.0	115.3	276	50	19	2.6	2.75	3.26	43"-M2	101
R	122.3	.332	.602	24.94	23.44	12.58	371.7	205.2	50.0	116.5	284				2.78	3.20	43"-BB	
R	122.3	.332	.602	24.94	23.13	12.68	374.0	208.7	50.0	115.3	286	53	17	3.1	2.70	3.20	43"-M2	105
S	126.5	.332	.604	25.06	23.44	12.75	375.7	205.0	50.0	120.7	293				2.69	3.07	43"-BB	
S	126.5	.332	.604	25.06	23.19	12.85	378.0	208.2	50.0	119.8	295	61	18	3.4	2.59	3.07	43"-M2	111

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Rocket Steel with Sensicore Iron Shafts																		
RR	114.7	.371	.580	20.56	18.94	8.93	418.8	263.4	50.0	105.4	313	89	52	1.7	1.96	2.28	37.5"	79
R	115.8	.368	.605	20.06	18.56	8.88	417.2	260.9	50.0	106.3	322	90	57	1.6	1.79	2.02	37.5"	83
S	120.5	.367	.603	20.94	19.44	9.14	425.1	264.3	50.0	110.8	342	96	51	1.9	1.78	2.05	37.5"	85
SensiCore Graphite Tour Flight Wood Shafts																		
R	71.0	.336	.600	24.13	21.94	10.40	327.9	213.8	50.0	64.1	253	43	27	1.6	3.94	4.35	43"-M2	90
S	71.9	.337	.599	24.25	22.06	10.43	328.5	213.6	50.0	64.9	244	40	25	1.6	3.96	4.32	43"-M2	86
SensiCore Graphite Tour Flight Iron Shafts																		
R	77.6	.372	.600	20.44	18.13	7.70	386.0	267.5	50.0	68.5	272	65	50	1.3	4.21	4.87	37.5"	62
S	77.4	.371	.598	20.44	18.13	7.68	385.9	267.5	50.0	68.4	279	70	51	1.4	4.23	4.82	37.5"	64
SensiCore Graphite Mid Flight Wood Shafts																		
R	71.0	.338	.599	24.31	22.00	10.38	327.7	213.9	50.0	63.8	246	42	21	2.0	4.27	4.62	43"-M2	85
S	71.7	.338	.601	24.38	22.13	10.43	328.6	214.2	50.0	64.4	249	42	21	2.0	4.28	4.62	43"-M2	86
SensiCore Graphite Mid Flight Iron Shafts																		
R	80.7	.371	.599	20.63	18.25	7.81	389.0	267.6	50.0	71.4	286	73	50	1.5	4.61	5.27	37.5"	65
S	83.2	.373	.601	20.81	18.50	7.90	391.3	267.6	50.0	73.7	300	82	51	1.6	4.43	5.02	37.5"	70
SensiCore Graphite High Flight Wood Shaft																		
S	74.3	.339	.601	24.38	22.19	10.54	330.5	213.3	50.0	67.2	270	52	22	2.4	4.53	4.92	43"-M2	94
SensiCore Graphite High Flight Iron Shafts																		
R	83.3	.373	.598	20.81	18.56	7.91	391.6	267.8	50.0	73.8	287	77	48	1.6	4.77	5.42	37.5"	66
S	85.4	.373	.602	20.94	18.63	7.95	392.4	266.4	50.0	76.0	297	80	49	1.6	4.69	5.36	37.5"	68
Stratus with Sensicore Wood Shafts																		
R	118.2	.333	.600	22.88	21.31	12.28	365.0	204.3	51.0	109.7	252				2.90	3.10	43"-BB	
R	118.2	.333	.600	22.88	21.06	12.35	366.7	207.3	51.0	108.4	254	43	17	2.5	2.88	3.10	43"-M2	91
S	121.0	.334	.600	22.75	21.19	12.35	366.5	203.0	51.0	112.5	259				2.79	2.95	43"-BB	
S	121.0	.334	.600	22.75	20.94	12.43	368.2	206.1	51.0	111.1	261	45	20	2.3	2.76	2.95	43"-M2	95
Stratus with Sensicore Iron Shafts																		
R	114.4	.369	.602	20.25	18.50	8.85	416.4	260.9	51.0	104.5	296	76	53	1.4	1.96	2.16	37.5"	74
S	117.1	.367	.603	20.31	18.56	8.94	418.9	260.9	51.0	107.0	304	82	55	1.5	1.89	2.07	37.5"	78

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Tri Gold Graphite 38" Iron Shafts (long irons play softer than DSFI ratings, while scoring irons play stiffer than DSFI ratings)																		
R	74.4	.366	.599	18.69	17.69	7.78	388.1	267.1	50.2	70.8	297	79	59	1.3	3.16	3.19	37.5"	73
S	73.9	.369	.597	18.69	17.75	7.75	387.6	266.9	50.2	70.5	306	84	58	1.4	3.25	3.28	37.5"	75
Tri Gold Steel 39" Iron Shafts (long irons play softer than DSFI ratings, while scoring irons play stiffer than DSFI ratings)																		
R	115.8	.367	.612	19.06	17.56	8.87	416.9	259.4	50.2	107.3	293	76	53	1.4	2.00	2.06	37.5"	73
S	115.7	.369	.607	18.94	17.50	8.86	416.8	259.1	50.2	107.5	302	81	56	1.4	1.89	1.95	37.5"	77
True Lite Graphite Wood Shafts																		
R	64.2	.337	.598	22.63	22.25	11.12	307.1	193.1	51.0	63.0	243				3.57	3.68	45"-BB	
R	64.2	.337	.598	22.63	21.31	10.02	321.6	209.9	51.0	60.7	247				3.54	3.68	43"-BB	
R	64.2	.337	.598	23.63	21.06	10.07	322.4	211.5	51.0	59.9	250	41	20	2.1	3.48	3.68	43"-M2	88
S	64.9	.337	.596	23.00	22.63	11.27	309.3	194.3	51.0	64.0	259				3.57	3.67	45"-BB	
S	64.9	.337	.596	23.00	21.81	10.12	323.1	210.7	51.0	61.4	265				3.55	3.67	43"-BB	
S	64.9	.337	.596	23.00	21.56	10.22	324.9	213.2	51.0	60.7	267	48	18	3.2	3.48	3.67	43"-M2	94
True Lite Graphite Iron Shafts																		
R	65.2	.372	.598	19.81	17.94	7.27	375.9	267.1	50.6	58.2	294				3.56	3.96	37.5"	65*
S	67.5	.375	.599	19.88	18.06	7.35	377.9	267.1	50.6	60.2	313				3.23	3.72	37.5"	71*
True Lite 55 Graphite Wood Shafts																		
L	53.2	.334	.582	22.75	21.25	9.85	290.5	193.5	47.4	49.6	223	30	13	2.3	7.46	7.86	44"-BB	70
A	54.9	.336	.605	23.25	22.44	10.62	299.3	196.2	50.0	53.1	231	30	12	2.5	6.40	6.52	45"-BB	77
R	57.1	.338	.599	23.69	22.81	10.85	302.9	196.3	51.0	55.6	240				5.94	6.11	45"-BB	81*
S	56.5	.337	.599	24.00	23.19	10.86	303.1	197.6	51.0	54.5	245	36	12	3.0	6.16	6.36	45"-BB	83
TT Lite Steel 47" R&S Combination Flex Wood Shaft																		
R	122.3	.333	.600	25.19	22.63	12.18	362.8	203.3	51.0	108.5	249				3.18	3.30	43"-BB	
R	122.3	.333	.600	25.19	22.31	12.28	365.0	206.6	51.0	107.4	250	40	14	2.9	3.09	3.30	43"-M2	87
S	122.1	.333	.601	25.19	22.63	12.24	364.0	203.0	51.0	110.0	261				2.94	3.30	43"-BB	
S	122.1	.333	.601	25.19	22.31	12.34	366.3	206.3	51.0	109.0	262	44	15	2.9	2.85	3.30	43"-M2	93
TT Lite 41" R&S Combination Flex Iron Shaft																		
R	118.8	.370	.598	20.50	18.06	8.76	413.9	258.8	50.6	104.5	312	88	54	1.6	1.76	----	37.5"	80
S	118.7	.369	.600	20.50	18.13	8.78	414.4	259.5	50.6	104.3	323	91	58	1.6	1.65	----	37.5"	84

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
TT Lite Steel 45" R&S Combination Flex Reinforced Tip for Metal Wood Shaft																		
R	117.1	.333	.601	22.63	20.69	12.13	361.8	204.5	50.8	106.5	243	44	21	2.1	2.73	----	43"-M1	89
S	116.8	.332	.601	22.75	20.88	12.17	362.6	205.1	50.8	106.7	252	46	20	2.3	2.54	----	43"-M1	93
TT Lite Steel 46" A&L Combination Flex Wood Shaft (pre 1996 trimming instructions)																		
L	----	----	----	----	21.38	11.28	350.2	207.1	47.4	95.7	237	42	15	2.8	3.25	----	42"-M1	78
A	----	----	----	----	21.94	11.86	356.0	208.2	50.8	97.0	235	37	13	2.8	3.27	----	43"-M1	79
TT Lite Steel 47" R&S Combination Flex Wood Shaft (pre 1996 trimming instructions)																		
R	122.3	.333	.602	25.25	22.13	12.25	364.4	206.9	50.6	106.9	255	45	16	2.8	2.87	----	43"-M1	91
S	122.3	.335	.600	25.25	22.06	12.31	365.7	206.9	50.6	108.2	266	52	19	2.7	2.64	----	43"-M1	98
TT Lite Steel 44" Taper Tip Wood Shafts																		
R	109.8	.294	.620	23.50	23.13	11.75	353.7	200.4	46.2	107.1	252	37	12	3.1	3.23	3.28	43"-TB	87
S	114.3	.294	.620	23.63	23.25	11.93	357.6	200.1	46.2	111.3	265	42	13	3.2	2.98	3.03	43"-TB	94
TT Lite XL R&S Combination Flex Wood Shaft w/ SensiCore																		
R	129.4	.333	.604	25.88	22.56	12.44	368.7	207.0	50.2	111.5	246	40	14	2.9	3.01	3.52	43"-M2	88
S	130.2	.334	.603	25.88	22.44	12.51	370.0	205.9	50.2	113.9	260	44	15	2.9	2.94	3.53	43"-M2	94
TT Lite XL R&S Combination Flex Iron Shaft w/ SensiCore																		
R	132.3	.370	.600	21.81	18.50	9.04	422.1	260.3	50.2	111.6	317	86	54	1.6	1.82	2.19	37.5"	80
S	132.2	.370	.600	21.69	18.31	9.02	421.6	260.3	50.2	111.1	327	90	57	1.6	1.71	2.19	37.5"	84
TT Lite XL 48" Graphite A&L Flex Wood Shaft																		
L	75.1	.333	.582	23.63	20.44	9.30	313.0	208.4	39.7	64.9	256	44	16	2.8	5.59	6.76	42"-M2	78
A	75.4	.334	.578	23.69	20.81	10.36	327.4	211.1	50.2	66.1	248	41	14	2.9	5.73	6.71	43"-M2	79
TT Lite XL Graphite 48" R&S Flex Wood Shaft																		
R	73.5	.332	.597	25.00	21.63	10.35	327.2	213.9	50.2	63.1	253	44	15	2.9	6.60	7.47	43"-M2	80
S	73.8	.333	.597	24.94	21.63	10.43	328.5	213.6	50.2	64.7	260	47	17	2.8	6.41	7.52	43"-M2	84
TT Lite XL Graphite 43" A&L Flex Iron Shaft																		
L	73.7	.369	.598	21.13	16.94	6.35	362.6	263.7	39.7	59.2	252	60	44	1.4	4.73	5.45	36.5"	52
A	73.7	.368	.595	21.13	17.75	7.38	378.4	267.1	50.2	61.1	252	59	38	1.6	4.64	5.73	37.5"	54

TRUE TEMPER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
TT Lite XL Graphite 43" R&S Flex Iron Shaft																		
R	78.3	.370	.599	21.25	17.88	7.53	382.1	266.5	50.2	65.4	278	77	46	1.7	4.69	5.56	37.5"	64
S	79.1	.369	.599	21.31	17.94	7.56	382.8	266.3	50.2	66.3	283				4.52	5.53	37.5"	60*
TT Lite Graphite Wood Shafts (pre 1999 version)																		
L	71.9	.347	.583	21.94	20.25	9.98	324.8	211.4	47.3	66.1	256	46	19	2.4	4.48	4.93	42"-M1	81
A	90.5	.338	.581	24.50	22.38	11.41	347.1	213.3	50.8	83.0	258				4.86	5.43	43"-M1	85*
R	88.0	.340	.598	24.06	21.94	11.31	345.0	213.6	50.6	80.8	260	50	16	3.1	4.01	4.64	43"-M1	89
S	89.0	.336	.602	24.31	22.13	11.37	346.2	213.9	50.6	81.7	273	55	18	3.1	3.94	4.48	43"-M1	95
TT Lite Graphite Iron Shafts (pre 1999 version)																		
L	85.0	.380	.584	20.38	18.38	7.56	391.7	267.5	47.3	76.9	290	81	54	1.5	3.70	4.23	36.5"	66
A	84.7	.370	.581	20.94	18.88	8.01	394.1	266.4	50.8	76.9	277	69	48	1.4	3.70	4.29	37.5"	64
R	86.3	.382	.599	20.88	18.88	8.07	395.4	266.8	50.6	78.0	299	81	53	1.5	4.09	4.62	37.5"	71
S	87.5	.374	.601	21.00	18.94	8.14	397.3	267.4	50.6	79.3	316	85	53	1.6	3.83	4.38	37.5"	74
TX-90 Wood Shafts																		
A	102.3	.334	.608	24.25	22.09	11.64	351.6	208.5	50.6	92.5	268	49	16	3.1	2.76	3.01	43"-M2	97
R	104.7	.334	.612	24.25	22.00	11.74	353.5	208.1	50.6	94.8	275	49	20	2.5	2.57	2.84	43"-M2	101
S	107.3	.333	.609	24.25	21.94	11.83	355.5	207.8	50.6	97.1	281	51	22	2.3	2.42	2.67	43"-M2	106
TX-90 39" Taper Tip Irons																		
A	96.7	.357	.602	20.50	18.94	8.45	405.5	265.9	50.9	88.7	295	75	48	1.6	2.05	2.15	37.5"	72
R	98.8	.357	.602	20.19	18.63	8.47	405.9	264.4	50.9	90.6	303	79	49	1.6	1.97	2.12	37.5"	75
S	101.2	.353	.603	20.56	19.00	8.59	409.3	265.6	50.9	92.8	314	84	52	1.6	1.88	1.96	37.5"	78
TX-90 Tour Iron Shafts																		
R	105.8	.368	.602	20.44	18.19	8.51	407.0	263.1	51.0	92.9	292	77	46	1.7	2.09	2.35	37.5"	71
S	108.4	.367	.602	20.50	18.22	8.59	409.4	263.1	51.0	95.3	305	81	51	1.6	1.90	2.18	37.5"	76

TRUE TEMPER TI formerly known as TITANIUM SPORTS TECHNOLOGIES

Titanium Low Flex Wood Shaft											(formerly Titanium LF 220 Wood Shaft)							
R	109.6	.336	.601	23.81	20.94	11.68	352.4	204.9	50.8	96.7	246				3.10	3.47	43"-M1	88*
S	111.7	.335	.601	23.94	21.56	11.74	353.6	201.7	51.0	100.9	252				3.17	3.63	43"-BB	
S	111.7	.335	.601	23.94	21.31	11.85	355.8	205.0	51.0	99.8	255	45	14	3.2	3.08	3.63	43"-M2	90

TRUE TEMPER TI continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Titanium Low Flex Wood Shaft													(formerly Titanium LF 260 Wood Shaft)					
X	109.0	.335	.596	22.88	20.94	11.86	356.2	205.4	50.8	100.0	267	50	21	2.4	2.59	2.89	43"-M1	98
Titanium Tour Mid Flex Wood Shaft													(formerly Titanium MF 220 Wood Shaft)					
R	109.6	.335	.599	23.88	21.00	11.68	352.3	205.1	50.8	96.4	248				2.89	3.32	43"-M1	90*
Titanium Tour Mid Flex Wood Shaft													(formerly Titanium MF 260 Wood Shaft)					
X	110.4	.335	.595	23.00	21.00	11.94	357.7	205.4	50.8	101.5	270	51	29	1.8	2.31	2.66	43"-M1	105
Titanium Tour Mid Flex Iron Shafts													(formerly Titanium MF Iron Shafts)					
R	106.6	.368	.598	19.63	17.69	8.46	405.8	259.0	50.6	96.2	277	69	40	1.7	2.17	2.33	37.5"	65
S	107.1	.366	.598	20.00	18.13	8.55	408.1	260.6	50.6	96.9	294	78	45	1.7	1.98	2.14	37.5"	72
X	106.7	.368	.596	19.94	18.06	8.55	408.3	261.1	50.6	96.6	297	80	47	1.7	1.93	2.07	37.5"	74

UNIFIBER

Jewel Series Wood Shaft																		
L	86.6	.335	.605	23.50	21.25	10.83	341.0	212.8	50.3	77.9	241	44	19	2.3	4.45	----	43"-M1	78
MasterStroke Wood Shafts																		
R	----	----	----	----	22.00	11.39	346.5	213.7	50.6	82.2	255	48	17	2.8	3.93	----	43"-M1	87
S	----	----	----	----	22.19	11.71	352.9	212.3	50.6	90.0	264	51	20	2.6	4.23	----	43"-M1	91
PowerStroke Wood Shaft																		
S	93.2	.333	.600	23.44	22.25	11.49	348.5	211.1	50.6	86.8	267	52	24	2.2	4.24	----	43"-M1	93
T30 Wood Shaft																		
R	86.7	.332	.595	24.13	21.94	11.20	12.09	213.9	50.6	78.2	246	42	18	2.3	4.22	4.34	43"-M1	83
S	92.1	.334	.600	24.19	22.13	11.41	346.9	213.1	50.6	83.2	262	49	20	2.5	4.36	4.53	43"-M1	90
T30 Senior Wood Shaft (formerly Senior Statement)																		
A	87.7	.333	.607	23.50	21.88	11.25	343.9	212.3	50.3	81.3	234				4.20	----	43"-M1	79*
T40 Wood Shaft																		
R	85.8	.334	.598	23.63	21.31	10.97	338.5	211.5	50.6	76.4	245				4.71	4.83	43"-M1	81*
S	88.0	.335	.602	24.06	21.81	11.18	342.4	212.9	50.6	78.9	264	50	21	2.4	4.21	4.47	43"-M1	91

UNIFIBER continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
TB40 Wood Shaft (for oversized metal woods)																		
R	85.8	.335	.598	23.69	21.94	10.94	337.8	208.3	50.6	78.9	251	41	20	2.0	4.52	4.69	43"-BB	86
S	88.8	.335	.598	23.69	22.00	11.09	340.9	208.3	50.6	82.0	263	44	22	2.0	4.09	4.20	43"-BB	92
T50 Wood Shaft																		
S	95.9	.334	.608	23.63	22.13	11.68	352.3	211.6	51.6	89.1	265	51	23	2.2	3.13	----	43"-M1	96
X	98.5	.335	.610	23.63	22.06	11.76	353.9	211.2	51.6	91.1	269	56	26	2.2	2.99	----	43"-M1	101
XX	101.8	.334	.616	23.75	22.25	11.72	353.1	210.4	50.0	92.7	275				3.34	----	43"-M1	97*
Unifiber Lite Wood Shaft																		
R	67.3	.333	.592	24.13	22.00	10.33	327.0	215.5	50.3	61.2	250				3.74	----	43"-M1	86*
S	68.1	.333	.594	24.00	21.94	10.35	327.2	215.5	50.3	61.4	262				4.02	----	43"-M1	89*

UNITED SPORTS TECHNOLOGY (UST)

Competition 75 47" A&L Combination Flex Wood Shaft																		
L	80.8	.336	.592	24.50	21.44	10.23	311.8	199.9	41.8	70.1	245	40	18	2.2	5.75	6.03	43"-M2	79
A	82.4	.337	.597	24.56	22.28	11.35	327.2	203.2	50.6	73.4	244	39	15	2.6	5.75	6.23	44"-M2	81
Competition 75 47" R&S Combination Flex Wood Shaft																		
R	86.2	.338	.600	24.75	22.34	11.51	330.1	202.8	50.6	76.7	257	43	17	2.5	5.84	6.03	44"-M2	87
S	86.9	.337	.600	24.81	22.44	11.62	331.9	203.7	50.6	77.6	264	48	20	2.4	5.00	6.02	44"-M2	94
Easyflex Wood Shaft																		
-----	-----	-----	-----	-----	21.94	10.94	337.9	215.5	50.6	71.8	234	38	20	1.9	4.34	----	43"-M1	79
Easyflex Iron Shaft																		
-----	-----	-----	-----	-----	19.19	8.09	396.1	273.2	50.6	72.3	277	77	47	1.6	3.38	----	37.5"	66
Inertial Transfer IT Wood Shaft																		
S	89.8	.335	.620	27.13	26.63	12.90	337.0	199.6	50.0	87.4	283	51	20	2.6	4.68	4.71	45"-BB	108
IRoD Driver Wood Shaft																		
A	67.1	.338	.602	23.31	22.41	11.40	311.3	195.8	50.9	64.6	228	28	8	3.3	3.40	3.44	45"-BB	80
R	65.2	.336	.603	23.44	22.50	11.34	310.3	197.0	50.9	62.4	243	33	10	3.3	3.34	3.43	45"-BB	88
S	64.9	.338	.605	23.31	22.44	11.29	309.6	196.7	50.9	62.0	257	37	11	3.4	3.21	3.32	45"-BB	95

UNITED SPORTS TECHNOLOGY continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
iRoD Utility Fairway Wood Shaft																		
R	72.5	.338	.610	23.13	22.22	10.62	331.9	211.9	50.9	69.1	256	45	19	2.4	3.99	4.06	43"-BB	89
S	71.3	.339	.607	23.13	22.13	10.57	331.1	212.1	50.9	68.1	266	50	23	2.2	4.07	4.16	43"-BB	95
iRoD Hybrid Long Iron Shaft																		
R	77.1	.374	.598	20.53	19.50	8.71	363.5	240.7	50.9	71.9	261	56	30	1.9	2.74	2.89	39.5"	63
S	79.6	.374	.600	20.63	19.59	8.83	366.1	241.0	50.9	74.2	270	59	34	1.7	2.68	2.85	39.5"	67
Ladies Easyflex Wood Shaft																		
L	80.3	.338	.582	23.44	21.50	10.62	336.7	213.0	50.6	73.1	224	35	18	1.9	4.08	----	42"-M1	72
Ladies Easyflex Iron Shaft																		
L	79.8	.372	.581	20.94	18.88	7.54	391.1	269.7	50.6	70.8	270	69	47	1.5	3.62	----	36.5"	59
Low Carb .335" Wood Shafts																		
A	51.2	.339	.613	23.94	22.88	10.69	300.4	200.6	48.9	50.9	215	23	7	3.3	4.78	4.86	45"-BB	71
R	54.3	.338	.621	24.25	23.31	10.90	303.5	200.6	52.0	50.9	230	27	9	3.0	4.27	4.37	45"-BB	79
S	53.5	.338	.621	24.31	23.19	10.81	302.3	200.7	50.7	50.9	248	34	12	2.8	4.31	4.39	45"-BB	88
Low Carb .350" Wood Shaft																		
S	52.6	.354	.610	24.13	23.06	10.85	302.9	202.0	50.9	50.0	245	32	14	2.3	4.19	4.23	45"-BB	88
ProForce 55 Wood Shafts																		
R	62.8	.340	.609	24.16	23.25	11.14	307.3	197.1	50.2	60.0	245	30	10	3.0	5.65	5.70	45"-BB	81
S	62.8	.339	.611	24.38	23.38	11.16	307.5	197.2	50.2	60.1	266	36	14	2.6	5.49	5.56	45"-BB	92
ProForce 85 Wood Shafts																		
R	84.6	.337	.603	24.00	22.41	11.68	333.0	204.4	50.6	78.0	258	41	18	2.3	3.44	3.53	44"-M2	94
S	87.7	.338	.606	24.22	22.56	11.85	336.2	204.4	50.6	81.2	267	45	20	2.3	3.43	3.53	44"-M2	99
X	91.6	.339	.610	24.31	22.69	11.99	338.9	203.7	50.6	84.6	288	51	25	2.0	3.48	3.56	44"-M2	109
ProForce 95 Wood Shaft																		
S	97.9	.337	.607	24.38	22.63	12.24	343.6	203.1	50.6	89.9	272	44	24	1.8	2.74	2.80	44"-M2	105
ProForce 95 Parallel Tip Iron Shafts																		
R	95.6	.375	.600	17.06	16.56	8.31	401.7	258.5	50.2	93.0	309	77	65	1.2	2.09	2.14	37.5"	78
S	95.2	.375	.598	17.09	16.56	8.30	401.5	258.5	50.2	92.8	324	83	68	1.2	2.14	2.18	37.5"	83

UNITED SPORTS TECHNOLOGY continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
ProForce 95 Taper Tip Iron Shaft																		
S	94.8	.363	.602	17.25	16.69	8.32	402.1	259.6	50.2	92.3	319				2.20	2.22	37.5"	78*
ProForce ATR Wood Shafts																		
L	71.3	.339	.588	23.19	22.31	11.19	311.3	192.4	50.6	68.3	224	30	8	3.8	4.31	4.40	44"-BB	74
A	71.1	.340	.590	23.63	22.75	11.49	312.6	194.1	50.6	67.9	227	29	8	3.6	4.19	4.26	45"-BB	78
R	71.7	.338	.615	23.81	22.94	11.56	313.8	194.4	50.6	68.8	238	32	11	2.9	4.00	4.07	45"-BB	85
S	76.5	.340	.619	24.06	23.19	11.78	317.6	193.9	50.6	73.1	254	39	14	2.8	3.94	4.02	45"-BB	94
ProForce LT. Wood Shafts																		
R	90.4	.339	.617	26.44	25.88	12.85	336.3	197.9	50.6	87.8	263	43	15	2.9	3.97	3.99	45"-BB	99
S	92.2	.339	.616	26.38	25.81	12.90	337.2	197.2	50.6	89.4	278	47	18	2.6	3.64	3.67	45"-BB	107
X	93.9	.339	.623	26.41	25.88	13.00	339.1	197.4	50.6	91.1	285	49	21	2.3	3.63	3.65	45"-BB	112
ProForce LD Wood Shaft (D-5 swingweight)																		
X	87.1	.342	.620	26.50	24.38	13.26	319.2	189.3	50.6	79.3	264	39	12	3.3	3.99	4.17	47"-M2	104
ProForce XL Wood Shaft																		
A	55.8	.333	.597	23.88	22.88	10.88	303.5	199.8	50.6	53.1	224	27	6	4.5	4.84	4.86	45"-BB	74
R	57.5	.335	.601	23.94	22.88	10.96	304.6	199.3	50.6	54.7	240	34	10	3.4	4.65	4.73	45"-BB	84
S	59.8	.337	.601	23.88	23.00	11.07	306.2	198.3	50.6	57.3	259	41	15	2.7	4.56	4.64	45"-BB	95
Speed Rated 6 Wood Shaft																		
L	81.0	.336	.580	23.50	22.13	10.32	331.2	208.6	47.1	75.5	229				4.21	4.32	42"-BB	
L	81.0	.336	.580	23.50	21.88	10.43	333.2	211.6	47.1	74.5	228	35	17	2.1	4.19	4.32	42"-M2	71
Speed Rated Lite 6 Wood Shaft																		
L	63.7	.337	.602	23.13	20.88	9.46	299.8	202.6	39.7	57.5	218	29	15	1.9	5.78	5.95	43"-M2	68
Speed Rated 6 Iron Shaft																		
L	78.3	.370	.580	20.75	18.69	7.34	386.1	269.5	47.1	69.5	263	68	48	1.4	3.65	3.99	36.5"	58
Speed Rated 7 Wood Shaft																		
A	80.3	.335	.580	23.88	22.44	10.80	335.4	209.8	50.8	74.8	235				4.57	4.63	43"-BB	
A	80.3	.335	.580	23.88	22.19	10.91	337.3	212.7	50.8	73.8	235	37	18	2.1	4.54	4.63	43"-M2	79

UNITED SPORTS TECHNOLOGY continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Speed Rated Lite 7 Wood Shaft																		
A	66.5	.337	.609	23.56	21.69	10.85	318.6	206.7	50.6	61.3	232	30	20	1.5	5.93	6.05	44"-M2	77
Speed Rated 7 Iron Shaft																		
A	81.8	.371	.581	21.38	19.44	7.85	389.9	265.8	50.8	73.3	274	70	47	1.5	3.39	3.73	37.5"	64
Speed Rated 8 Wood Shaft																		
R	94.2	.335	.600	24.69	23.13	11.47	348.2	209.8	51.0	87.4	250				4.09	4.14	43"-BB	
R	94.2	.335	.600	24.69	22.88	11.53	349.3	212.1	51.0	86.2	249	45	19	2.4	4.07	4.14	43"-M2	87
Speed Rated Lite 8 Wood Shaft																		
R	69.6	.338	.611	23.81	21.94	11.00	321.1	206.6	50.6	63.9	251	37	24	1.5	5.02	5.11	44"-M2	87
Speed Rated 8 Iron Shaft																		
R	83.2	.370	.603	20.81	18.88	7.98	393.3	267.9	51.0	74.4	295	84	54	1.6	3.40	3.90	37.5"	72
Speed Rated 9 Wood Shaft																		
S	93.8	.335	.602	25.06	23.56	11.50	348.7	210.8	51.0	86.9	258				3.94	3.96	43"-BB	
S	93.8	.335	.602	25.06	23.31	11.58	350.3	213.8	51.0	85.5	258	49	18	2.7	3.92	3.96	43"-M2	90
Speed Rated Lite 9 Wood Shaft																		
S	71.4	.338	.617	24.00	22.19	11.10	322.9	206.8	50.6	65.5	263	42	25	1.7	5.03	5.15	44"-M2	93
Speed Rated 9 Iron Shaft																		
S	85.3	.371	.601	20.94	19.06	8.10	396.2	268.4	51.0	76.8	309	85	56	1.5	3.36	3.93	37.5"	75
Speed Rated 10 Wood Shaft																		
X	94.6	.335	.622	24.50	22.88	10.96	338.3	205.3	46.0	87.0	268				3.16	3.22	43"-BB	
X	94.6	.335	.622	24.50	22.50	11.05	339.9	208.3	46.0	85.6	267	46	22	2.1	3.15	3.22	43"-M2	96
Speed Rated Lite 10 Wood Shaft																		
X	72.3	.338	.618	24.22	22.38	11.17	323.9	207.0	50.6	66.3	271	47	25	1.9	5.14	5.26	44"-M2	97
Speed Rated 10 Iron Shaft																		
X	90.6	.372	.612	20.94	19.06	7.94	392.1	264.7	46.0	81.4	319	87	62	1.4	2.27	2.66	37.5"	81
Super 39 Wood Shaft																		
R	45.5	.337	.579	23.91	22.88	10.36	295.7	201.8	50.6	43.3	224	27	10	2.7	5.90	6.05	45"-BB	74

UNITED SPORTS TECHNOLOGY continued

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Super 47 Wood Shafts																		
R	48.6	.334	.608	23.94	23.00	10.36	295.8	199.4	50.0	46.4	233	32	10	3.2	5.45	5.49	45"-BB	79
S	49.6	.335	.614	24.25	23.31	10.42	296.5	199.2	50.0	47.3	247	37	11	3.4	5.37	5.42	45"-BB	85
Tour Weight Wood Shafts																		
R	100.8	.336	.597	24.00	22.19	11.78	354.4	211.6	50.6	92.2	252	46	19	2.4	3.17	3.24	43"-M1	90
3	105.0	.335	.602	24.13	22.25	11.94	357.7	211.3	50.6	95.8	260	47	20	2.4	2.98	3.08	43"-M1	93
Tour Weight Iron Shafts																		
R	112.5	.370	.601	20.69	18.88	8.84	416.3	263.1	50.6	102.6	309	86	54	1.6	1.95	2.31	37.5"	78
S	114.8	.371	.601	20.63	18.81	8.91	418.1	262.3	50.6	105.2	319	92	55	1.7	1.86	2.26	37.5"	82
X	115.3	.370	.599	20.75	18.88	8.94	419.1	262.5	50.6	106.0	329	94	56	1.7	2.04	2.46	37.5"	83
6600 Wood Shafts																		
R	-----	-----	-----	-----	22.38	11.09	340.7	213.5	47.1	80.1	250	44	21	2.0	3.08	----	43"-M1	90
S	-----	-----	-----	-----	22.31	11.17	342.1	212.5	47.1	82.5	263	48	24	2.0	2.82	----	43"-M1	97
660 Iron Shafts																		
R	86.1	.374	.610	20.94	19.00	7.98	393.1	265.5	50.6	77.0	302	81	53	1.5	2.15	----	37.5"	75
S	-----	-----	-----	-----	19.00	8.17	398.1	269.8	50.6	77.7	311	87	56	1.6	2.06	----	37.5"	79
8000 Wood Shaft																		
S	-----	-----	-----	-----	22.00	11.61	350.9	212.4	50.6	87.9	257	47	22	2.1	2.74	----	43"-M1	95
9200 Wood Shaft																		
S	-----	-----	-----	-----	21.81	11.34	345.6	213.3	50.6	81.7	260	50	25	2.0	3.17	----	43"-M1	95
910 Iron Shaft																		
S	-----	-----	-----	-----	19.19	8.33	402.4	270.5	50.6	81.3	329	94	53	1.8	2.43	----	37.5"	81