

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Apollo Balisik 44" L/A/R/S Steel Iron Shaft												(tip trimming L-flex 1.5", A-flex 2.5", R-flex 3.5", S-flex 4.5")						
L	127.1	.368	.602	22.88	18.56	8.37	400.3	256.5	42.1	101.7	293	69	45	1.5	2.15	2.47	37"	66
A	127.4	.369	.604	22.81	19.00	9.35	416.4	259.4	51.0	106.0	298	67	42	1.6	2.02	2.47	38"	70
R	129.7	.369	.605	22.75	19.00	9.43	418.6	259.2	51.0	108.4	305	71	45	1.6	1.93	2.39	38"	73
S	130.5	.370	.605	22.81	18.94	9.45	419.3	258.9	51.0	109.4	313	73	47	1.6	1.87	2.41	38"	76
Apollo Hump 41" Steel Iron Shafts												(no tip trimming)						
R	111.7	.371	.584	20.88	18.56	9.10	409.7	259.2	51.0	99.5	283	61	46	1.3	2.07	2.19	38"	68
S	117.1	.370	.580	20.69	18.44	9.16	411.0	255.3	51.0	104.7	294	67	49	1.4	1.87	2.06	38"	72
Apollo Shadow 40" A&L Steel Iron Shaft												(tip trimming L-flex 1.5", A-flex 2.5")						
L	98.3	.370	.578	20.94	18.69	8.00	390.4	261.0	42.1	87.3	271	61	36	1.7	2.50	2.78	37"	58
A	103.8	.370	.580	21.19	19.38	9.06	408.4	262.8	51.0	94.6	277	62	34	1.8	2.38	2.69	38"	62
Apollo Shadow 42" R&S Steel Iron Shaft												(tip trimming R-flex 1.5", S-flex 3.5")						
R	126.1	.370	.605	22.13	19.25	9.50	420.6	260.2	51.0	109.4	319	77	44	1.8	1.88	2.15	38"	77
S	127.1	.368	.607	22.13	19.19	9.54	422.1	259.6	51.0	111.5	331	80	49	1.6	1.74	2.15	38"	82
Apollo Spectre Lite 40" A&L Steel Iron Shaft												(tip trimming L-flex 1.5", A-flex 2.5")						
L	98.6	.371	.579	20.75	18.50	8.01	390.6	261.1	42.1	87.4	287	68	43	1.6	2.15	2.43	37"	65
A	101.5	.372	.579	20.75	19.00	8.92	404.6	260.0	51.0	93.6	291	67	40	1.7	2.06	2.37	38"	69
Apollo Spectre Lite 42" R&S Steel Iron Shaft												(tip trimming R-flex 1.5", S-flex 3.5")						
R	109.9	.369	.601	22.00	19.19	9.02	407.5	260.6	51.0	95.9	312	72	41	1.8	1.96	2.29	38"	73
S	110.3	.369	.601	22.00	19.13	9.10	409.7	260.3	51.0	98.4	324	75	47	1.6	1.78	2.22	38"	78
Apollo Standard Stepless 40" A&L Steel Iron Shaft												(tip trimming L-flex 1", A-flex 2")						
L	126.6	.371	.581	20.13	17.94	8.65	408.0	253.3	42.1	112.6	301	71	51	1.4	1.91	2.13	37"	70
A	127.4	.373	.582	20.13	18.38	9.57	116.6	255.3	51.0	116.6	303	70	46	1.5	1.89	2.10	38"	73
Apollo Standard Stepless 41" R&S Steel Iron Shaft												(tip trimming R-flex 1", S-flex 2")						
R	122.0	.372	.604	21.06	18.81	9.40	418.0	257.7	51.0	109.3	306	71	46	1.5	1.92	2.10	38"	74
S	123.4	.372	.605	20.94	18.69	9.44	418.9	257.4	51.0	110.5	316	73	50	1.5	1.81	2.06	38"	77
Apollo Standard Stepped 39" A&L Iron Shaft												(tip trimming L-flex 1", A-flex 2")						
L	117.6	.368	.579	20.31	18.50	8.69	409.0	259.8	42.1	107.1	292	70	46	1.5	2.02	2.23	37"	67
A	119.0	.371	.580	20.44	19.19	9.57	423.0	259.6	51.0	112.4	297	70	46	1.6	2.00	2.19	38"	72
Apollo Standard Stepped 40" R&S Iron Shaft												(tip trimming R-flex 1", S-flex 2")						
R	121.5	.370	.601	20.88	19.19	9.49	420.4	258.7	51.0	110.7	292	68	42	1.6	2.03	2.17	38"	69
S	124.0	.372	.603	21.00	19.19	9.61	424.1	258.9	51.0	114.2	302	69	44	1.6	1.90	2.14	38"	72

Flex	Raw Weight (g)	Tip Dia. (in.)	Butt Dia. (in.)	BP1 (in.)	BP2 (in.)	BP3 (in.)	Static Weight (g)	Head Weight (g)	Grip Weight (g)	Shaft Weight (g)	Freq. (cpm)	Butt Deflect. (oz.)	Tip Deflect. (.oz.)	T/B Ratio	Torque Cut (deg)	Torque Raw (deg)	Length -Bore Type	DSFI
Apollo Shadow 45" A&L Steel Wood Shaft															(tip trimming L-flex 0", A-flex 1")			
L	116.6	.334	.581	23.94	22.13	11.99	344.2	195.4	42.1	106.7	238	32	12	2.7	3.33	3.38	43"-M2	79
A	119.3	.334	.580	23.56	23.56	13.08	360.7	197.9	51.0	111.8	242	31	11	2.8	3.15	3.33	44"-M2	84
Apollo Shadow 47" R&S Steel Wood Shaft															(tip trimming R-flex 0", S-flex 2")			
R	131.3	.333	.604	25.13	22.81	13.37	366.9	198.6	51.0	117.3	248	35	12	2.9	3.04	3.14	44"-M2	88
S	132.3	.334	.600	25.13	22.75	13.44	368.6	197.8	51.0	119.8	262	38	14	2.7	2.72	3.14	44"-M2	96
Apollo Spectre Lite 45" A&L Steel Wood Shaft															(tip trimming L-flex 0", A-flex 1")			
L	101.0	.336	.580	23.69	22.00	11.35	331.7	197.1	42.1	92.5	223	25	10	2.5	3.58	3.70	43"-M2	71
A	102.4	.336	.580	23.69	22.63	12.56	349.9	201.9	51.0	97.0	227	28	9	3.1	3.44	3.68	44"-M2	76
Apollo Spectre Lite 47" R&S Steel Wood Shaft															(tip trimming R-flex 0", S-flex 2")			
R	114.5	.334	.602	24.94	22.75	12.79	354.6	200.9	51.0	102.7	254	36	11	3.3	3.12	3.23	44"-M2	89
S	115.8	.334	.603	24.94	22.58	12.88	356.5	200.2	51.0	105.3	265	39	13	3.0	2.86	3.23	44"-M2	96
Apollo Standard Stepless 45" A&L Steel Wood Shaft															(tip trimming L-flex 0", A-flex 1")			
L	127.3	.337	.580	23.56	21.88	12.41	352.9	193.7	42.1	117.1	244	34	16	2.1	3.12	3.21	43"-M2	84
A	131.0	.337	.579	23.38	22.19	13.46	369.1	193.9	51.0	124.2	247	34	15	2.3	2.95	3.17	44"-M2	89
Apollo Standard Stepless 46" R&S Steel Wood Shaft															(tip trimming R-flex 0", S-flex 1")			
R	132.5	.335	.602	23.94	22.25	13.44	368.6	195.0	51.0	122.6	254	36	15	2.4	2.95	3.03	44"-M2	92
S	135.3	.335	.608	24.00	22.31	13.57	371.5	195.0	51.0	125.5	260	38	17	2.2	2.85	3.04	44"-M2	95
Apollo Standard Stepped 45" A&L Wood Shaft															(tip trimming L-flex 0", A-flex 1")			
L	125.7	.336	.578	23.44	21.75	12.32	351.0	193.6	42.1	115.3	243	34	17	2.0	3.08	3.12	43"-M2	84
A	129.9	.337	.579	23.63	22.44	13.48	369.4	195.2	51.0	123.2	250	36	16	2.3	2.93	3.10	44"-M2	91
Apollo Standard Stepped 46" R&S Wood Shaft															(tip trimming R-flex 0", S-flex 1")			
R	128.5	.335	.603	24.38	22.63	13.34	366.3	197.2	51.0	118.1	253	34	14	2.4	2.98	3.00	44"-M2	90
S	129.5	.335	.602	24.19	22.50	13.40	367.7	196.5	51.0	120.2	259	37	15	2.5	2.81	2.99	44"-M2	94